

CLAYTON CHEMICAL CO. -- C132 DEVELOPER STARTER (174-0000) -- 6750-00-165-7189

=====
Product Identification
=====

Product ID:C132 DEVELOPER STARTER (174-0000)

MSDS Date:07/27/1992

FSC:6750

NIIN:00-165-7189

MSDS Number: BDDXP

=== Responsible Party ===

Company Name:CLAYTON CHEMICAL CO.

Address:13310 FIGUEROA STREET

City:LOS ANGELES

State:CA

ZIP:90061

Country:US

Info Phone Num:310-538-9530

Emergency

Phone Num:310-538-9530/800-424-9300(CHEMTREC)

Preparer's Name:JOHN B. TAYLOR

CAGE:61803

=== Contractor Identification ===

Company Name:CLAYTON CHEMICAL CO.

Address:13310 S. FIGUEROA STREET

Box:City:LOS ANGELES

State:CA

ZIP:90061

Country:US

Phone:310-538-9530/800-424-9300(CHEMTREC)

CAGE:61803

Company Name:CLAYTON CHEMICAL CO., A DIV OF VARICHEM CORP

Address:RR 1

Box:276-Z

City:HEATHSVILLE

State:VA

ZIP:22473

Country:US

Phone:703-759-9399

CAGE:6W820

=====
Composition/Information on Ingred

ients =====

Ingred Name:SODIUM BROMIDE
CAS:7647-15-6
RTECS #:VZ3150000
Fraction by Wt: 30-40%

Ingred Name:ACETIC ACID (SARA III)
CAS:64-19-7
RTECS #:AF1225000
Fraction by Wt: 1-5%
OSHA PEL:10 PPM
ACGIH TLV:10 PPM/15 STEL; 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:WATER
CAS:7732-18-5
RTECS #:ZC0110000
Fraction by Wt: 55-70%

===== Hazards Identification =====

LD50 LC50 Mixture:NOT SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalati

on:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:MAY CAUSE EYE IRRITATION AND BURNING.

MAY CAUSE SKIN IRRITATION. INHALATION OF MIST COULD CAUSE
RESPIRATORY IRRITATION. MAY CAUSE SEVERE IRRITATION OF MUCOUS
MEMBRANES OR DIGESTIVE TRACT IF INGESTED.

Explanation of Carcinogenicity:PRODUCT CONTAINS NO INGREDIENTS

CURRENTLY CLASSIFIED AS CARCINOGENIC BY NTP, IARC OR OSHA.

Effects of Overexposure:EYE IRRITATION, EYE

BURNING, SKIN IRRITATION,

SKIN BURNING, RESPIRATORY IRRITATION, MUCOUS MEMBRANE IRRITATION,
DIGESTIVE TRACT IRRITATION.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:EYES: IMMEDIATELY FLUSH WITH WATER FOR 15 MINUTES; OBTAIN
MEDICAL ATTENTION. SKIN: FLUSH AFFECTED AREAS PROMPTLY WITH WATER
FOR 15 MINUTES. REMOVE CONTAMINATED CLOTHING. INHALATION: FOR
OVEREXPOSURE, REMOVE TO

FRESH AIR. INGESTION: DRINK MILK OR WATER.
INDUCE VOMITING. OBTAIN IMMEDIATE MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point:NOT FLAMMABLE

Lower Limits:NOT GIVEN

Upper Limits:NOT GIVEN

Extinguishing Media:ANY EXTINGUISHING MEDIA APPLICABLE TO SURROUNDING AREA.

Fire Fighting Procedures:EVACUATE PERSONNEL TO A SAFE AREA. KEEP PERSONNEL REMOVED AND UPWIND OF FIRE. WEAR SELF-CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:WHEN HEATED TO DECOMPOSITION EMISSION OF TOXIC FUMES IS POSSIBLE.

===== Accidental Release Measures =====

Spill Release Procedures:USE APPROPRIATE PERSONAL PROTECTIVE EQUIPMENT DURING CLEANUP. DIKE SPILL. PREVENT LIQUID FROM ENTERING SEWER, WATERWAYS OR LOW AREA. SOAK UP WITH SAND, OILDRY OR OTHER ABSORBENT MATERIAL. SPILL MAY BE NEUTRALIZED WITH POWDERED SODIUM CARBONATE.

Neutralizing Agent:SODIUM CARBONATE.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN WELL VENTILATED AREA. KEEP CONTAINER TIGHTLY CLOSED. DO NOT STORE WITH INCOMPATIBLE MATERIALS.

Other Precautions:DO NOT STORE OR CONSUME FOOD,DRINK OR TOBACCO IN AREA WHERE THEY MAY BECOME CONTAMINATED WITH THIS MATERIAL.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:SUFFICIENT ROOM VENTILATION.

Ventilation:ADEQUATE MECHANICAL (GENERAL) VENTILATION

Protective Gloves:

PVC

Eye Protection:EYEGLASSES WITH SIDE SHIELDS

Other Protective Equipment:PROTECTIVE APRON, EMERGENCY SHOWER AND EYEWASH STATION

Work Hygienic Practices:WASH WITH SOAP AND WATER AFTER HANDLING PRODUCT AND BEFORE EATING DRINKING OR SMOKING.

Supplemental Safety and Health

FORMULA #424-12A.

===== Physical/Chemical Properties =====

HCC:C3

Boiling Pt:B.P. Text:>212F,>100C

Melt/Freeze Pt:M.P/F.P Text:NOT GIVEN

Vapor Pres:NOT GIVEN

Vapor Density:NOT GIVEN

Spec Gra

vity:1.005

pH:1.80

Evaporation Rate & Reference:NOT GIVEN

Solubility in Water:COMPLETE

Appearance and Odor:CLEAR, COLORLESS LIQUID, MILD VINEGAR ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NONE SPECIFIED BY MANUFACTURER.

Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products:NONE SPECIFIED BY MANUFACTURER.

Conditions to Avoid Polymerization:MAY OCCUR. NO CONDITIONS TO AVOID

SP

ECIFIED BY MANUFACTURER.

===== Disposal Considerations =====

Waste Disposal Methods:RECOVER NONUSABLE FREE LIQUID AND/OR
CONTAMINATED WATER AND DISPOSE OF IN AN APPROVED AND PERMITTED
TREATMENT SYSTEM. REMOVE NONUSABLE SOLID MATERIAL AND/OR
CONTAMINATED SOIL, FOR DISPOSAL IN AN APPROVED AND PERMITTED
LANDFILL.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Depar

tment

of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.