

LENMAR INC -- G-660 -- 8010-00-166-1667

===== Product Identification =====

Product ID:G-660

MSDS Date:01/01/1985

FSC:8010

NIIN:00-166-1667

MSDS Number: BDDZP

=== Responsible Party ===

Company Name:LENMAR INC

Address:33 N WARWICK AVENUE

City:BALTIMORE

State:MD

ZIP:21223-1413

Country:US

Info Phone Num:410-947-2300 / FAX 410-566-4817

Emergency Phone Num:410-947-2300

CAGE:12904

=== Contractor Identif

ication ===

Company Name:LENMAR INC

Address:33 N WARWICK AVENUE

Box:City:BALTIMORE

State:MD

ZIP:21223-1413

Country:US

Phone:410-947-2300

CAGE:12904

===== Composition/Information on Ingredients =====

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS:78-93-3

RTECS #:EL6475000

OSHA PEL:200 PPM/300 STEL

ACGIH TLV:200 PPM/300STEL 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:N-BUTYL ACETATE (SARA III)

CAS:123-86-4

RTECS #:AF7350000

OSHA PEL:150 PPM/

200 STEL  
ACGIH TLV:150 PPM/200STEL;9192  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:ACETONE (SARA III)  
CAS:67-64-1  
RTECS #:AL3150000  
OSHA PEL:1000PPM  
ACGIH TLV:750PPM/1000STEL;9293  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:TOLUENE (SARA III)  
CAS:108-88-3  
RTECS #:XS5250000  
OSHA PEL:200 PPM/150 STEL  
ACGIH TLV:50 PPM; 9293  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)  
CAS:1330-20-7  
RTECS #:ZE2100000  
OSHA PEL:100 PPM/150 STEL  
A  
CGIH TLV:100 PPM/150STEL;9192  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

===== Hazards Identification =====

Effects of Overexposure:EYE,THROAT,SKIN,LUNG  
IRRITANT;HEADACHE;DIZZINESS;COMA.

===== First Aid Measures =====

First Aid:SKIN:WASH WELL. EYES:FLUSH W/WATER.INHAL:REMOVE TO FRESH  
AIR.GIVE ARTIF.RESP.IF NEEDED.REMOVE CONTAMINATED  
CLOTHING.INGEST:DO NOT INDUCE VOMIT;TAKE TO DR. IMMEDIATELY.

=====

==== Fire Fighting Measures =====

Flash Point:18F,-7C SCC

Lower Limits:1.1

Upper Limits:2.6

Extinguishing Media:FOAM,DRY CHEM.,CARBON DIOXIDE,WATER FOG

Unusual Fire/Explosion Hazard:AVOID FIRE,HEAT,SPARKS,IGNITION  
SOURCES,STORAGE IN DIRECT SUNLIGHT

===== Accidental Release Measures =====

Spill Release Procedures:VENTILATE AREA MECHANICALLY,KEEP FROM  
FLAME,FIRE,SPARKS, IGNITION SOURCES;DO NOT BREATHE VAPORS;CLEAN UP  
WITH ABSORBENT MAT

ERIAL;CALL FIRE AND HEALTH AGENCIES;PUT LEAKING  
CONTAINERS OUTDOORS.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED,UPRIGHT FROM  
FIRE,FLAME,SPARKS,IGNITION SOURCES, DIRECT SUNLIGHT;NO  
SMOKING;AROUND CONTAINERS WHEN POURING

Other Precautions:DO NOT TRANSFER TO UNMARKED CONTAINERS;EXTINGUISH  
PILOT LIGHTS;USE NON-SPARKING TOOLS; DO NOT APPLY TO HOT SURFACES  
USE ADEQUATE VENTILATION.

===== Ex  
posure Controls/Personal Protection =====

Respiratory Protection:MECHANICAL FILTER RESPIRATOR OR CHEMICAL  
MECHANICAL FILTERS

Ventilation:LOCAL EXHAUST

Protective Gloves:YES

Eye Protection:GLASSES,SAFETY

Supplemental Safety and Health

ALSO CONTAINS CYCLOHEXANONE(5PCT.)NIOSH NO.GW1050000:BOILING RANGE IS  
133-281F. (ACETONE-XYLENE)

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:133F,56 C

Percent Volatiles by Volume:83.0

=====

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

OXYGEN AND STRONG OXIDANTS

Hazardous Decomposition Products: CARBON DIOXIDE/MONOXIDE

Conditions to Avoid Polymerization: TEMP. OVER 150F, HEAT, SPARKS, FLAME, HOT SURFACES.

===== Disposal Considerations =====

Waste Disposal Methods: LOCAL, STATE AND FED. LAWS. USE SANITARY

LANDFILL; DO NOT INCINERATE CLOSED CONTAINERS; SEAL EMPTY DRUMS TIGHTLY.

Disclaimer (pr

vided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.