

EASTMAN KODAK COMPANY(PHIPPS PRODUCTS-DISTRIBUTOR) -- TT-M-268,METHYL ISOBUTYL KETONE -- 6810-00-180-5976

===== Product Identification =====

Product ID:TT-M-268,METHYL ISOBUTYL KETONE
MSDS Date:01/01/1985
FSC:6810
NIIN:00-180-5976
MSDS Number: BDFYY
=== Responsible Party ===
Company Name:EASTMAN KODAK COMPANY(PHIPPS PRODUCTS-DISTRIBUTOR)
Address:343 STATE STREET
City:ROCHESTER
State:NY
ZIP:14650
Country:US
Info Phone Num:716-722-5151
Emergency Phone Num:716-722-5151
CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS
Address:343 STATE ST
Box:City:ROCHESTER
State:NY
ZIP:14650-1115
Country:US
Phone:716-722-5151/(800) 242-2424
CAGE:19139

===== Composition/Information on Ingredients =====

Ingred Name:METHYL ISOBUTYL KETONE (SARA III)
CAS:108-10-1
RTECS #:SA9275000
Fraction by Wt: 100%
OSHA PEL:100 PPM/75 STEL
ACGIH TLV
:50 PPM/75 STEL; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

===== Hazards Identification =====

Effects of Overexposure:IRRITANT TO EYES & RESPIRATORY TRACT,HIGH
CONCS-NARCOSIS,DEFATTING OF SKIN, IRRITATIONS >200 PPM.

===== First Aid Measures =====

First Aid:SKIN CONTACT: FLUSH AFFECTED AREAS THOROUGHLY WITH WATER. EYE
CONTACT: IRRIGATE IMMEDIATELY & THOROUGHLY WITH WATER FOR 15
MINUTES & GET MEDICAL ATTEN

TION. INHALATION: REMOVE FROM EXPOSURE &
TREAT SYM PTOMATICALLY.

===== Fire Fighting Measures =====

Flash Point:60F

Lower Limits:1.22

Upper Limits:7.96

Extinguishing Media:DRY CHEMICAL, CO*2

Fire Fighting Procedures:USE WATER SPRAY TO COOL CONTS,WEAR
SELF-CONT.BREATHER,GOGGLE

Unusual Fire/Explosion Hazard:MAY TRAVEL A CONSIDERABLE DISTANCE TO A
SOURCE OF IGNITION & FLASH BACK.

===== Handling and Storage =====

Ha

ndling and Storage Precautions:ISOLATE & SEAL FIRMLY THE CONTAINERS
TO AVOID LEAKAGE & STORE IN COOL, DARK & WELL-VENTILATED PLACES.
OUTDOOR OR DETACHED STORAGE IS PREFERABLE.

Other Precautions:WEAR RUBBER GLOVES,FACE SHIELD,OVERALLS.PREPARE
MULTI-PURPOSE GAS MASK.AVOID EYE & PROLONGED OR REPEATED SKIN
CONTACT.AVOID INHALATION OF HIGH CONCS OF VAPOR.USE W/VENTILATION
TO MAINTAIN