View NSN Online: https://aerobasegroup.com/nsn/9150-00-180-6266

EMERY CHEMICALS, DIV NATIONAL DISTILLERS&CHEM CORP -- EMERY 2952 SYNTHETIC TURBINE LUBRICANT -- 9150-00-180-6266

============= Product Identification ==================

Product ID:EMERY 2952 SYNTHETIC TURBINE LUBRICANT

MSDS Date:06/18/1986

FSC:9150

NIIN:00-180-6266

MSDS Number: BDGCL === Responsible Party ===

Company Name: EMERY CHEMICALS, DIV NATIONAL DISTILLERS&CHEM CORP

Address:4900 ESTE AVENUE

City:CINCINNATI

Stat e:OH

ZIP:45232 Country:US

Emergency Phone Num: (513) 482-2297

CAGE:EO063

=== Contractor Identification ===

Company Name: EMERY CHEM DIV OF NATIONAL DISTILLERS & CHEM CORP

Address:11501 NORTHLAKE DR

Box:429557

City:CINCINNATI

State:OH

ZIP:45249-1619

Country:US

Phone:513-482-2297

CAGE:33358

Company Name: EMERY CHEMICALS, DIV NAT'L DISTILLERS

CAGE:EO063

======= Composition/Information on Ingredients ========

Ingred Name: PENTAERYTHRITOL ESTERS, TECH

Ingred Name: ADDITIVES

===== Hazards Identification ==============
Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Effects of Overexposure:LOW TOXICITY, NOT EYE,SKN IRRT.
======================================
First Aid:INHAL:RMV TO FRESH AIR. IF NOT BRTHNG GIVE CPR; IF BRTHNG DIFF GIVE OXYGEN. EYE:IMMED FLUSH W/PLENTY OF WATER. SKIN:WASH W/SOAP & WATER. RMV CONTAM CLTHG & SHOES. INGEST:DO NOT INDUCE VOMIT
. NOTHG BY MOUTH IF UNCONSC. GET MEDICAL ATTN.
======================================
Flash Point Method:COC Flash Point:490F/254C Extinguishing Media:WATER SPRAY,DRY CHEMICAL,FOAM,OR CARBON DIOXIDE.WATER INEFFECTIVE.USE WATER TO COOL CONTAINERS.ALSO WATER SPRAY TO DISPR Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS IN THE POSITIVE-PRESSURE MODE WITH A FULL FACEPIECE WHEN THERE IS A POSSIBILITY OF EXPOSURE TO SMOKE. Unusual Fire /Explosion Hazard:NONE ==================================
Spill Release Procedures:USE SCBA & FULL BODY PROTECTION. CONTAIN SPILL,PUMP OR SCOOP INTO CLOSABLE CONTAINERS.COLLECT RESIDUAL SPILLAGE W/ABSORBENT. REMOVE OIL SLICK W/BIODEGRADABLE DETERGENT & WATER TO SEWER.
======================================
Handling and Storage Precautions:STORE IN COOL DRY AREA Other Precautions:NONE GIVEN.
====== Exposure Con

trols/Personal Protection =======
Respiratory Protection:USE MIST RESPIRATOR AS REQD Ventilation:GENERAL MECHANICAL Protective Gloves:IMPERVIOUS Eye Protection:SAFETY GLASSES. Other Protective Equipment:NONE GIVEN Supplemental Safety and Health MSDS DTD 18JUN86
========= Physical/Chemical Properties ==========
HCC:V6 Boiling Pt:B.P. Text:>540F; 282C Spec Gravity:0.997 Solubility in Water:NEGLIGIBLE Appearance and Odor:AMBER LIQUID, TYPICAL PETROLEUM ODOR.
======= Stability and Reactivity Data =========
Stability Indicator/Materials to Avoid:YES OXIDIZERS Stability Condition to Avoid:EXTREME HEAT, IGNITION SOURCES. Hazardous Decomposition Products:CARBON OXIDES
======= Disposal Considerations ==========
Waste Disposal Methods:RECLAIM OR INCINERATE IAW ALL LAWS & REGS. DO NOT LANDFILL
Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.