

AMERICAN OIL AND SUPPLY CO -- MIL-L-23699C (1) QA TURBINE LUBRICANT -- 9150-00-180-6266

=====
Product Identification
=====

Product ID:MIL-L-23699C (1) QA TURBINE LUBRICANT

MSDS Date:05/01/1989

FSC:9150

NIIN:00-180-6266

MSDS Number: BDGCN

=== Responsible Party ===

Company Name:AMERICAN OIL AND SUPPLY CO

Address:238 WILSON AVE

City:NEWARK

State:NJ

ZIP:07105-3824

Country:US

Info Phone Num:201-589-02

63

Emergency Phone Num:201-589-0250

Preparer's Name:LAB MANAGER

CAGE:92895

=== Contractor Identification ===

Company Name:AMERICAN OIL AND SUPPLY CO

Address:239 WILSON AVE

City:NEWARK

State:NJ

ZIP:07105-3824

Country:US

Phone:201-589-0250

CAGE:92895

=====
Composition/Information on Ingredients
=====

Ingred Name:POLYOL ESTER

Other REC Limits:NONE SPECIFIED

Ingred Name:INFORMATION WITHHELD AS A TRADE SECRET.

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Health Hazards Acute and Chronic:MILD IRRITATION AND REDNESS TO THE EYES. MILD IRRITATION TO THE SKIN. NASAL IRRITATION, HEADACHE, POSSIBLE UNCONCIOUSNESS IF INHALED. NAUSEA, VOMITING, DIARRHEA, GASTROINTESTINAL IRRITATION IF INGESTED.

Explanation of Carcinogenicity:THIS QUESTION IS NOT ADDRESSED BY THE MANUFACTURER.

Effects of Overexposure:SEE HEALTH HAZARDS.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
===== First Aid Measures =====

First Aid:INHALATION:REMOVE TO FRESH AIR. RESUSCITATE IF NOT BREATHING. GET MEDICAL ATTENTION. EYES:IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR 15 MINUTES HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION. SKIN:REMOVE CONTAMINATED CLOTHING. WASH WITH SOAP AND WATER. IF IRRITATION PERSISTS, GET MEDICAL ADVICE. INGESTION:DO NOT INDUCE VOMITING. GIVE NOTHING BY MOUTH IF UNCONSCIOUS. GET IMMEDIATE MEDICAL ATTENTION.

=====
===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:490F,254C

Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL.

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY. CONTAIN RUNOFF.

Unusual Fire/Explosion Hazard:DO NOT USE DIRECT STREAM OF WATER. MATERIAL MAY FLOAT AND REIGNITE.

==

=====
===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE ALL SOURCES OF IGNITION. PROVIDE ADEQUATE VENTILATION. RECOVER FREE LIQUID. ADD ABSORBENT TO SPILL AREA. COLLECT ABSORBENT. KEEP PRODUCT OUT OF WATERWAYS.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL, DRY, WELL VENTILATED AREA. KEEP CONTAINERS TIGHTLY CLOSED WH

EN NOT IN USE. PROTECT

CONTAINERS FROM PHYSICAL DAMAGE.

Other Precautions:DO NOT TAKE INTERNALLY. DO NOT BREATHE MIST. AVOID PROLONGED OR REPEATED BREATHING OF VAPOR. AVOID CONTACT WITH EYES. USE WITH ADEQUATE VENTILATION. WASH THOROUGHLY AFTER HANDLING. EMPTY CONTAINERS CAN BE HAZARDOUS DUE TO RESIDUES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:EXHAUST FAN RECOMMENDED.

Ventilation:MECHANICAL (GENERAL) ROOM VENTILATION IS NORMALLY ADEQUATE.

LOCAL EXHAUST MAY BE REQUIRED IF WORK AREA NOT VENTED.

Protective Gloves:RUBBER

Eye Protection:SAFETY GOGGLES WITH OPTIONAL FACE SHIELD

Other Protective Equipment:EYE WASH STATION AND SAFETY SHOWER.

INDUSTRIAL-TYPE WORK CLOTHING AND APRON AS REQUIRED.

Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHING OR FOOTWEAR.

Supplemental Safety and Health

AVOID PROLONGED OR REPEATED EXPOSURE. DO NOT GET ON SKIN OR IN EYES. DO

NOT BREATHE VAPORS OR MISTS.

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:>550F,>288C

Vapor Pres:10

Spec Gravity:0.980

Evaporation Rate & Reference: