

DEFT CHEMICAL COATINGS -- LXP-3015 BASE,BROWN 20400,POLYURETHANE -- 8010-00-181-7049

=====
Product Identification
=====

Product ID:LXP-3015 BASE,BROWN 20400,POLYURETHANE

MSDS Date:01/01/1985

FSC:8010

NIIN:00-181-7049

Kit Part:Y

MSDS Number: BDGGW

=== Responsible Party ===

Company Name:DEFT CHEMICAL COATINGS

Address:17451 VON KARMAN AVE

City:IRVINE

State:CA

ZIP:92714-6205

Country:US

Emergency Phon

e Num:949-474-0400

CAGE:EO418

=== Contractor Identification ===

Company Name:DEFT CHEMICAL COATINGS

CAGE:EO418

Company Name:DEFT, INC.

Address:17451 VON KARMAN AVE

City:IRVINE

State:CA

ZIP:92614

Country:US

Phone:949-474-0400

CAGE:33461

=====
Composition/Information on Ingredients
=====

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS:78-93-3

RTECS #:EL6475000

Fraction by Wt: 30.0%

OSHA PEL:200 PPM/300 STEL

ACGIH TLV:200 PPM/300STEL 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:2-ETHOXYETHYL ACETATE (CELLOSOLVE ACETATE) (EGEEA)

CAS:111-15-9

RTECS #:KK8225000

Fraction by Wt: 10.0%

OSHA PEL:S,100 PPM

ACGIH TLV:S, 5 PPM; 9192

Ingred Name:N-BUTYL ACETATE (SARA III)

CAS:123-86-4

RTECS #:AF7350000

Fraction by Wt: 10.0%

OSHA PEL:150 PPM/200 STEL

ACGIH TLV:150 PPM/200STEL;9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:DIBUTYL TIN DILAURATE (AS TIN)

CAS:77-58-7

RTECS #:WH7000000

Fraction by Wt: 0.05%

OSHA PEL:S, 0.1 MG/M3

ACGIH

TLV:S, 0.1 MG/M3; 8990

Ingred Name:CHLOROBENZENE (SARA III)

CAS:108-90-7

RTECS #:CZ0175000

Fraction by Wt: 5.0%

OSHA PEL:75 PPM

ACGIH TLV:10 PPM; 9192

EPA Rpt Qty:100 LBS

DOT Rpt Qty:100 LBS

=====
===== Hazards Identification =====

Effects of Overexposure:EYES:MODERATE IRRIT;SKIN:POSSIBLE IRRIT BY
SOLVENTS;INH:SOLVENT VAPORS CAN CAUSE IRRIT OR NARCOSIS.

=====
===== First Aid Measures =====

First Aid:SKIN:WIPE OFF WITH A RAG TH

EN THOROUGH RINSING W/H*20 &
WASHING W/MILD SOAP AND WATER;EYES:FLUSH W/WATER FOR AT LEAST 10
MIN & CONSULT AN EYE PHYSICIAN;INH:REMOVE TO FRESH AIR.GIVE
CPR/OXYGEN IF NEEDED.

=====
Fire Fighting Measures
=====

Flash Point:28F(-2.2C)-TOC
Extinguishing Media:CARBON DIOXIDE,FOAM OR DRY CHEMICALS.
Fire Fighting Procedures:USE SELF-CNTND BRTHNG APP;CAN USE H*20
SPRAY/FOG EFFECTIVLY.
Unusual Fire/Explosion Hazard:CAUTION AGAINST APPLICATION TO HOT
SURFACES & USE IN AREASWHERE SOURCES OF IGNITION MAY BE PRESENT.

=====
Accidental Release Measures
=====

Spill Release Procedures:EVACUATE UNPROTCTD PERSONS.ELIM IGN
SOURCES.USE SAFETY EQUIP.VENTLATE AREA.STOP LEAK W/O RISK;ABSORB SM
SPILL W/OIL ABSORBING COMPD/RAGS.PER MFR,FLUSH AREA W/LG AMT
H*20;DIKE LG SPILL.PUMP LIQ TO SALV AGE TANK.SHOVEL UP RESIDUE INTO
COVEREDCONTNRS.

=====
Handling and Storage
=====

H
andling and Storage Precautions:STORE IN COOL,DRY,WELL VETNILATED,LOW
FIRE RISK AREA.KEEP CONTAINERS TIGHTLY CLOSED.PROTECT FROM PHYSICAL
DAMAGE.
Other Precautions:AVOID PROLONGED INHALATION OF VAPORS.IF VENTILATION
IS POOR,USE A FRESH AIR SUPPLY MASK.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:GOOD VENTILATION;HOWEVER,USE NIOSH APPRVD RESP
IF NEEDED FOR PAINTS.
Ventilation:USE ADEQUATE VENTILATION W/EXHAUST FAN
Protective Gloves:
NEOPRENE/RUBBER
Eye Protection:SAFETY/CHEM GOGG W/SHIELD
Other Protective Equipment:USE CARTRIDGE TYPE RESPIRATOR W/PARTICULATE
FILTERS.
Supplemental Safety and Health
BASE ALSO CONTAINS DESPERSING AGENT 1%, ANTI-MAR AGENT 1.0
Spec Gravity:1.1553
Evaporation Rate & Reference: