

DEFT CHEMICAL COATINGS -- 03-GN-28 BASE, GREEN 34079, POLYURETHANE -- 8010-00-181-8155
===== Product Identification =====

Product ID:03-GN-28 BASE, GREEN 34079, POLYURETHANE

MSDS Date:01/01/1985

FSC:8010

NIIN:00-181-8155

Kit Part:Y

MSDS Number: BDGQS

=== Responsible Party ===

Company Name:DEFT CHEMICAL COATINGS

Address:17451 VON KARMAN AVE

City:IRVINE

State:CA

ZIP:92714-6205

Country:US

CAGE:EO418

===

Contractor Identification ===

Company Name:DEFT CHEMICAL COATINGS

CAGE:EO418

Company Name:DEFT, INC.

Address:17451 VON KARMAN AVE

City:IRVINE

State:CA

ZIP:92614

Country:US

Phone:949-474-0400

CAGE:33461

===== Composition/Information on Ingredients =====

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS:78-93-3

RTECS #:EL6475000

Fraction by Wt: 10.0%

OSHA PEL:200 PPM/300 STEL

ACGIH TLV:200 PPM/300STEL 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Nam

e:2-ETHOXYETHYL ACETATE (CELLOSOLVE ACETATE) (EGEEA)

CAS:111-15-9

RTECS #:KK8225000

Fraction by Wt: 19.2%

OSHA PEL:S,100 PPM

ACGIH TLV:S, 5 PPM; 9192

Ingred Name:POLYESTER RESIN

Fraction by Wt: 31.9%

Ingred Name:ETHYL ACETATE (CAS #141-78-6)

RTECS #:AH4250000

Fraction by Wt: 11.3%

ACGIH TLV:400 PPM

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 0.9%

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

=====

Hazards Identification =====

Effects of Overexposure:EYES:MODERATE IRRIT;SKIN:POSSOBEL IRRIT BY SOLVENTS;INH:SOLVENT VAPORS CAN CAUSE IRRIT OR NARCOSIS

===== First Aid Measures =====

First Aid:SKIN:WIPE OFF WITH A RAG THEN THOROUGH RINSINGW/H*2O & WASHING W/MILD SOAP AND WATER;EYES:FLUSH W/WATER FOR AT LEAST 10 MIN & CONSULT AN EYE PHYSICIAN;INH:REVOVE TO FRESH AIR.GIVE CPR/OXYGEN IF NEEDED .

===== Fire

Fighting Measures =====

Flash Point:28F(-2.2C)-OC

Lower Limits:1.6

Extinguishing Media:CO*2,DRY CHEM,FOAM

Fire Fighting Procedures:DO NOT USE H*2O STREAM ON FIRE,H*2O SPRAY/FOG IS MORE EFFCTV

Unusual Fire/Explosion Hazard:CAUTION AGAINST APPLICATION TO HOT SURFACES & USE IN AREA WHER SOURCES OF IGNITION MAY BE PRESENT

===== Accidental Release Measures =====

Spill Release Procedures:EVACUATE UNPROTECTED PERSONS.ELIM IGN SOURCES.USE SAFE

TY EQUIP. VENTLATE AREA. STOP LEAK W/O RISK. ABSORB SM
SPILL W/OIL ABSORBING COMPD/RAGS; DIKE LG SPILL. PUMP LIQ TO SALVAGE
TANK. SHOVEL UP RESIDUE INTO COVRD DRUMS; PER MFR, FLUSH AREA W/LG
AMOH*20.

=====
===== Handling and Storage =====

Handling and Storage Precautions: STORE IN COOL, DRY, WELL VENTILATED, LOW
FIRE RISK AREA. KEEP CONTNRS TIGHTLY CLOSED. KEEP AWAY FM HEAT, SPARK
OR OPEN FLAME.

Other Precautions: AVOID PROLONGED INHALATION OF VAP. PER MFR, WATER
SPRAY
OR FOG CAN BE USED EFFECTIVELY ON FIRE AND TO COOL HEAT/FIRE
EXPOSED CONTNRS.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection: GOOD VENTILATION IS NEEDED. HOWEVER USE NIOSH
APPRVD SCBA FOR PAINTS.

Ventilation: USE ADEWUATE VENTILATION USING EXHAUST FAN.

Protective Gloves: IMPERVIOUS

Eye Protection: SAFETY/CHEM GOGGLES.

Other Protective Equipment: AS REQD TO PREVENT PROLONGED OR REPRATED
CONTACT.

Work Hygienic Practices: TWO PART KIT. TH
IS IS BASE; ALSO CONTAINS: 0.1% OF

10% SOLN DIBUTYLTINDILAUATE, 0.1% OF 8% ZINC OCTOATE. 0.2% SILICONE
RESIN, 0

Supplemental Safety and Health

TWO PART KIT. THIS IS BASE; ALSO CONTAINS: 0.1% OF 10% SOLN
DIBUTYLTINDILAUATE, 0.1% OF 8% ZINC OCTOATE, 0.2% SILICONE RESIN,
0.5% DISPERSIONAID, 0.3% ANTI-SETTLING AGENT 9.95 SILICA; NOW SEE ADDL
DATA. KEY1 :F3.

=====
===== Physical/Chemical Properties =====

HCC:F3

Boiling Pt: B.P. Text: 175-331F

Vapor Pres: 15

Vapor Density: >

1.0

Spec Gravity:1.2

Evaporation Rate & Reference: