View NSN Online: https://aerobasegroup.com/nsn/8010-00-181-8284

AKZO COATINGS INC -- BOSTIK -- 8010-00-181-8284

Product ID:BOSTIK

MSDS Date:01/01/1985

FSC:8010

NIIN:00-181-8284

Kit Part:Y

MSDS Number: BDGTR === Responsible Party ===

Company Name: AKZO COATINGS INC

Address:434 W. MEATS STREET

City:ORANGE

State:CA ZIP:92661 Country:US

Info Phone Num:714-637-1750

Emergency Phone Num:714-637-1750; CHEMTREC 800-424-9300

CAGE:98502

=== Contractor Identification ===

Company Name: AKZO COATINGS INC

Address:434 W. MEATS STREET

Box:City:ORANGE

State:CA ZIP:92661 Country:US

Phone:714-637-1750; CHEMTREC 800-424-9300

CAGE:98502

======= Composition/Information on Ingredients ========

Ingred Name:SOLVENTS Fraction by Wt: 45.0% ACGIH TLV:100-400 PPM

Ingred Name: POLYESTER RESIN

Fraction by Wt: 19.1%

Ingred Name: ISOCYANATE PREPOLYMER (ALIPHATIC)

Fraction by Wt: 16.5%

Ingred Name:PIGMENTS Fraction by Wt: 19.2%

Ingred

Name:ADDITIVES Fraction by Wt: 0.2%
======================================
Effects of Overexposure:INHALE-IRRITATE NOSE & THROAT. MAY CAUSE NAUSEA OR VOMITING. MAY CAUSE EYE & SKIN IRRITATION.
======================================
First Aid:SKIN-WASH WITH SOAP & WATER. EYE FLUSH WITH WATER; CONSULT DOCTOR. INHALE-REMOVE TO FRESH AIR;CONSULT DOCTOR. INGESTION. INDUCE VOMITING;CONSULT DOCTOR.
============ Fire Fighting Measures ====================================
Flash Point:23F, -5C TCC Lower Limits:1.1 Extinguishing Media:CO2 OR DRY CHEM FOR SMALL; ALCOHOL FOAM FOR LARGE FIRES. Fire Fighting Procedures:WATER MAY E INEFFECTIVE.USE AIR SUPPLIED RESCUE EQUIPMENT Unusual Fire/Explosion Hazard:DO NOT APPLY TO HEATED SURFACES OR IN AREAS WHERE ELECTRICAL SPARKS MAY BE PRESENT ===================================
Handling and Storage Precautions:DO NOT STORE OR MIX WITH STRONG OXIDANTS. Other Precautions:DO NOT STORE OR MIX WITH STRONG OXIDANTS. ===================================

ET TLV Protective Gloves:SOLVEN RESISTAN Eye Protection:GOGGLES OR FACE SHIELD Other Protective Equipment:COVERALLS, APRON, NON-SPARKING SAFETY SHOES, ETC.
Supplemental Safety and Health
========= Physical/Chemical Properties ==========
HCC:F2
Boiling Pt:B.P. Text:175-320F
Vapor Density:>AIR
Evaporation Rate & Description R