

CROWN INDUSTRIAL PRODUCTS COMPANY -- YELLOW MARKING INK NO. 7272 -- 7510-00-183-7698

=====
Product Identification
=====

Product ID:YELLOW MARKING INK NO. 7272

MSDS Date:01/01/1985

FSC:7510

NIIN:00-183-7698

MSDS Number: BDGXD

=== Responsible Party ===

Company Name:CROWN INDUSTRIAL PRODUCTS COMPANY

Emergency Phone Num:815-6482424

CAGE:92381

=== Contractor Identification ===

Company Name:CROWN INDUS

TRIAL PRODUCTS CO

Address:HWY 47 N

Box:350

City:HEBRON

State:IL

ZIP:60034

Country:US

Phone:815-648-2424

CAGE:92381

=====
Composition/Information on Ingredients
=====

Ingred Name:ACETONE (SARA III)

CAS:67-64-1

RTECS #:AL3150000

Fraction by Wt: 24%

OSHA PEL:1000PPM

ACGIH TLV:750PPM/1000STEL;9293

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 9%

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qt

y:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:METHYLETHYL KETONE
RTECS #:PM7780500
Fraction by Wt: 4%
ACGIH TLV:200PPM

Ingred Name:ISOBUTYL ACETATE (SARA III)
CAS:110-19-0
RTECS #:AI4025000
Fraction by Wt: 4%
OSHA PEL:150 PPM
ACGIH TLV:150 PPM; 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)
CAS:78-93-3
RTECS #:EL6475000
Fraction by Wt: 19%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:200 PPM
ACGIH TLV:200 PPM/300STEL;9394
EPA Rpt Qty
:5000 LBS
DOT Rpt Qty:5000 LBS

=====
===== Hazards Identification =====

Effects of Overexposure:EYES:IRRITATION,BLURRED
VISION.SKIN:IRRITATION.INHALATION:UNCONSCIOUSNESS.INGESTION:NAUSEA,
DIARRHEA.

=====
===== First Aid Measures =====

First Aid:REMOVE TO FRESH AIR.GIVE ARTIFICIAL RESPIRATION IF
REQUIRED.EYES:COPIOUS WATER FLUSH.SKIN:WASH WITH SOAP AND WATER.IF
IRRITATION PERSISTS CONSULT PHYSICIAN.

=====

==== Fire Fighting Measures =====

Flash Point:HIGHLY FLAMMABLE

Lower Limits:1.8

Upper Limits:9.5

Extinguishing Media:CARBON DIOXIDE,FOAM, DRY CHEMICAL

Fire Fighting Procedures:TREAT AS COMPRESSED GAS

Unusual Fire/Explosion Hazard:HIGHLY VOLATILE WITH LOW LEVEL VAPORS
SUBJECT TO FLASH FIRES.

===== Accidental Release Measures =====

Spill Release Procedures:PROVIDE VENTILATION. REMOVE SOURCES OF
IGNITION.WIPE UP WITH INERT ABSORBENT MATERIAL,
PLACE IN SUITABLE
CONTAINER.

===== Handling and Storage =====

Handling and Storage Precautions:AVOID OPEN FLAME AND SPARK,SUNLIGHT
AND 120F TEMPERATURE.AVOID CONTACT WITH SKIN

Other Precautions:USE ONLY AS DIRECTED.INHALING CONTENTS MAY BE FATAL.

===== Exposure Controls/Personal Protection =====

Ventilation:LOCAL EXHAUST

Protective Gloves:OPTIONAL

Eye Protection:SAFETY GLASSES,SHIELD

Supplemental Safety and Health

SECTIONII-TX22750

00,PROPANE,

12%,TLV:1000PPM.ISOBUTANE-TZ24300000,12%,TLV:1000PPM

===== Physical/Chemical Properties =====

HCC:V3

Boiling Pt:B.P. Text:134F,57C

Vapor Pres:186

Vapor Density:>AIR

Spec Gravity:1.0008

Evaporation Rate & Reference:>ETHER

Solubility in Water:NEGLIGIBLE

Appearance and Odor:WHITE SHARP,PENETRATING RESIDUAL ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

St

ability Condition to Avoid:SPARKS AND OPEN FLAMES

Hazardous Decomposition Products:COMBUSTION YIELDS CO*2 AND CO.

===== Disposal Considerations =====

Waste Disposal Methods:AEROSOL CONTAINER UNDER PRESSURE.DO NOT PUNCTURE
OR INCINERATE.EXPELL PROPELLANT GAS AFTER CONTENTS ARE
EXHAUSTED.PLACE CONTAINER IN APPROPRIATE DISPOSAL.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of th

e Department

of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.