View NSN Online: https://aerobasegroup.com/nsn/9150-00-186-6668

WOLF'S HEAD OIL REFINING CORP. -- WOLF'S HEAD SPECIAL DUTY SERIES 3 OIL 10W --9150-00-186-6668

Product ID:WOLF'S HEAD SPECIAL DUTY SERIES 3 OIL 10W MSDS Date:01/01/1985 FSC:9150 NIIN:00-186-6668 MSDS Number: BDGZV === Responsible Party === Company Name:WOLF'S HEAD OIL REFINING CORP. Emergency Phone Num:(814) 677-6190 CAGE:DO762 === Contractor Identification ===

Company Name: PENNZOIL CO Address:700 MILIAM PENNZOIL PL Box:2967 City:HOUSTON State:TX ZIP:77252-2967 Country:US Phone:800-546-6227 CAGE:01326 Company Name: WOLF'S HEAD OIL COMPANY Address:P.O.BOX 808 Box:808 City:OIL CITY State:PA ZIP:16301-0808 Phone:713-236-6070 CAGE:DO762

Ingred Name: PETROLEUM HYDROCARBON (TLV OF 5 MG/CUM OIL MIST)

Effects of Overexpos

ure:SKIN: PRLNG EXPOS POSS DERMATITIS. INH: POSS ASPIR PNEUM FROM MIST. INGEST: POSS NAVSEA,LAXATIVE EFF

First Aid:EYES: FLUSH W/ CLEAN,WARM WATER. IF LIQ IS HOT TREAT FOR BURNS,CALL MD. SKIN: WIPE OFF EXCESS. WASH W/ SOAP/WATER. IF LIQ HOT, CHILL AREA, TREAT FOR SHOCK, CALL MD. INH: REMOVE TO FRESH AIR. IF NEC,GI VE ARTIF RESP,CALL MD. INGEST: DO NOT INDUCE VOMIT

================== Fire Fighting Measures

Flash Point:395F COC Extinguishing Media:FAOM, DRY CHEMICAL, CO*2 Fire Fighting Procedures:DO NOT USE WATER AS A SOLID STREAM - POSS FROTH,SPREAD FIRE Unusual Fire/Explosion Hazard:NONE

Spill Release Procedures:SM SPILLS: PICK UP W/ABSORBENTS (PAPER, CLOTH, DRY SAND, EARTH). LG SPILLS: USE PUMPS, BUCKETS, SHOVELS OR OTHER APPLICABLE TOOLS. PUT DRY SAND OR SPECIAL OIL ABSORBENTS ON OILY

AREAS TO HELP PREVENT ACCIDENTS.

Handling and Storage Precautions:FOR STORAGE & HANDLING REQUIREMENTS, SEE: 49 CFR 1910.106 - FLAM & COMBUST LIQUIDS NFPA NO. 30 - FLAM & COMBUSTIBLE LIQUIDS CODE.

Other Precautions:DO NOT TRANSFER TO UNMARKED CONTAINERS. FOLLOW DOT REGULATIONS DURING TRANSPORT. SHOULD A SITUATION ARISE REQUIRING ADDITIONAL PROPRIETARY INGRED INFORMATION CONTACT WOLF'S HEAD.

Respiratory Protection:NIOSH/MSHA APPRVD RESP PROT FOR PARTICULAR EXPOS OF CONCERN

Ventilation: VENTIL IAW GOOD ENGINEERING PRACTICE TO KEEP BELOW TLV LIMIT

Protective Gloves: INSULATED TYPE

Eye Protection: SAFETY GOG OR FACE SHIELD

Other Protective Equipment:PROT EXPOS AREAS W/PLASTIC OR RUBBERIZED PERSONAL PROT EQUIP Supplemental Safety and Health

CONTAINERS SIZE: 5 GAL.

====

HCC:V6 Boiling Pt:B.P. Text:>800F Spec Gravity:0.882 Solubility in Water:NEGLIGIBLE Appearance and Odor:OPAQUE - DARK - MILD ODOR

Stability Indicator/Materials to Avoid:YES OXIDIZERS Stability Condition to Avoid:NONE Hazardous Decomposition Products:CARBON MONOXIDE & SOOT CAN BE PROD IN AN O*2 DEFICIENT FIRE.

Waste Disposal Methods:DISPOSAL MUST BE IAW ALL APPLICABLE LOCAL, STATE & FED LAWS. QUANTITIES MAY BE DISPOSED OF BY CONTROLLED INCINERATION OR IN A SANITARY LANDFILL ACCD TO MFR.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this docume

nt should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.