

CONSOLIDATED MOTOR OILS,INC. -- CONSOLMO MOTOR OIL 10W -- 9150-00-186-6668

=====  
Product Identification  
=====

Product ID:CONSOLMO MOTOR OIL 10W

MSDS Date:01/01/1987

FSC:9150

NIIN:00-186-6668

MSDS Number: BDHBQ

=== Responsible Party ===

Company Name:CONSOLIDATED MOTOR OILS,INC.

Emergency Phone Num:(609)691-1066

CAGE:9Z316

=== Contractor Identification ===

Company Name:CONSOLIDATED MOTOR OIL CO INC

Address:1773 PINE AVE

Box:427

City:VINELAND

State:NJ

ZIP:08360-3442

Country:US

Phone:609-691-1066

CAGE:9Z316

=====  
Composition/Information on Ingredients  
=====

Ingred Name:REFINED PETROLEUM OILS, (LD50,ORAL RAT:>15G/KG)TAKE TLV AS  
OIL MIST =5MG/CUM,(75-80%)

Fraction by Wt: 80.0%

ACGIH TLV:5MG/CUM(OILMIST

Ingred Name:DETERGENT INHIBITOR PACKAGE(CONTAINS ZINC  
DIALKYLDITHIOPHOSPHATE,5-15%)

Fraction by Wt: 10.0%

ACGIH TLV:NOT SPECIFIED

Ingred Name:POLYMERIC HYDROCARBON  
,5-10%

Fraction by Wt: 7.5%

ACGIH TLV:NOT SPECIFIED

=====  
Hazards Identification  
=====

Effects of

Overexposure:EYES:IRRITATION;SKIN:IRRITATION/DERMATITIS;INGEST/INHA  
L:NAUSEA,VOMIT,DIARRHEA;IRRITATION RESP.TRACT

=====  
First Aid Measures  
=====

First Aid:INHALE:REMOVE TO FRESH AIR, GIVE CPR/O\*2 IF  
NEED;EYES/SKIN:FLUSH W LG AMTS H\*2O FOR 15 MIN;INGEST:RINSE MOUTH;  
GET MEDICAL ATTENTION FOR EYES, BREATHING DI

FFICULTY, OR OTHER  
SYMPTOMS OF OVEREXPOSURE.

===== Fire Fighting Measures =====

Flash Point:430F/221C (COC)  
Extinguishing Media:CO\*2,DRY CHEMICAL,FOAM,OR WATER FOG  
Fire Fighting Procedures:NONE NOTED;USE NIOSH/MSHA APPROVED SCBA IN  
ENCLOSED AREA  
Unusual Fire/Explosion Hazard:WATER MAY CAUSE FROTHING

===== Accidental Release Measures =====

Spill Release Procedures:USE PROPER PERSONAL PROTECTION;RECOVER FREE  
LIQUID;USE S  
UITABLE ABSORBENT MATERIAL AND RECOVER FOR PROPER  
DISPOSAL;DO NOT LET THE PRODUCT GO TO SEWER OR WATER COURSES.

===== Handling and Storage =====

Handling and Storage Precautions:STORE AT ROOM TEMPERATURE.KEEP AWAY  
FROM HEAT OR OPEN FLAMES.KEEP CONTAINER CLOSED WHEN NOT IN USE.  
Other Precautions:AVOID CONTACT WITH EYES AND SKIN.DO NOT INHALE  
VAPORS/MIST.WASH AFTER USE.

===== Exposure Controls/Personal Protection =====

Respirator  
y Protection:USE NIOSH/MSHA APPROVED RESPIRATOR FOR ORGANIC  
VAPORS/MIST IF > TLV  
Ventilation:MECH(GEN)OR LOCAL EXHAUST THAT PROVIDES ADEQUATE  
VENTILATION  
Protective Gloves:OIL IMPERVIOUS  
Eye Protection:SAFETY/CHEM GOGGLES  
Other Protective Equipment:FULL WORK CLOTHING TO PREVENT REPEATED OR  
PROLONGED CONTACT.  
Supplemental Safety and Health  
MSDS REVISED DATE:01/15/86;ITEM IS 10W GRADE OF SPEC:MIL-L-2104.

===== Physical/Chemical Properties =====

HCC:V6  
Vapo

r Pres:NEG  
Vapor Density:>1.0  
Spec Gravity:0.88  
Evaporation Rate & Reference:NEGLIGIBLE  
Solubility in Water:NEGLIGIBLE  
Appearance and Odor:AMBER LIQUID  
Percent Volatiles by Volume:NEGL

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
STRONG OXIDANTS  
Stability Condition to Avoid:HEAT,OPEN FLAMES  
Hazardous Decomposition Products:BURNING:CO,CO\*2,TRACES OF SULFUR  
OXIDES AND OF P,ZN

===== Disposal Considerations

=====

Waste Disposal Methods:DISPOSE OF COLLECTED MATERIAL IN ACCORDANCE WITH  
LOCAL,STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should see  
k competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.