View NSN Online: https://aerobasegroup.com/nsn/9150-00-188-9858

Product ID:DELVAC 1330 (SAE 30) MSDS Date:01/01/1985 FSC:9150 NIIN:00-188-9858 MSDS Number: BDHMF === Responsible Party === Company Name: MOBIL OIL CORPORATION Emergency Phone Num:212-883-4242 CAGE:1G112 === Contractor Identification === Company Name: MOBIL CORP Address:150 E 42ND ST Box:City:NEW YO RK State:NY ZIP:10017-5612 Country:US Phone:212-883-4242 CAGE:57635 Company Name: MOBIL OIL CORPORATION Address:3225 GALLOWS RD City:FAIRFAX State:VA ZIP:22037-0001 Phone:(703) 846-1482 CAGE:1G112 Ingred Name: MINERAL OIL (EXPOSURE REGULATED AS 'OIL MIST') CAS:8012-95-1 RTECS #:PY8030000 Fraction by Wt: >90% OSHA PEL:5 MG/M3

ACGIH TLV:5 MG/M3/10 STEL;9192

Ingred Name:ADDITIVES Fraction by Wt: 0.5 LITER(PINT) INGEST, IMMED GIVE 1-2 GLASSES OF H*20. (SEE SUPP DATA)

 Fire Fighting Measures	

Flash Point:425F;218C (OC) Extinguishing Media:CO*2, FOAM, DRY CHEM Fire Fighting Procedures:USE NIOSH/MSHA APPRVD SCBA Unusual Fire/Explosion Hazard:NONE

Spill Release Procedures: ABSORB ON FIRE RETARDANT TREATED SAWDUST, DIATOMACEOUS EARTH, OR OTHER ABSORBENT. SHOVEL UP & REMOVE. REPORT SPILL TO APPROP IATE AUTHORITIES. SPILLS THAT MAY REACH WATER(DRY

CREEKS INCLUDED)CALL COAST GUARD 800-424-8802.

Other Precautions: EYE PROTECTION: IF EYE CONTACT IS LIKELY USE CHEM TYPE GOGGLES OR SAFETY GLASSES W/ SIDE SHIELDS

====== Exposure Controls/Personal Protection ==========

Respiratory Protection:NONE NEEDED UNDER NORMAL CONDITIONS AND W/ ADEQUATE VENT MFR Ventilation:ADEQUATE VENT TO KEEP BELDW TLV. Protecti ve Gloves:SEE OTHER EQUIP Eye Protection:SEE OTHER PRECAUTIONS. Other Protective Equipment:OIL IMPERVIOUS GLOVES FOR RPTD/PRLNG EXPOSURE. Supplemental Safety and Health FIRST AID PROCEDURE:INGEST-CALL MD/POISON CONTROL FOR WAY TO INDUCE VOMIT. IF UNCON-DO NOT INDUCE VOMIT OR GIVE ANYTHING BY MOUTH. CONTAINER SIZE:5 GAL DRUM. VP:600F;316C Solubility in Water:NEGLIGIBLE Appearance and Odor:CLEAR LIQUID;MILD ODOR

Stab

ility Indicator/Materials to Avoid:YES STRONTG OXIDIZERS Stability Condition to Avoid:STRONG OXIDIATION Hazardous Decomposition Products:METAL OXIDES, CO

Waste Disposal Methods:MFR RECOMMENDS DILUTING WASTE W/ A FLAMMABLE SOLVENT (FL PT ABOUT 100F) & DISPOSE BY SUPERVISED INCINERATION. DISPOSAL METHODMUST BE IAW FEDERAL,STATE AND LOCAL CODES.

Disclaimer (provided with this information by the compiling agencies): Thi

s information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.