

IMPERIAL OIL CO.,INC. -- 30 GRADE LUB OIL;MFG'S BRAND NAME:SEE"SUPP" -- 9150-00-188-9858

=====
Product Identification
=====

Product ID:30 GRADE LUB OIL;MFG'S BRAND NAME:SEE"SUPP"

MSDS Date:09/01/1986

FSC:9150

NIIN:00-188-9858

MSDS Number: BDHMH

=== Responsible Party ===

Company Name:IMPERIAL OIL CO.,INC.

Address:ORCHARD PLACE

Box:279

City:MORGANVILLE

State:NJ

ZIP:07751

Country:US

Emergency Phone

Num:(201) 591-9400

CAGE:58563

=== Contractor Identification ===

Company Name:IMPERIAL OIL CO INC

Address:FOOT OF ORCHARD PL

Box:279

City:MORGANVILLE

State:NJ

ZIP:07751

Country:US

Phone:732-591-9400/FAX: 732-591-8825

CAGE:58563

=====
Composition/Information on Ingredients
=====

Ingred Name:LUB OIL BASE STOCK

Fraction by Wt: >99%

Ingred Name:ZINC ADDITIVE

Fraction by Wt: 0.2-0.3%

Ingred Name:PROPRIETARY ADDITIVES.

Fraction by Wt: 0.6-0.7%

=====
Hazards Ident

ification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Health Hazards Acute and Chronic:THERE IS NO MEDICAL OR TOXICOLOGICAL EVIDENCE THAT THIS IS AN IRRITANT,CORROSIVE OR CARCINOGEN. IT HAS A LOW ORDER OF ORAL & DERMAL TOXICITY. INHALATION OF PRODUCT MIST MAY CAUSE PULMONARY PROBLEMS. I F LEFT UNATTENDED,COULD CAUSE PULMONARYINJURY & POSSIBLE DEATH.

Medical Cond Aggravated by Exposure:DIRECT CONTACT WITH THE EYES MAY CAUSE EYE IRRITATION.

PROLONGED SKIN CONTACT MAY CAUSE SKIN IRRITATION.

===== First Aid Measures =====

First Aid:ING:DO NOT INDUCE VOMITING,CALL A PHYSICIAN IMMEDIATELY;
EYE:FLUSH WITH COPIOUS AMOUNTS OF WATER; SKIN:WASH WITH SOAP & WATER.

===== Fire Fighting Measures =====

Flash Point:446F/230C (0.C)

Extinguishing Media:CO*2, FOAM, DRY CHEM & H*2O FOG.

Fire Fighting Procedures:USE MESA/NIOSH APPRVD SCBA;USE H*2O SPRAY TO COOL CONTNRS.

Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====

Spill Release Procedures:DIKE & CONTAIN SPILL WITH INERT MATERIAL SUCH AS SAND,EARTH,ETC.,RECOVER OR DISPOSE OF DIKED LIQUID. PREVENT MATERIAL FROM GETTING INTO SEWERS & OPEN BODIES OF WATER. AREA MAY BE SLIPPERY-PREVENT FALL S.

===== Handling and Storage =====

Handling and Storage Precautions:THESE LUBRICANTS BECOME VERY VISCOUS

WHEN STORED AT LOW TEMPERATURES.THEY CONGEAL AT TEMPERATURES FROM -12 TO -32C.

Other Precautions:AVOID CONTACT WITH SKIN AND EYES:DO NOT BREATHE VAPORS/MIST;WASH THOROUGHLY AFTER EACH USE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE SUPPLIED-AIR RESPIRATORY PROTECTION IN CONFINED OR ENCLOSED SPACES IF NEEDED.

Ventilation:PROVIDE MECHAN(GEN/LOCAL EXHAUST)VENT TO MAINTN 600F/316C

Vapor Pres: