View NSN Online: https://aerobasegroup.com/nsn/9150-00-189-6730 CONTINENTAL OIL CO -- CONOCO FLEET MOTOR OIL, GRADE 40 -- 9150-00-189-6730 Product ID:CONOCO FLEET MOTOR OIL, GRADE 40 MSDS Date:01/01/1985 FSC:9150 NIIN:00-189-6730 MSDS Number: BDHST === Responsible Party === Company Name: CONTINENTAL OIL CO Emergency Phone Num:405-767-3456 CAGE:KO523 === Contractor Identification === Company Name: CONOCO INC Address: 1000 S PINE Box:1267 City:PONCA CITY State:OK ZIP:74603 Country:US Phone:800-441-3637, CHEMTREC 800-424-9300 CAGE:58326 Company Name: CONTINENTAL OIL CO. CAGE:KO523 ====== Composition/Information on Ingredients ======== Ingred Name: LUBRICATING OIL ========= Hazards Identification =============== Effects of Overexposure: EXCESS INH OF MISTS/VAPORS: PULMONARY DISORDERS. MAY CAUSE EYE IRRIT. SKIN IRRIT POSS. First Aid:EYE: IMMED FLUSH W/WATER AT LEAST 15 MIN, CALL MD. SKIN: WASH THOROUGHLY W/SOAP & WATER. REMOVE CONTAM CLOTHING & WASH BEFORE REUSE. GROSSLY CONTAM LEATHER SHOES SHOULD BE DISCARDED. INGEST: LG AMTS, INDUCE VOMIT, CALL MD. INH: CALL MD! Flash Point:390-440 COC Extinguishing Media:WATER SPRAY, FOAM, CO*2, DRY CHEM Fire Fighting Procedures: USE PROPER PROT EQUIP INCL SELF-CNTND BRTHNG **APPARATUS**

| Unusual Fire/Explosion Hazard:NONE |
|--|
| ========== Accidental Release Measures =========== |
| Spill Release Procedures:CLEAN UP PROMPTLY BY ABSORPTION IN CLAY OR EARTH |
| ========== Handling and Storage ============ |
| Handling and Storage Precautions:MAY BE STORED OUTDOORS OR INDOORS AWAY FROM FURNACE OR OTHER HEATING EQUIP Other Precautions:FOLLOW NEC PRECAUTIONS IAW NFPA CODE 30-1969 FOR COMBUSTIBLE LIQ, CLASS IIIB |
| ====== Exposure Controls/P ersonal Protection ========= |
| Respiratory Protection:NONE REQ Ventilation:MECH, NORM SHOP VENT Protective Gloves:NONE REQ Eye Protection:NONE REQ Supplemental Safety and Health VAP PRESS: NIL. SPEC GRAV: 0.86-0.89. MFR STATES PROD NOT CONSIDERED TO BE TOXIC ORALLY OR DERMALLY. |
| ======== Physical/Chemical Properties ========= |
| HCC:V6 Boiling Pt:B.P. Text:600F INIT Evaporation Rate & Dilution Rate & Dilut |
| ========= Stability and Reactivity Data ========= |
| Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING MATLS, HEAT, FLAME Hazardous Decomposition Products:NORM COMBUST: CO*2, WATER VAPOR. INCOMP COMBUST: CO. |
| ======= Disposal Considerations ========== |
| Waste Disposal Methods:MFR SUGGESTS CONTROLLED INCINERATION, STORE FOR PROFESSIONAL REMOVAL & DISPOSAL. AVOID DRAINAGE INTO SEWER.DISPOS |

E IAW LOCAL, STATE, FED REG.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this inform ation to their particular situation.