

GENERAL ELECTRIC CO.,PAINT OPERATION -- GLYPTAL 1202 -- 5970-00-214-1728
===== Product Identification =====

Product ID:GLYPTAL 1202
MSDS Date:01/01/1985
FSC:5970
NIIN:00-214-1728
MSDS Number: BDJSF
=== Responsible Party ===
Company Name:GENERAL ELECTRIC CO.,PAINT OPERATION
Address:1 CAMPBELL RD
City:SCHENECTADY
State:NY
ZIP:12306-9701
Country:US
Emergency Phone Num:518-273-3330
CAGE:OD426
=== Con
tractor Identification ===
Company Name:GENERAL ELECTRIC COMPANY
Address:SILICONE PRODUCTS DIVISION
City:WATERFORD
State:NY
ZIP:12188
Country:US
Phone:518-237-3330
CAGE:OD426
Company Name:INSULATING MATERIALS INC
Address:1 CAMPBELL RD
Box:1404
City:SCHENECTADY
State:NY
ZIP:12306-9701
Country:US
Phone:518-395-3300
CAGE:08800

===== Composition/Information on Ingredients =====

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)
CAS:1330-20-7
RTECS #:ZE2100000
Fraction by Wt: 50.0%

OSHA PEL:100 PPM/150 STEL
ACGIH TLV:100 PPM/150STEL;9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:ALKYD RESIN(% WT BY DIFFERENCE)
Fraction by Wt: 50.0%

=====
Hazards Identification
=====

Effects of Overexposure:INH:RESP IRRIT,DIZZ,UNCON/DEATH;EYES:SEV
IRRITN,BURNS;SKIN:MILD IRRITATION,BURNS,POSS ALRGIC REACTN.

=====
First Aid Measures
=====

First Aid:INH:REMOVE FROM EXPOSURE.GIVE CPR/OXYGEN WHEN
NE
EDED;EYES:FLUSH W/COPIOUS AMOUNT OF WATER.SEE PHYSICIAN;SKIN:WASH
THOROUGHLY WITH SOAP AND WATER.USE HAND LOTION.SEE PHYSICIAN.

=====
Fire Fighting Measures
=====

Flash Point:81F-TCC
Lower Limits:1.0
Upper Limits:UNK
Extinguishing Media:CO*2, FOAM, DRY CHEM.
Fire Fighting Procedures:WEAR SELF-CNTD BRTHG,APP H*20 SPRAY TO COOL
CONTR.
Unusual Fire/Explosion Hazard:EXPLOSION HAZARD DUE TO PRESSURE BUILD-UP
BECAUSE OF HEAT OF FIRE.

=====
Accidental Release Measures
=====

Spill Release Procedures:REMOVE IGNITION SOURCES,VENTILATE AREA
WELL.ABSORB WITH VERMICULITE OR OTHER MATERIALS, SUCH AS
SAWDUST,RAGS,PAPER & PLACE IN CLOSED CONTAINER. USE NON SPARKING
TOOLS. WEAR PROPER PROTECTIVE EQUIPMENT DURING CLEAN UP.

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENT,LOW FIRE
RISK AREA. PROTECT FROM PHYSICAL DAMAGE.AVOID ANY

PHYSICAL CONTACT.

KEEP CONTAINERS TIGHTLY CLOSED.

Other Precautions:KEEP FREE FALL OF LIQUID TO A FEW INCHES TO AVOID BUILD UP OF STATIC ELECTRICITY.DO NOT TAKE INTERNALLY.AVOID PROLONGED CONTACT WITH SKIN.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE APPROPRIATE RESPIRATOR APPROVED BY NIOSH/MESA.

Ventilation:PROVIDE MECHAN(GEN/LOCAL EXHAUST)VENT TO MAINTN 1.0

Spec Gravity:1.002

Evaporation Rate & Reference: