

SOUTHWEST GREASE AND OIL CO. -- 61023 -- 8030-00-221-1834

=====  
Product Identification  
=====

Product ID:61023

MSDS Date:01/01/1987

FSC:8030

NIIN:00-221-1834

MSDS Number: BDJVT

=== Responsible Party ===

Company Name:SOUTHWEST GREASE AND OIL CO.

Emergency Phone Num:913-782-5800

CAGE:7L754

=== Contractor Identification ===

Company Name:EXXON CO USA-SOUTHWEST GREASE BUSINESS UNIT

Address:1400 S HARRI

SON

Box:1974

City:OLATHE

State:KS

ZIP:66061

Country:US

Phone:913-656-3701/800-424-9300(CHEMTREC)

CAGE:70878

Company Name:SOUTHWEST GREASE & OIL CO, INC

CAGE:7L754

=====  
Composition/Information on Ingredients  
=====

Ingred Name:ASBESTOS (AMIANTHUS, OBSOLETE AMOSITE), (FOR OSHA PEL, SEE  
29CFR 1910.1101)

CAS:1332-21-4

RTECS #:CI6475000

OSHA PEL:0.2 FIBERS/CC

ACGIH TLV:0.5 FIBERS/CC; A1;89

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Name:STODDARD SOLVENT

CAS:8052-41-3

RTECS #:WJ

8925000  
OSHA PEL:500 PPM  
ACGIH TLV:100 PPM; 9293

Ingred Name:ASPHALT (PETROLEUM)  
CAS:8052-42-4  
RTECS #:CI9900000  
ACGIH TLV:5 MG/M3; (FUME);9192

=====  
Hazards Identification  
=====

Effects of Overexposure:IRRITATES EYES,MUCOUS  
MEMBRANE;HEADACHE;DIZZINESS;NAUSEA

=====  
First Aid Measures  
=====

First Aid:DO NOT INDUCE VOMITING-GIVE MILK OR WATER;WASH SKIN WITH SOAP  
AND WATER;FLUSH EYES WITH WATER;REMOVE TO FRESH AIR;  
CALL DOCTOR

=====  
Fire Fighting Measures  
=====

Flash Point:105F,40.6C PMCC  
Lower Limits:1.1  
Upper Limits:6.1  
Extinguishing Media:CARBON DIOXIDE DRY CHEMICAL,WATER FOG,SAND  
Fire Fighting Procedures:DO NOT SPRAY WATER ON FLAME

=====  
Accidental Release Measures  
=====

Spill Release Procedures:REMOVE ALL SOURCES OF  
HEAT,FLAES,SPARKS;VENTILATE AREA; USE ABSORBENT MATERIAL

=====  
Handling and Storage  
=====

Handling and Storage Precautions:DO NOT STORE NEAR HEAT OR  
FLAMES,SPARKS;KEEP CONTAINERS CLOSED AND UPRIGHT; GROUND CONTAINERS  
WHEN TRANSFERRING MATERIAL

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:SELF-CONTAINED RESPIRATOR  
Ventilation:LOCAL EXHAUST;EXPLOSION-PROOF AT FLOOR LEVEL  
Protective Gloves:RUBBER OR PLAST  
Supplemental Safety and Health

=====  
Physical/Chemical Properties  
=====

Boiling Pt:B.P. T

ext:300F,148.9C

Vapor Pres:5.0

Vapor Density:4.83

Spec Gravity:0.97

Solubility in Water:SLIGHT

Appearance and Odor:BLACK,SEMI-LIQUID,PETROLEUM ODOR

Percent Volatiles by Volume:28.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Conditions to Avoid Polymerization:HEAT SPARKS; OPEN FLAMES

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elemen

ts of the Department

of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.