View NSN Online: https://aerobasegroup.com/nsn/8010-00-221-2775

PRATT & LAMBERT-WICHITA DIV -- 786324 LACQUER C/N GLOSS LGHT YELLOW 13655

8010-00-221-2775

============= Product Identification =================

Product ID:786324 LACQUER C/N GLOSS LGHT YELLOW 13655

MSDS Date:01/01/1985

FSC:8010

NIIN:00-221-2775

MSDS Number: BDJVZ === Responsible Party ===

Company Name: PRATT & LAMBERT-WICHITA DIV

Address:16116 E 13TH ST

Box:2153 City:WICHITA State:KS ZIP:67201

Country:US CAGE:KO

010

=== Contractor Identification ===

Company Name: PRATT & LAMBERT-WICHITA DIV.

Box:2153 CAGE:KO010

Company Name: PRATT AND LAMBERT INC

Address:Box:6027 City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

======= Composition/Information on Ingredients ========

Ingred Name: ISOBUTYL ACETATE

RTECS #:NP9100000 Fraction by Wt: 25% ACGIH TLV:150PPM

Ingred Name: ISOBUTYL ALCOHOL (SARA III)

CAS:78-83-1

RTECS #:NP9625000 Fraction by Wt: 15% OSHA PEL:100 PPM


ACGI

H TLV:50 PPM; 9293 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS Ingred Name: NAPHTHA (PETROLEUM SPIRITS OR BENZIN) CAS:8030-30-6 RTECS #:SE7555000 Fraction by Wt: 15% **OSHA PEL:100 PPM** Ingred Name:LEAD CHROMATE PIGMENT LD 50 > 10.000 GMS/KG Fraction by Wt: 8% Ingred Name: METHYL ISOBUTYL KETONE (HEXONE) (SARA III) CAS:108-10-1 RTECS #:SA9275000 Fraction by Wt: >5% Other REC Limits: NONE RECOMMENDED OSHA PEL:100 PPM ACGIH TLV:50 PPM/75 STEL; 9394 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS ====== Hazards Identification =========== Effects of Overexposure: INHAL: ANEST, IRRIT OF RESPIR TRACT OR ACUT NERV SYS DEPRESN, HDACH, DIZZ, CONFUS, UNCONSCIOUS, COMA. First Aid:IN CASE OF CONTACT, FLUSH SKIN & EYES W/PLENTY OF WATER WHILE REMOVING CONTAMINATED CLOTHING.IF INHALED REMOV TO FRESH AIR.CALL A PHYSICIAN IF SYMPTOMS PERSIST. Flash Point:50F TCC 10C Lower Limits:.90 Extinguishing Media: USE FIRE EXTING(CO*2, DRY CHEM OR ALCOH FOAM) LO FIRE-POLYMER Fire Fighting Procedures: SELF-CONTAINED BREATH APPARATUS SHLD BE AVAIL F/FIREMEN

Unusual Fire/Explosion Hazard: KEEP CONTNRS TIGHTLY CLOS: ISOLAT FR HEAT, ELECTR EQPMT. SPARKS & OPEN FLAME. CLOS CONTNRS MAY EXPLO(SUP

======== Accidental Release Measures ============

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION (FLAMES, HOT SURFACES,



======

Waste Disposal Methods:DISPOSE IN ACCORDANC3E W/LOC,STATE & FEERAL REGULATIONS.INCINERATE IN APPRVD FACILITY. DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.