

ALOX CORP -- ALOX 2022 -- 6850-00-224-6656

=====
===== Product Identification =====

Product ID:ALOX 2022

MSDS Date:01/01/1987

FSC:6850

NIIN:00-224-6656

MSDS Number: BDKKT

=== Responsible Party ===

Company Name:ALOX CORP

Address:3943 BUFFALO AVE

Box:517

City:NIAGARA FALLS

State:NY

ZIP:14302

Country:US

CAGE:60773

=== Contractor Identification ===

Company Name:ALOX CORP

Address:3943 BUFFALO AVE

Box:517

Ci

ty:NIAGARA FALLS

State:NY

ZIP:14302

Country:US

Phone:716-282-1295

CAGE:60773

=====
===== Composition/Information on Ingredients =====

Ingred Name:ALIPHATIC PETROLEUM DISTILLATE CAS# 64742-21-8

CAS:64742-21-8

RTECS #:PY8033500

Fraction by Wt: 60.4%

Ingred Name:2-BUTOXYETHANOL

CAS:111-76-2

RTECS #:KJ8575000

Fraction by Wt: 1.0%

OSHA PEL:S, 50 PPM

ACGIH TLV:S, 25 PPM; 9293

Ingred Name:SEVERELY TREATED NAPHTHENIC OIL CAS#64742-52-5

CAS:64742-52-5

RTECS #:PY8035000

Fraction by Wt: 35%

Ingred Name:WATER CAS# 7732-18-5
CAS:7732-18-5
RTECS #:ZC0110000
Fraction by Wt: 1%
Fraction by Wt: 2%

=====
Hazards Identification
=====

Effects of Overexposure:SOLVENTS:NPC WARNS HARMFUL IF INHAL,CAUSE IRRIT.NON-MINERAL SPIRITS PORTION:NON-HAZARDOUS.SEE SUPP

=====
First Aid Measures
=====

First Aid:INHAL:REMOVE TO FRESH AIR,GIVE O*2.TREAT SYMPTOM.EYE;FLUSH W/ WATER AT LEAST 15 MIN.CALL MD.SKIN:WASH W/ SOAP & WATER.TREAT BURNS FROM HOT MATRL AS THERMAL BURNS.INGEST:DO NOT INDUCE VOMIT.CALL MD.

=====
Fire Fighting Measures
=====

Flash Point:140F,60C TCC
Extinguishing Media:DRY CHEMICAL,CO*2,WATER FOG
Fire Fighting Procedures:DO NOT USE WATER EXCEPT AS FOG,TO COOL CONTNR,TO FLUSH SPILL
Unusual Fire/Explosion Hazard:WATER STREAMS ON BURNING MATRL MAY SPREAD FIRE.DO NOT WELD,CUT EVEN EMPTY DRUM,CAN IGNIT EXPLOSIVELY

=====
Accidental Release Measures
=====

Spill Release Procedures:PROVIDE VENTILATION.ELIMINATE IGNITION SOURCES.ATTEMPT TO RECOVER.KEEP PETROLEUM PRODUCTS OUT OF STREAMS AND WATERWAYS.

=====
Handling and Storage
=====

Handling and Storage Precautions:AVOID PRLG/RPTD CONT,BREATH VAP.PROVIDE VENT.KEEP CONTNR CLOSED WHEN NOT IN USE.WASH BEFORE EAT,SMOKE,USE TOILET.WASH SATURATED CLOTHING BEFORE REUSE.
Other Precautions:IF INGEST,VOMIT OCCURS,MONITOR PATIENT

FOR 48 HR FOR

BREATH DIFFICULTIES. PROPRIETARY PROD-AN OXYGENATED HYDRICARBON FROM
PARTIAL OXIDN OF ALIPHATIC PETRO FRACTION BLEND W/ NA PETRO
SULFONATE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection: USE NIOSH/MSHA APPROVED MASK FOR VAPORS OR MIST.

Ventilation: LOCAL EXHAUST PREFERRED IF VAPORS OR MIST ARE GENERATED

Protective Gloves: OIL IMPERVIOUS

Eye Protection: SAFETY GLASSES.

Other Protective Equipment: AS NEEDED TO PROTECT AGAINST HOT P

ROD OR

RPTD/PRLG CONTACT.

Supplemental Safety and Health

MSDS PREP: 86353. OVEREXPOS: INHAL: NAUS, DIZZ, IRRIT NOSE & THROAT, WATERING
EYES. SKIN: CONT W/ HOT MATRL MAY BURN. INGEST: IRRIT, VOMIT, DIARR, NAUS.

===== Physical/Chemical Properties =====

HCC: F4

Boiling Pt: B.P. Text: >302F, >150C

Vapor Pres: 1

Spec Gravity: 0.8

Evaporation Rate & Reference: