

AMERICAN FINISH AND CHEMICAL CO -- F 2742:CLEANING COMPOUND -- 6850-00-224-6665
===== Product Identification =====

Product ID:F 2742:CLEANING COMPOUND
MSDS Date:03/24/1987
FSC:6850
NIIN:00-224-6665
MSDS Number: BDKLB
=== Responsible Party ===
Company Name:AMERICAN FINISH AND CHEMICAL CO
Address:1012 BROADWAY
Box:278
City:CHELSEA
State:MA
ZIP:02150
Country:US
Info Phone Num:617-884-6060 / 617-884-5634
Emergency Phone Num:617-884-6060 / 617-884-5634
Preparer's Name:WILLIAM T. JONES
CAGE:0AYG6
=== Contractor Identification ===
Company Name:AMERICAN FINISH AND CHEMICAL CO
Address:1012 BROADWAY
Box:City:CHELSEA
State:MA
ZIP:02150
Country:US
Phone:617-884-6060 / 617-884-5634
CAGE:0AYG6

===== Composition/Information on Ingredients =====

Ingred Name:KEROSINE SOLVENT (COAL OIL)
CAS:8008-20-6
RTECS #:OA5500000
Other REC Limits:20 PPM

Ingred Name:HIGH FLASH NAPHTHA
CAS:64742-95

Ingred Name:FATTY ACID DETERGENTS

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Health Hazards Acute and Chronic:ACUTE:IRRITATION OF EYES,SKIN AND
RESPIRATORY TRACT;NAUSEA,DIZZINESS. CHRONIC:NO DATA AVAILABLE.
Effects of Overexposure:SEE HEALTH HAZARDS DATA.
Medical Cond Aggravated by Exposure:NOT KNOWN.

=====
===== First Aid Measures =====

First Aid
:EYES:FLUSH WITH PLENTY OF WATER. SEEK MEDICAL ATTENTION.
SKIN:WASH THOROUGHLY WITH SOAP & WATER. INHALATION:REMOVE TO FRESH
AIR. INGESTION:CONTACT A PHYSICIAN IMMEDIATELY.

=====
===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:>100F/38C
Extinguishing Media:FOAM,DRY CHEMICAL OR CO*2.
Fire Fighting Procedures:TREAT AS COMBUSTIBLE LIQUID;USE NIOSH/MSHA
APPROVED SCBA IN AN ENCLOSED AREA.
Unusual Fire/Explosion Hazard:NONE KNOWN.

=====
===== Accidental Release Measures =====

Spill Release Procedures:USE PROPER PERSONAL PROTECTION;CONTAIN FREE
LIQUID:USE SUITABLE INERT ABSORBENT MATERIAL AND RECOVER FOR PROPER
DISPOSAL.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL,DRY AND WELL VENTILATED
AREA.KEEP AWAY FROM HEAT,OPEN FLAMES.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NI

OSHA/MSHA APPROVED RESPIRATOR FOR ORGANIC VAPORS IF ABOVE TLV/PEL.

Ventilation:LOCAL/MECHANICAL TO MAINTAIN TLV/PEL.

Protective Gloves:RUBBER.

Eye Protection:CHEMICAL GOGGLES.

Other Protective Equipment:EYE-WASH:PROTECTIVE CLOTHING AGAINST SKIN.

Work Hygienic Practices:AVOID CONTACT WITH EYES AND SKIN;DO NOT BREATHE VAPORS/MIST.WASH THOROUGHLY AFTER EACH USE.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:3

13F/155C

Spec Gravity:0.8523

Evaporation Rate & Reference:SLOWER (ETHER=1)

Solubility in Water:SLIGHT

Appearance and Odor:CHARACTERISTIC PETROLEUM SOLVENT ODOR, PALE AMBER LIQUID.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:EXTREME HEAT.

Hazardous Decomposition Products:CO,CO*2

===== Disposal Considerations =====

Waste Disposal Metho

ds:DISPOSE OF COLLECTED MATERIAL IN ACCORDANCE WITH LOCAL,STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify a

nd

assume responsibility for the suitability of this information to their particular situation.