View NSN Online: https://aerobasegroup.com/nsn/9150-00-231-6689

BULK CHEMICAL DIST INC. -- VV-L-800A; LUBRICATING OIL, GEN PURPOSE -- 9150-00-231-6689

Product ID:VV-L-800A;LUBRICATING OIL,GEN PURPOSE

MSDS Date:01/01/1987

FSC:9150

NIIN:00-231-6689

MSDS Number: BDLCF === Responsible Party ===

Company Name: BULK CHEMICAL DIST INC.

Emergency Phone Num:504-362-3232

CAGE:EO174

=== Contractor Identification ===
Company Name:BULK CHEMI

CAL DIV, MALTER INTERNATIONAL

Address:80 FIRST ST

City:GRETNA

State:LA ZIP:70053 Country:US CAGE:EO174

Company Name: BULK CHEMICALS DISTRIBUTORS, INC

Address:80 FIRST STREET

City:GRETNA,

State:LA ZIP:70053 Country:US

Phone:504-362-3232 DISCONNECTED(2-20-92)

CAGE:56921

======= Composition/Information on Ingredients ========

Ingred Name:TRANSFORMER OIL

Fraction by Wt: 92.0%

ACGIH TLV:5MG/CUM(PER MFR

Ingred Name: CORROSION INHIBITOR IN GREASE (ALOX 2201)

Fraction by Wt: 6.0%

Ingred Name

Ingred Name: FOOD-GRADE ANTIOXIDANT Fraction by Wt: 0.5% Ingred Name:LOW FOAMING SURFACTANT, NON-TOXIC Fraction by Wt: 0.5% =========== Hazards Identification ========================== Effects of Overexposure: EYES: CAUSES SEV IRRIT, BLURD VISION; SKIN: REPTD/PROLNGD CONTCT CAUSES MOD IRRITATION; -SEE SUPPL DATA-First Aid:SKIN:WASH W.SOAP & H*20 EYES:FLUSH W. H*2O. INGESTED:GIVE 2 GLASSES H*20; INDUCE VOMITING.CALL A PHYSICIAN. INHALE:REMOVE TO FRESH AIR. GIVE CPR/OXYGEN IF NEED. KEEP WARM & QUIET. REMOVE CONTAMINATED CLOTHING. IF UNCONS DO NOT TAKE ANYTHING BY MOUTH. Flash Point:295F/146C(T.C.C Extinguishing Media: DRY CHENICAL OR CARBON DIOXIDE Fire Fighting Procedures: WATER OR FOAM MAY CAUSE FROTHING WHICH CAN BE DANGEROUS. Unusual Fire/Explosion Hazard:NONE ======== Accidental Release Measures ============ Spill Release Procedures: SM SPILL: ABSORB LIQ ON PAPER, VERMICULITE, COMMERCIAL ABSORBENTS & TRANSFER TO HOOD; LG SPILL: ELIMINATE IGN SOURCES. EVACUATE UNPROTECTED PERSONS. USE PROTECTV EQUIPMNT.STOP LEAK W/O RISK.DIKE AREA OF SPIL L,PUMP LIQ TO SALVGE TANK. SHOVEL REMAING INTO CONT ============ Handling and Storage =========================== Handling and Storage Precautions: STORE IN COOL, DRY, WELL VENTILATED

:THERMO SETTING ACRYLIC PLASTICIZER

Fraction by Wt: 1.0%

AREA. PROTECT FROM PHYSICAL DAMAGE.KEEP CONTAINERS CLOSED. MAINTAIN STANDARD HYGIENE FOR CHEM HANDLING.

Other Precautions: AVOID PROLONGED OR REPEATED SKIN CONTACT; OBSERVE ALL PRECAUTION IN THIS DATA SHEET WHEN HANDLING EMPTY CONTAINERS.

====== Exposure Controls/Personal Protection ========

Respiratory Protection:WEAR SELF CONTAINED BREATHING APP W/POSITIVE PRESSURE MODE.

Ventilation:LOCAL EXHAUST TO MAINTN BELOW TLV.

Protective Gloves: NEOPRENE

Eye Protection:SAFE

TY GLASSES

Other Protective Equipment: IMPERVIOUS CLOTHING & BOOTS.

Supplemental Safety and Health

-OVER-EXPOSURE: DERMATITIS, DEFATTING; INH: MAY CAUSE NASAL/RESP IRRIT, DIZZ, NAUSEA, UNCONCIOUSNSS; ING: CAUSES GI IRRIT, VOMITG, DIARRHEA; MSDS FROM MFR UNDATED.

======== Physical/Chemical Properties ==========

HCC:V6
Boiling Pt:B.P. Text:560F/293C
Vapor Pres:5
Vapor Density:>1.0
Spec Gravity: