

AMERON PROTECTIVE COATINGS -- 703-200 -- 8010-00-234-5176

=====  
Product Identification  
=====

Product ID:703-200  
MSDS Date:01/01/1987  
FSC:8010  
NIIN:00-234-5176  
MSDS Number: BDLKD  
=== Responsible Party ===  
Company Name:AMERON PROTECTIVE COATINGS  
Address:201 NORTH BERRY STREET  
City:BREA  
State:CA  
ZIP:92622-1020  
Country:US  
Info Phone Num:714-529-1951  
Emergency Phone Num:714-529-1951  
CAGE:0Y2E4  
=== Con  
tractor Identification ===  
Company Name:AMERON PROTECTIVE COATINGS  
Address:201 NORTH BERRY STREET  
Box:1020  
City:BREA  
State:CA  
ZIP:92622-1020  
Country:US  
Phone:714-529-1951  
CAGE:0Y2E4

=====  
Composition/Information on Ingredients  
=====

Ingred Name:BENZIN, NAPHTHA, MINERAL SPIRITS, PETROLEUM NAPHTHA  
CAS:8030-30-6  
RTECS #:DE3030000  
Other REC Limits:STEL 400 PPM  
OSHA PEL:100 PPM  
ACGIH TLV:300 PPM

=====  
Hazards Identification  
=====

Routes of Entry

: Inhalation:YES Skin:NO Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:INHALATION: ANESTHETIC. IRRITATION OF  
RESPIRATORY TRACT. MAY CAUSE NERVOUS SYSTEM DEPRESSION. SKIN/EYES:  
IRRITATION.  
Effects of Overexposure:IRRITATION

=====  
===== First Aid Measures =====

First Aid:SKIN/EYES: FLUSH W/WATER. INHALATION: REMOVE TO FRESH AIR.  
OBTAIN MEDICAL ATTENTION IN ALL CASES.

=====  
===== Fire Fighting Measures =====

Flash Point Method:TCC  
Flash Point:100F  
Lower Limits:1.1  
Extinguishing Media:SMALL FIRES: CO2/DRY CHEMICAL. LARGE FIRES: FOAM  
Fire Fighting Procedures:USE SELF CONTAINED BREATHING APPARATUS FOR  
FIREMEN.  
Unusual Fire/Explosion Hazard:CLOSED CONTAINERS EXPOSED TO HEAT MAY  
EXPLODE.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. AVOID  
BREATHING VAPORS. REMOVE W/INERT ABSORBENT & NON-SPARKING TOOLS.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:DON'T STORE ABOVE 120F. STORE LARGE  
QUANTITIES IN BUILDINGS DESIGNED FOR STORAGE OF NFPA CLASS ONE  
FLAMMABLES.  
Other Precautions:CONTAINERS SHOULD BE GROUNDED WHEN POURING. AVOID  
FREE FALL OF LIQUID IN EXCESS OF FEW INCHES.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH APPROVED PAINT RESPIRATOR/AI

R SUPPLIED

RESPIRATOR. RESPIRATOR USED BASED ON CHEMICAL CONDITION & CONDITIONS OF USE.

Ventilation:PROVIDE GENERAL DILUTION/LOCAL EXHAUST AS NECESSARY.

Work Hygienic Practices:REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:270-390F

Vapor Density:>1

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:54

===== St  
ability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:FIRE, HEAT, HOT SURFACES

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE W/LOCAL, STATE & FEDERAL REGULATIONS. DON'T INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The U

nited States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.