

ASHLAND OIL INC. -- TECTYL 502C -- 8030-00-244-1295

=====
Product Identification
=====

Product ID:TECTYL 502C

MSDS Date:01/01/1985

FSC:8030

NIIN:00-244-1295

MSDS Number: BDNBD

=== Responsible Party ===

Company Name:ASHLAND OIL INC.

Address:1409 WINCHESTER AVE

Box:391

City:ASHLAND

State:KY

ZIP:41114

Country:US

CAGE:81355

=== Contractor Identification ===

Company Name:ASHLAND INC

Address:1409 WINCH

ESTER AVE

Box:391

City:ASHLAND

State:KY

ZIP:41114

Country:US

Phone:800-622-6846

CAGE:81355

=====
Composition/Information on Ingredients
=====

Ingred Name:SOLVENTS

Fraction by Wt: 40%

ACGIH TLV:500 PPM

Ingred Name:PETROLEUM OIL *FOR OIL MIST

Fraction by Wt: 20%

ACGIH TLV:5MG/CUM*

=====
Hazards Identification
=====

Effects of Overexposure:MAY CAUSE IRRITATION;EXCESSIVE INHAL MAY CASUE
DIZZINESS,NAUSEA, VOMITING,HEADACHE

=====

=====
First Aid Measures
=====

First Aid:FLUSH EYES WITH WATER,FLUSH SKIN WITH SOAP & WATER. IF SWALLOWED, DO NOT INDUCE VOMITING.

=====
Fire Fighting Measures
=====

Flash Point:105F CC 41C CC
Lower Limits:0.9
Upper Limits:5.0
Extinguishing Media:CO*2,FOAM,DRY CHEMICAL
Fire Fighting Procedures:NONE
Unusual Fire/Explosion Hazard:NONE

=====
Accidental Release Measures
=====

Spill Release Procedures:ELEIMINATE IGNITION SOURCE,STOP SPILL AT SOURCE CONTAIN SPILL BY DIKE,ETC., PUMP INTO SALVAGE TANK.

=====
Handling and Storage
=====

Handling and Storage Precautions:AVOID CONTACT W/EYES & PROLONGED CONTACT W/SKIN. AVOID BREATHING VAPOR. WASH AFTER HANDLING.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:NONE REQD
Ventilation:LOC EXHAUST-SPEC VENT TO MAINTN LEVELS BELOW EST. TLV.
Protective Gloves:WEAR LNG GLOVES
Eye Protection:SAFETY GLASSES
Other Protective Equipment:NONE
Supplemental Safety and Health

=====
Physical/Chemical Properties
=====

HCC:F4
Boiling Pt:B.P. Text:310F 154C
Vapor Pres:UNK
Vapor Density:>1
Spec Gravity: