

ASHLAND OIL INC.(SUPPLIED BY STEVEN INDUSTRIES). -- TECTYL 502C -- 8030-00-244-1297

=====
Product Identification
=====

Product ID:TECTYL 502C

MSDS Date:01/01/1987

FSC:8030

NIIN:00-244-1297

MSDS Number: BDNBJ

=== Responsible Party ===

Company Name:ASHLAND OIL INC.(SUPPLIED BY STEVEN INDUSTRIES).

Emergency Phone Num:614-790-3333

CAGE:81355

=== Contractor Identification ===

Company Name:ASHLAND INC

Address:1409 WINCHESTER AVE

Box:391

City:ASHLAND

State:KY

ZIP:41114

Country:US

Phone:800-622-6846

CAGE:81355

Company Name:ELECTRONIC PARTS CO

Address:6263 PRESTON CREEK DRIVE

Box:City:DALLAS

State:TX

ZIP:75240-3517

Country:US

CAGE:33157

=====
Composition/Information on Ingredients
=====

Ingred Name:SOLVENTS

Fraction by Wt: 40.0%

ACGIH TLV:500PPM

Ingred Name:PETROLEUM

Fraction by Wt: 20.0%

ACGIH TLV:5MG/M3

=====
Hazards Identification
=====

Effects of Overexposure:IRRITANT. EXCESSIVE INHALATION MAY CAUSE
DIZZINESS, NAUSEA, VOMITING, HEADACHE.

=====
First Aid Measures
=====

First Aid:FLUSH EYES WITH WATER, FLUSH SKIN WITH SOAP AND WATER. IF
SWALLOWED, DO NOT INDUCE VOMITING.

=====
Fire Fighting Measures
=====

Flash Point:105F/40C CC
Lower Limits:0.80
Upper Limits:5.00
Extinguishing Media:CARBON DIOXIDE, FOAM, DRY CHEMICAL.
Fire Fighting Procedures
:NONE
Unusual Fire/Explosion Hazard:NONE

=====
Accidental Release Measures
=====

Spill Release Procedures:ELIMINATE IGNITION SOURCE, STOP SPILL AT
SOURCE, CONTAIN SPILL, PUMP INTO SALVAGE TANK.

=====
Handling and Storage
=====

Handling and Storage Precautions:AVOID CONTACT, BREATHING OF VAPORS
WASH AFTER HANDLING

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:NONE UNLESS OVER
TLV
Ventilation:TO MAINTAIN BELOW TLV
Protective Gloves:LONG GLOVES
Eye Protection:SAFETY GLASSES
Supplemental Safety and Health

=====
Physical/Chemical Properties
=====

HCC:F4
Boiling Pt:B.P. Text:310F/154C
Vapor Density:>1
Spec Gravity: