

PENRECO, DIV OF PENNZOIL CO -- PETROTECT 2,MIL-C-16173,GRADE 2 -- 8030-00-244-1297

=====
Product Identification
=====

Product ID:PETROTECT 2,MIL-C-16173,GRADE 2
MSDS Date:01/01/1985
FSC:8030
NIIN:00-244-1297
MSDS Number: BDNBM
=== Responsible Party ===
Company Name:PENRECO, DIV OF PENNZOIL CO
Address:700 MILIAM ST
Box:2967
City:HOUSTON
State:TX
ZIP:77252
Country:US
Info Phone Num:800-245-3952
Eme
rgency Phone Num:800-245-3952
CAGE:86459
=== Contractor Identification ===
Company Name:PENRECO, DIV OF PENNZOIL CO
Address:700 MILIAM ST
Box:2967
City:HOUSTON
State:TX
ZIP:77252
Country:US
Phone:800-245-3952
CAGE:86459

=====
Composition/Information on Ingredients
=====

Ingred Name:STODDARD SOLVENT
CAS:8052-41-3
RTECS #:WJ8925000
Fraction by Wt: 36%
OSHA PEL:500 PPM
ACGIH TLV:100 PPM; 9293

=====
Hazards Identification
=====

Effects of Overexposure

xposure:EYE: BURN/IRRIT. SKIN: DEFATTING. VAPORS:
IRRIT,DIZZINESS,DROWSINESS,PNEUMONIA,COMA. INGEST: GI IRRIT

=====
First Aid Measures
=====

First Aid:EYE: FLUSH WITH WATER 15 MIN,CALL PHYSICIAN. SKIN: WASH WITH SOAP & WATER,REMOVE CONTAMINATED CLOTHES. INHALATION: REMOVE TO FRESH AIR,GIVE ARTIF RESP IF NEEDED,CALL MD. INGESTION: DO NOT INDUCE VOMIT ING,CALL A DOCTOR IMMEDIATELY.

=====
Fire Fighting Measures
=====

Flash Point:100F/37C (ASTM)
Lower Limits:1.0
Upper Limits:6.0
Extinguishing Media:FOAM,DRY CHEMICAL,CARBON DIOXIDE
Fire Fighting Procedures:TREAT AS OIL FIRE,WATER ONLY TO COOL EXPOSED CONTAINERS
Unusual Fire/Explosion Hazard:DENSE SMOKE MAY BE GENERATED WHEN BURNING.

=====
Accidental Release Measures
=====

Spill Release Procedures:SCRAPE UP MATERIAL INTO WASTE CONTAINERS,OR ABSORB WITH DRY SAND OR OIL ABSORBENTS. CLEAN SPILL AREA WITH DETERGENT SOLUTIONS OR SAFETY SOLVENTS. PROVIDE ADEQUATE VENTILATION DURING CLEAN UP.

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE IN SEALED CONTAINERS AWAY FROM HEAT,OPEN FLAME,AND OXIDIZING MATERIALS.
Other Precautions:FIRE EXTINGUISHERS MUST BE KEPT READILY AVAILABLE & PERSONNEL TRAINED IN PROPER USE.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:NIOSH/MSHA APPROVED RESP DEVIC

E IN ACCORD WITH
EXPOSURE OF CONCERN

Ventilation:LOCAL/GENERAL

Protective Gloves:RUBBER SYNTH

Eye Protection:SPLASH PROOF GOGGLES

Other Protective Equipment:SYNTHETIC RUBBER PROTECTIVE
CLOTHING,BOOTS,APRON.

Supplemental Safety and Health

THE 50% DISTILLATION TEMPERATURE RANGES BETWEEN 330 TO
340F,TYPICALLY.PKG: 1 GAL CAN SOLVENT CONTAINS NO DETECTABLE
BENZENE (IE: