

PENRECO -- PETROTECT 2,MIL-C-16173,GRADE 2 -- 8030-00-244-1298

=====
Product Identification
=====

Product ID:PETROTECT 2,MIL-C-16173,GRADE 2

MSDS Date:01/01/1985

FSC:8030

NIIN:00-244-1298

MSDS Number: BDNBQ

=== Responsible Party ===

Company Name:PENRECO

Address:700 MILIAM ST PENNZOIL PL

Box:2967

City:HOUSTON

State:TX

ZIP:77252

Country:US

CAGE:PENRE

=== Contractor Identification ===

Company Name:P

ENRECO

Address:4401 PARK AVENUE

City:DICKINSON

State:TX

ZIP:77539

Country:US

Phone:713-236-6070

CAGE:PENRE

Company Name:PENRECO, DIV OF PENNZOIL CO

Address:700 MILIAM ST

Box:2967

City:HOUSTON

State:TX

ZIP:77252

Country:US

Phone:800-245-3952

CAGE:86459

=====
Composition/Information on Ingredients
=====

Ingred Name:STODDARD SOLVENT

CAS:8052-41-3

RTECS #:WJ8925000

Fraction by Wt: 36%

OSHA PEL:500 PPM

ACGIH TLV:100 PPM; 9293

=====
Hazards Identification
=====

=====

Effects of Overexposure:EYE: BURN/IRRIT. SKIN: DEFATTING. VAPORS:
IRRIT, DIZZINESS, DROWSINESS, PNEUMONIA, COMA. INGEST: GI IRRIT

===== First Aid Measures =====

First Aid:EYE: FLUSH WITH WATER 15 MIN, CALL PHYSICIAN. SKIN: WASH WITH
SOAP & WATER, REMOVE CONTAMINATED CLOTHES. INHALATION: REMOVE TO
FRESH AIR, GIVE ARTIF RESP IF NEEDED, CALL MD. INGESTION: DO NOT
INDUCE VOMITING, CALL A DOCTOR IMMEDIATELY.

===== Fire Fighting Measures =====

Flash Point:100F/37C (ASTM)
Lower Limits:1.0
Upper Limits:6.0
Extinguishing Media:FOAM, DRY CHEMICAL, CARBON DIOXIDE
Fire Fighting Procedures:TREAT AS OIL FIRE, WATER ONLY TO COOL EXPOSED
CONTAINERS
Unusual Fire/Explosion Hazard:DENSE SMOKE MAY BE GENERATED WHEN
BURNING.

===== Accidental Release Measures =====

Spill Release Procedures:SCRAPE UP MATERIAL INTO WASTE CONTAINERS, OR
ABSORB WITH DRY SAND OR OIL ABSORBENTS.
CLEAN SPILL AREA WITH
DETERGENT SOLUTIONS OR SAFETY SOLVENTS. PROVIDE ADEQUATE
VENTILATION DURING CLEAN UP.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN SEALED CONTAINERS AWAY FROM
HEAT, OPEN FLAME, AND OXIDIZING MATERIALS.
Other Precautions:FIRE EXTINGUISHERS MUST BE KEPT READILY AVAILABLE &
PERSONNEL TRAINED IN PROPER USE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection

:NIOSH/MSHA APPROVED RESP DEVICE IN ACCORD WITH
EXPOSURE OF CONCERN

Ventilation:LOCAL/GENERAL

Protective Gloves:RUBBER SYNTH

Eye Protection:SPLASH PROOF GOGGLES

Other Protective Equipment:SYNTHETIC RUBBER PROTECTIVE
CLOTHING.BOOTS,APRON.

Supplemental Safety and Health

THE 50% DISTILLATION TEMPERATURE RANGES BETWEEN 330 TO 340F,TYPICALLY.

PKG: 5 GAL PAIL. SOLVENT CONTAINS NO DETECTABLE BENZENE (IE: