

PENRECO -- PETROTECT IX,MIL-C-16173,GRADE 1 -- 8030-00-244-1299

=====
Product Identification
=====

Product ID:PETROTECT IX,MIL-C-16173,GRADE 1

MSDS Date:01/01/1985

FSC:8030

NIIN:00-244-1299

MSDS Number: BDNBV

=== Responsible Party ===

Company Name:PENRECO

Address:700 MILIAM ST PENNZOIL PL

Box:2967

City:HOUSTON

State:TX

ZIP:77252

Country:US

CAGE:PENRE

=== Contractor Identification ===

Company Name

:PENRECO

Address:4401 PARK AVENUE

City:DICKINSON

State:TX

ZIP:77539

Country:US

Phone:713-236-6070

CAGE:PENRE

Company Name:PENRECO, DIV OF PENNZOIL CO

Address:700 MILIAM ST

Box:2967

City:HOUSTON

State:TX

ZIP:77252

Country:US

Phone:800-245-3952

CAGE:86459

=====
Composition/Information on Ingredients
=====

Ingred Name:NAPHTA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:DE3030000

Fraction by Wt: 37%

OSHA PEL:100 PPM

=====
Hazards Identification
=====

=====

Effects of Overexposure:EYE: BURN/IRRIT. SKIN: IRRIT. VAPORS:
IRRIT,DROWSINESS,PNEUMONIA,COMA. INGESTION: IRRIT GI TRACT

===== First Aid Measures =====

First Aid:EYE: FLUSH WITH WATER 15 MIN,CALL PHYSICIAN. SKIN: WASH WITH
SOAP & WATER,REMOVE CONTAMINATED CLOTHING. INHALATION: REMOVE TO
FRESH AIR,GIVE ARTIF RESP IF NEEDED,CALL MD. INGESTION: DO NOT
INDUCE VOMI TING,CALL A PHYSICIAN.

===== Fire Fighting Measur
es =====

Flash Point:100F/37C (PMCC)
Extinguishing Media:FOAM,DRY CHEMICAL,CARBON DIOXIDE
Fire Fighting Procedures:TREAT AS AN OIL FIRE,WATER ONLY TO COOL
EXPOSED CONTAINERS
Unusual Fire/Explosion Hazard:DENSE SMOKE MAY BE GENERATED WHEN
BURNING,SOLVENT CAN CREATE MODERATE FIRE OR EXPLOSION HAZARD

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE FROM IGNITION SOURCES,SCRAPE MATERIAL
INTO WASTE CONTAINERS,OR ABSORB
WITH DRY SAND OR OIL ABSORBENTS.
CLEAN SPILL AREA WITH DETERGENT SOLUTIONS OR SAFETY SOLVENTS.
PROVIDE ADEQUATE VENTILATION DURING CLEAN UP.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN SEALED CONTAINERS AWAY FROM
HEAT,OPEN FLAME,AND OXIDIZING MATERIALS.
Other Precautions:FIRE EXTINGUISHERS MUST BE KEPT READLY AVAILABLE &
PERSONNEL TRAINED IN PROPER USE.

===== Exposure Controls/Personal Protection ===
=====

Respiratory Protection:NIOSH/MSHA APPROVED RESP DEVICE IN ACCORD WITH
EXPOSURE OF CONCERN
Ventilation:LOCAL/GENERAL
Protective Gloves:RUBBER,SYNTHETI
Eye Protection:SPLASH PROOF GOGGLES
Other Protective Equipment:RUBBER PROTECTIVE CLOTHING,BOOTS,APRONS
Supplemental Safety and Health
50% DISTILLATION TEMPERATURE IS BETWEEN 300-360F. PKG: 5 GAL PAIL.
SOLVENT CONTAINS NO DETECTABLE BENZENE (IE: