

CON-LUX COATINGS INC -- TT-P-86G, TY 1, RED LEAD BASE READY-MIXED -- 8010-00-244-5791

=====
Product Identification
=====

Product ID:TT-P-86G, TY 1, RED LEAD BASE READY-MIXED

MSDS Date:01/01/1985

FSC:8010

NIIN:00-244-5791

MSDS Number: BDNCX

=== Responsible Party ===

Company Name:CON-LUX COATINGS INC

Address:226 TALMADGE RD

Box:847

City:EDISON

State:NJ

ZIP:08818-0847

Country:US

Info Phone Num:908-2

87-4000 / FAX 908-287-9288

Emergency Phone Num:908-287-4000

CAGE:60189

=== Contractor Identification ===

Company Name:CON-LUX COATINGS INC

Address:226 TALMADGE RD

Box:847

City:EDISON

State:NJ

ZIP:08818-0847

Country:US

Phone:732-287-4000

CAGE:60189

=====
Composition/Information on Ingredients
=====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

Fraction by Wt: 6.6%

OSHA PEL:100 PPM

Ingred Name:LEAD TETROXIDE (RED LEAD), (OSHA PEL FROM 29CFR

1910.1025)
CAS:1314-41-6
RTECS #:OG5425000
Fraction by Wt: 77.3%
OSHA PEL:0.05 MG/M3 (PB)
ACGIH TLV:0.15 MG/M3(PB); 8990

===== Hazards Identification =====

Effects of Overexposure:EYES/SKIN:IRRIT. INH:IRRITATE RESP TRACT, HDCH,
DIZZINESS (INDICATIVE OF SOLVENT BASE PRODUCTS)

===== First Aid Measures =====

First Aid:SKIN/EYES:FLUSH W/PLENTY OF WATER 15 MINS. INH:MOVE TO FRESH
AIR. IF ANY IRRITATION PERSISTS, CONSULT
MD.

===== Fire Fighting Measures =====

Flash Point:105F,41C TCC
Lower Limits:1.0
Upper Limits:6.0
Extinguishing Media:CO*2,DRY CHEMICAL,FOAM.H*2O SPRAY POSS INEFFECTIVE.
Fire Fighting Procedures:USE H*2O TO COOL CLSD CNTNR,PRVNT PRESS BLD-UP
& AUTOIGNITN.
Unusual Fire/Explosion Hazard:CLSD CNTNRS MAY EXPLODE WHEN EXPSD TO
EXTREME HEAT.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF
IGNITION (FLAMES,HOT
SURFACES,ELECTRICAL STATIC OR FRICTIONAL SPRARKS). AVOID BREATHING
OF VAPORS. VENTILATE AREA. REMOVE W/INERT ABSORBENT & NON-SPARKING
TOOLS.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE AT ELEVATED TEMPS. KEEP
AWAY FROM OPEN FLAMES & SPARKS. DO NOT APPLY TO HOT SURFACES. KEEP
CNTNRS TIGHTLY CLOSED.
Other Precautions:DO NOT TAKE INTERNALLY. CONTAINERS SHOULD BE GROUNDED
WHEN POURING

. AVOID PROLONGED OR REPEATED CONTACT W/SKIN.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPRVD CHEMICAL-MECHANICAL FILTER
RESP.

Ventilation:LOC EXHST TO KEEP TLV BELOW ACCEPTABEL LIMIT.

Protective Gloves:PRLNG/RPTD CNTC

Eye Protection:SPLASH-PROOF SFTY EYEWEAR

Other Protective Equipment:PREVENT PROLONGED CONTACT W/CONTAMINATED
CLOTHING.

Supplemental Safety and Health
CONTAINER SIZE: 1 GAL CAN.

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:300F,149C

Vapor Pres:2.0

Vapor Density:4.9

Spec Gravity:2.94

Evaporation Rate & Reference: