

MALLINCKRODT INC.,SCIENCE PRODUCTS DIVISION -- ETHYL ACETATE AR -- 6810-00-245-6695  
===== Product Identification =====

Product ID:ETHYL ACETATE AR  
MSDS Date:01/01/1987  
FSC:6810  
NIIN:00-245-6695  
MSDS Number: BDNFV  
=== Responsible Party ===  
Company Name:MALLINCKRODT INC.,SCIENCE PRODUCTS DIVISION  
Address:PARIS BYPASS  
Box:M  
City:PARIS  
State:KY  
ZIP:40361  
Country:US  
Info Phone Num:314-982-5000  
Emergen  
cy Phone Num:314-982-5000  
CAGE:62910  
=== Contractor Identification ===  
Company Name:MALLINCKRODT SPECIALTY CHEMICALS CO  
Address:222 RED SCHOOL LANE  
Box:City:PHILLIPSBURG  
State:NJ  
ZIP:08865  
Country:US  
Phone:908-859-2151  
CAGE:62910

===== Composition/Information on Ingredients =====

Ingred Name:ETHYL ACETATE (SARA III)  
CAS:141-78-6  
RTECS #:AH5425000  
Fraction by Wt: >99%  
OSHA PEL:400 PPM  
ACGIH TLV:400 PPM; 9192  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

===== Ha

zards Identification =====

Effects of Overexposure:INH:IRRITNT TO NOSE/RESP TRCT;ING:CAUSES  
DIARRHEA,SORE THROAT;SKIN:DEFATS,IRRIT,EYES:IRRITATION.

===== First Aid Measures =====

First Aid:INHAL:REMOVE TO FRESH AIR.GIVE CPR/OXYGEN IF NEEDED;INGEST:IF  
SWALLOWED,GIVE TWO GLASSES OF WATER & INDUCE VOMIT.NOTHING BY MOUTH  
IF UNCON;SKIN/EYE EXPOSURE:RMV CONTMNTD CLOTHG.WASH SKIN W/SOAP &  
H\*2O .FLUSH SKIN/EYES W/LG H\*2O;GET MED H  
ELPIMMEDIATLY

===== Fire Fighting Measures =====

Flash Point Method:CC  
Flash Point:=-4.4C, 24.F  
Autoignition Temp:=-427.C, 800.6F  
Lower Limits:2.2  
Upper Limits:11.0  
Extinguishing Media:DRY CHEMICALS,FOAM,CO\*2;WATER SPRAY TO KEEP EXPOSD  
CANS COOL  
Fire Fighting Procedures:USE H\*20 TO COOL EXPD CONTRS. USE SCBA & FULL  
PROT.CLTHG.  
Unusual Fire/Explosion Hazard:ABOVE FLASH POINT,VAP-AIR MIXTURES ARE  
EXPLOSIVE WITHIN FLAMMABLE LIMITS;AUTO IGN TEMP:427C(80  
0F)

===== Accidental Release Measures =====

Spill Release Procedures:RMV IGN SOURCES.VENT AREA.USE RESP PROTCTION &  
PROTCTV CLOTHG.KEEP OUT OF SURF H\*20,SEWRS/CONFND AREAS;SM  
SPILL:ABSORB W/PAPER TOWELS.EVVAP UNDER FUME HOOD THEN BURN  
CAREFULLY;LG SPILL:DIKE AREA.CONTA IN & RECOVER SPILL IF POSS;SHOVL  
RESDUEINTO DRUMS

===== Handling and Storage =====

Handling and Storage Precautions:PROTCT AGAINST PHYSICAL DAMAGE.  
STORE  
IN COOL,DRY WELL VNTLTD AREA AWAY FM ING/HEAT SOURCES,OXIDZG  
MATL.OUTSIDE OR DETACHED SORAGE IS PREFERRED.  
Other Precautions:KEEP AWAY FROM HEAT,SPARKS,FLAMES.KEEP CONTNRS  
CLOSED.USE W/ADEQUATE VENT.AVOID BRTHG DUST.WASH THOROUGHLY AFTER  
HNDLG.VOND/GROUND CONTNRS WHEN TRNSFRG MATERL.USE NON-SPARKG TYPE  
TOOL & EQUIP.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:FULL FACE RESPIRATOR  
Ventilation:LOCAL EXHAUST TO MAINTN BELOW

TLV.  
Protective Gloves:IMPERVIOUS  
Eye Protection:GOGGLES/FACE SHIELD  
Other Protective Equipment:FULL PROTECTIVE CLOTHING,SAFETY SHOWER,EYE  
WASH STATION  
Supplemental Safety and Health  
MSDS FM MR DATED:22 AUG 85,CONFORMS TO OSHA HAZ COMM STD.

===== Physical/Chemical Properties =====

HCC:F2  
NRC/State Lic Num:NOT RELEVANT  
Boiling Pt:=77.2C, 171.F  
Vapor Pres:76  
Vapor Density:3.0  
Spec Gravity:0.9  
Evaporation Rate & Reference:6(BUT ACETATE=1)  
Solubility in Water:MO  
DERATE  
Appearance and Odor:COLORLESS LIQUID.PLEASANT FRUITY ODOR.  
Percent Volatiles by Volume:100

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
STRONG OXIDIZERS,STRONG ALKALIES/ACIDS.NITRATES.  
Stability Condition to Avoid:HEAT, IGNITION SOURCES  
Hazardous Decomposition Products:CO, CO\*2 WHEN HEATED TO DECOMPOSITION  
Conditions to Avoid Polymerization:HEAT WILL CONTRIBUTE TO  
INSTBLTY.SLOWLY DECOMPOSED BY MOISTR

===== Disposal Considerations =====

Waste Disposal Methods:LG SPILL & LOT SIZES OF HAZ WASTE CAN BE  
ATOMIZED IN A RCRA APPRVD COMBUSTION CHAMBER OR DISPOSED OF IN A  
RCRA APROVED LAND FILL FACILITY.DO NOT FLUSH TO SEWER.ENSURE  
COMPLIANCE W/FED,STATE, & LOCAL R EGS; REPORTABLE QTY  
(RQ)(CWA/CERCLA);5000LBS

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The U

nited States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.