EASTMAN KODAK CO TENNESSEE EASTMAN CO DIV -- ETHYL ACETATE -- 6810-00-245-6695

Product ID: ETHYL ACETATE MSDS Date:10/03/1996 FSC:6810 NIIN:00-245-6695 MSDS Number: BDNFW === Responsible Party === Company Name: EASTMAN KODAK CO TENNESSEE EASTMAN CO DIV Address: EASTMAN RD Box:511 City:KINGSPORT State:TN ZIP:37662 Country:US Info Phone Num:423-229-2000 **Emergency Pho** ne Num:HEALTH 800-EASTMAN; 800-424-9300 CAGE:7B604 === Contractor Identification === Company Name: AMJAY CORP. DBA AMJAY CHEMICALS Address:11200 WESTHEIMER SUITE 310 Box:218786 **City:HOUSTON** State:TX ZIP:77218-8786 Country:US Phone:713-492-2000 CAGE:64184 Company Name: EASTMAN KODAK CO TENNESSEE EASTMAN CO DIV Address: EASTMAN RD Box:511 City:KINGSPORT State:TN ZIP:37662 Country:US Phone:615-229-2000 CAGE:7B604

Ingred Name:ETHYL

ACETATE (SARA III) CAS:141-78-6 RTECS #:AH5425000 Fraction by Wt: 85% OSHA PEL:400 PPM ACGIH TLV:400 PPM; 9192 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS
======================================
Effects of Overexposure: EYES-IRRITATION, SKIN-PROLONGED CONTACT DRIES & CRACKS. VAPOR IRRITATES MUCOUS MEMBRANES, NARCOTIC EFF.
======================================
First Aid:EYES-FLUSH WITH WATER FOR 15 MINUTES.CALL DOCTOR.SKIN-FLUSH W
ITH WATER.INHALATION-REMOVE TO FRESH AIR
======================================
Flash Point Method:TCC Flash Point:24.8F,-4.0C Lower Limits:2.02 Upper Limits:10.7 Extinguishing Media:WATER SPRAY,CARBON DIOXIDE,DRY CHEMICAL Fire Fighting Procedures:NONE Unusual Fire/Explosion Hazard:NONE
======================================
Spill Release Procedures:CONTAIN SPILL,IF SMALL FLUSH WITH LARGE VOLUME OF WATER.REMOVE ANY SOURCE OF SPAR KS OF FLAME.PROVIDE ADEQUATE EXHAUST.ABSORB MATERIAL
======================================
Handling and Storage Precautions: AVOID EYE CONTACT. AVOID REPEATED OR PROLONGED SKIN CONTACT. USE WITH ADEQUATE VENTILATION TO KEEP BELOW TLV.KEEP CONTAINER CLOSED
======================================
Respiratory Protection:SELF CONTAINED IF NEEDED,ESPECIALLY IN CONFINED AREAS Ventilation:LOCAL - RECOMMENDED Protective Gloves:RU

BBER Eye Protection: FACE SHIELD/SAFETY GOGGLE Supplemental Safety and Health

HCC:F3 Boiling Pt:B.P. Text:172F,78C Vapor Pres:75 Vapor Density:3.0 Spec Gravity:0.902 Evaporation Rate & amp; Reference:1.1 (N-BUTYL ACETATE =1) Solubility in Water:MODERATE Appearance and Odor:COLORLESS LIQUID WITH A SWEET ESTER ODOR.

Stability Indicator/Materials to Avoid:YES OX IDIZERS

Waste Disposal Methods:PLACE ABSORBED MATERIAL IN CONTAINERS SUITABLE FOR SHIPPING TO DISPOSAL AREA

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use.

Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.