View NSN Online: https://aerobasegroup.com/nsn/9140-00-247-4354 ASHLAND OIL, INC. -- NO.6 FUEL OIL -- 9140-00-247-4354 ============= Product Identification ======================== Product ID:NO.6 FUEL OIL MSDS Date:01/01/1985 FSC:9140 NIIN:00-247-4354 MSDS Number: BDNNB === Responsible Party === Company Name: ASHLAND OIL, INC. Address:1409 WINCHESTER AVE Box:391 City: ASHLAND State:KY ZIP:41114 Country:US CAGE:81355 === Contractor Identification === Company Name: ASHLAND INC Address:1409 WINCHESTER AVE Box:391 City: ASHLAND State:KY ZIP:41114 Country:US Phone:800-622-6846 CAGE:81355 ======= Composition/Information on Ingredients ======== Ingred Name: AROMATIC HYDROCARBON Fraction by Wt: 60.0% **ACGIH TLV:100PPM** Ingred Name: ALIPHATIC HYDROCARBON Fraction by Wt: 1-10% **ACGIH TLV:500 PPM** ========== Hazards Identification ============================ Effects of Overexposure: SEVERE EYE IRRIT. DEFATTING, DERMATITIS, MOD. SKIN

Effects of Overexposure:SEVERE EYE IRRIT.DEFATTING,DERMATITIS,MOD.SKIN IRRIT.,NASAL & RESPIRATORY IRRIT,FATIGU

======================================
First Aid:SKIN:WASH W/WATERLESS HAND CLEANER THEN SOAP & WATER.DISCARD CONT.CLTHG & SHOES.EYES:FLUSH W/WATER. INGEST:GIVE 2 GLASSES OF WATER;INDUCE VOMIT. CALL DR.INHAL:MOVE TO FRESH AIR. RESTORE BREATHING IF N EEDED.KEEP WARM,QUIET,DOCTR.
======================================
Flash Point:140F COC Lower Limits:UNK. Upper Limits:UNK. Extinguishing Media:DRY CHEM.CO*2. Fire Fighti
ng Procedures:SELF-CONTAINED BREATHING APPARATUS W/FULL FACEPIECE-POSS.PRE
Unusual Fire/Explosion Hazard: VAPORS ARE HEAVIER THAN AIR & MAY TRAVEL ALONG THE GROUND & IGNITED BY HT, PILOT LIGHTS, OTHER FLAMES.
========= Accidental Release Measures ==========
Spill Release Procedures:SMALL SPILL:ABSORB LIQUID ON PAPER,VERMICULITE,FLOOR ABSORBENT,OR OTHER ABSORBENT MATL & TRANSFER TO HOOD.LARGE SPILL:EXCLUDE PEOPLE FROM AREA OF SPILL(IF NOT WEARING PROTECTIVE E QUIP.);STOP AT SOURCE, DIKE AREA,PUMP LIQ.TO SALVAGE TK.ABSORB BALANCE.
=========== Handling and Storage ============
Handling and Storage Precautions:CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS WHEN EMPTIED.SINCE EMPTIED CONTAINERS RETAIN PRODUCT RESIDUES(VAPORS,LIQUID,&/OR SOLID)  Other Precautions:ACUTE & SUBCHRONIC DOSES OF DIESEL FUEL FED TO RATS HAVE BEEN FOUND TO PRODUCE CHROMOSOMAL BREAKAGE.SKIN PAINT TESTS ON LAB.ANIMALS-PRODUCES SKIN CANCR.
====== Exposure Controls/Personal Protection =======
Respiratory Protection:NOT REQUIRED UNDER NORMAL CONDITIONS OF USE.  Ventilation:PROVIDE SUFFICIENT MERCHANICAL &/OR LOCAL EXHAUST  VENTILATIO
Protective Gloves:BUNA-N,NEOPRENE Eye Protection:CHEM.SPLASH GOGGLES Other Protective Equipment:IMPERMEABLE APRONS.USE BARRIER CREAMS & TAKE DAILY SHOWERS.
Supplemental Safety and Health
========= Physical/Chemical Properties ==========
HCC:F4

E,

Boiling Pt:B.P. T

ext:UNK. Vapor Pres:1.0 Spec Gravity: