

PERMATEX INDUSTRIAL DIV OF LOCTITE CORP -- 80011, FORM-A-GASKET #2 SEALANT --
8030-00-252-3391

===== Product Identification =====

Product ID:80011, FORM-A-GASKET #2 SEALANT

MSDS Date:07/21/1992

FSC:8030

NIIN:00-252-3391

MSDS Number: BDNXM

=== Responsible Party ===

Company Name:PERMATEX INDUSTRIAL DIV OF LOCTITE CORP

Address:705 NORTH MOUNTAIN ROAD

Box:11915

City:NEWINGTON

State:CT

ZIP:06111-1411

Country:US

Info Phone Num:203-278-1280 OR 203-527-5211

Emergency Phone Num:800-641-7376

Preparer's Name:SCOTT BEVIL

CAGE:62377

=== Contractor Identification ===

Company Name:PERMATEX INDUSTRIAL

Address:HARTFORD SQUARE N 10 COLUMBUS BLVD

Box:City:HARTFORD

State:CT

ZIP:06106

Country:US

Phone:877-376-2839

CAGE:62377

===== Composition/Information on Ingredients =====

Ingred Name:ISOPROPANOL (ISOPROPYL ALCOHOL), 2-PROPANOL, DIMETHYL
CARBINOL

CAS:67-63-0

RTECS #:NT8050000

Fract

ion by Wt: 10-15%
Other REC Limits:400 PPM
OSHA PEL:400 PPM
ACGIH TLV:400 PPM

Ingred Name:ROSIN ACID *93-4*
CAS:8050-09-7
Fraction by Wt: 15-20%

Ingred Name:CLAY (KAOLIN), ALUMINUM SILICATE
CAS:1332-58-7
RTECS #:GF1670500
Fraction by Wt: 50-55%
ACGIH TLV:10 MG/CUM TOTAL DUST

Ingred Name:CASTOR OIL, POLYMD., OXIDIZED
CAS:68439-93-0
Fraction by Wt: 15-20%

Ingred Name:SOYBEAN DERIVATIVE *93/4*
CAS:8002-43-5
Fraction by Wt: 1-3%

=====
===== Hazards Identification =====
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYES: IRRITATION. INHALATION: NOSE &
THROAT IRRITATION, ALLERGEN. INGESTION: GI TRACT.
Explanation of Carcinogenicity:NONE
Effects of Overexposure:INHALATION: HEADACHE, DIZZINESS, NAUSEA.
Medical Cond Aggravated by Exposure:SKIN, EYE, RESPIRATORY DISORDERS

=====
===== First Aid Measures =====
=====

First Aid:
NGESTION: INDUCE VOMITING. INHALATION: REMOVE TO FRESH AIR.
SKIN: WASH W/SOAP & WATER. EYES: FLUSH W/WATER FOR 15 MINS. OBTAIN
MEDICAL ATTENTION IN ALL CASES.

=====
===== Fire Fighting Measures =====
=====

Flash Point Method:TCC
Flash Point:69F
Lower Limits:2%
Upper Limits:12%
Extinguishing Media:CO2, DRY CHEMICAL, FOAM

=====
===== Accidental Release Measures =====
=====

Spill Release Procedures:SCRAPE UP AS MUCH AS POSSIBLE & STORE IN A
CLOS

