

SOUTHWEST PETRO-CHEM -- CORROSION-PREVENTV FINGERPRINT REMOV MIL-C --
8030-00-252-8300

=====
Product Identification
=====

Product ID:CORROSION-PREVENTV FINGERPRINT REMOV MIL-C

MSDS Date:01/01/1985

FSC:8030

NIIN:00-252-8300

MSDS Number: BDNVYV

=== Responsible Party ===

Company Name:SOUTHWEST PETRO-CHEM

Address:1400 S HARRISON

Box:1974

City:OLATHE

State:KS

ZIP:66061

Country:US

CAGE:70878

=== Contrac

tor Identification ===

Company Name:EXXON CO USA-SOUTHWEST GREASE BUSINESS UNIT

Address:1400 S HARRISON

Box:1974

City:OLATHE

State:KS

ZIP:66061

Country:US

Phone:913-656-3701/800-424-9300(CHEMTREC)

CAGE:70878

=====
Composition/Information on Ingredients
=====

Ingred Name:METHYLAMYALCOHOL

RTECS #:PG8150000

Ingred Name:BARIUM (SARA III)

CAS:7440-39-3

RTECS #:CQ8370000

OSHA PEL:0.5 MG/M3

ACGIH TLV:0.5 MG/M3; 9192

=====
Hazards Identification
=====

=====

Effects of Overexposure:MAY CAUSE SKIN & EYE IRRIT. MAY CAUSE
DIZZINESS,HDACHE,& NAUSEA.

===== First Aid Measures =====

First Aid:EYE:FLUSH W/LG AMT OF WATR F/AT LEAST 15 MIN.CALL A DR.
INMMED. SKIN CONTCT,WASH THOROUGHLY W/SOAP & WATER.INHAL:IF
OVERCOME BY VAPORS,REMOV VICTIM FROM CONTAMINAT AREA.CALL A DR
IMMED.

===== Fire Fighting Measures =====

Flash Point:103F PMCC 39C
Extinguishing Media:DRY C
HEM,CO*2,FOAM,WATRFOG,SAND,EARTH
Fire Fighting Procedures:FIREGIGHTRS SHLD WEAR SELF-CONTND BREATHING
APPARATUS.
Unusual Fire/Explosion Hazard:DENSE SMOKE.

===== Accidental Release Measures =====

Spill Release Procedures:VENTILAT AREA.UTILIZING PROPR PERSONAL
PROTECTIVE EQPMT,TRANSFER BULK OF MATERL INTO ANOTHER CONTNR.ABSORB
REMAINING RESIDUE W/PROPER ABSORBENTS SUCH AS SAND,EARTH &
VERMICULITE.SWEEP UP & DISPOSE AS SOLID WAST IN ACCORD
W/LOC/S
TATE/FEDERAL REGULATS.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED.KEEP AWAY FROM
HEAT & FLAMES. STORE IN COOL DRY AREA.AVD CONTCT W/SKIN,EYES &
CLOTHING.WASH THOROUGHLY AFTER HANDLNG.WASH CLOTH(

===== Exposure Controls/Personal Protection =====

Respiratory Protection:LOC/GEN DILUT VENT TO KP EXPOS LEVELS BELOW
PERMISBL CONCENTRA LEVEL
Ventilation:IF TLV OF PRODCT,OR ANY COMPON EXCEDE

D,USE SELF-CONTN
BREATH

Protective Gloves:RBBR OR PLASTIC

Eye Protection:SPLASH GOGG/FUL FACE SHLD

Other Protective Equipment:KEEP CONTAINERS COLSED.KEEP AWAY FROM HEAT &
FLAMES. STORE I

Supplemental Safety and Health

PRECAUT F/HANLNG/STORAG:BEFORE REUSE. KEEP AWAY FROM FEED & FOOD
PRODUCTS.

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:266F 130C

Vapor Pres:5

Vapor Density:3.5

Spec Gravity:0.874

Evaporation Rate & Reference:NBU

AC BAS ON SOLVN

Solubility in Water:NEGLIGIBLE

Appearance and Odor:AMBER LIQUID W/SOLVENT ODOR.

Percent Volatiles by Volume:47

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

===== Disposal Considerations =====

Waste Disposal Methods:BY METHODS CONSISTENT W/LOCAL,STATE, & FEDERAL
REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulate

d for use by elements of the Department

of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.