View NSN Online: https://aerobasegroup.com/nsn/8030-00-252-8301

DAUBERT CHEMICAL COMPANY -- NOX RUST X-205(FORMERLY NOX RUST 314)

8030-00-252-8301

Product ID:NOX RUST X-205(FORMERLY NOX RUST 314)

MSDS Date:01/01/1985

FSC:8030

NIIN:00-252-8301

MSDS Number: BDNYX === Responsible Party ===

Company Name: DAUBERT CHEMICAL COMPANY

Address:1200 JORIE BLVD

City:OAK BROOK

State:IL

ZIP:60521-2210

Country:US

CAGE:02847

=== Contractor

Identification ===

Company Name: DAUBERT CHEMICAL CO

Address:1200 JORIE BLVD

City:OAK BROOK

State:IL

ZIP:60521-2210

Country:US CAGE:02847

======= Composition/Information on Ingredients ========

Ingred Name:BARIUM SOAP OF HIGH MOLECULAR WEIGHT OXIDIZED PETROLATUM

Fraction by Wt: 10%

Ingred Name: MORPHOLINE SOAP OF CLEIC ACID

Fraction by Wt: 8%

Ingred Name:PETROLEUM OIL & CO-SOLVENTS

Fraction by Wt: 51%

Ingred Name: NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6 RTECS #:SE7555

000 Fraction by Wt: 31% OSHA PEL:100 PPM
======================================
Effects of Overexposure:AVOID SKIN & EYE CONTACT
======================================
First Aid:SKIN:WASH W/SOAP & WATER. EYES:IMMEDIATELY FLUSH W/WATER A LEAST 15 MINUTES.CALL MD. INHALATION:REMOVE TO FRESH AIR.
======================================
Flash Point:100 F PMCC Lower Limits:0.7 Upper Limits:6.0 Extingui shing Media:CO*2, FOAM Fire Fighting Procedures:TREAT AS PETROLEUM OIL & SOLVENT FIRE Unusual Fire/Explosion Hazard:NONE
========= Accidental Release Measures ==========
Spill Release Procedures:SHUT OFF LEAK. DIKE LARGE SPILLS. KEEP AWAY FROM OPEN FLAMES OR SPARKS.
============= Handling and Storage ==============
Handling and Storage Precautions:TREAT AS LOW FLASH SOLVENT.
====== Exposure Controls/Personal Protection ========
Protect ive Gloves:OIL RESISTANT Eye Protection:GOGGLES RECOMMENDED Supplemental Safety and Health BOILING PT GIVEN FOR SOLVENT. VAPOR PRESSURE GIVEN @ 100F. PRODUC CONFORMS TO MIL-C-15074C
========= Physical/Chemical Properties ===========
HCC:F4 Boiling Pt:B.P. Text:311 TO 392F Vapor Pres:0.3 Spec Gravity:0.89 Appearance and Odor:AMBER OIL-MILERAL OIL ODOR Percent Volatiles by Volume:42
========= Stability and Reactivity Data ===========

Stability Indicator/M

ateria	le t∩	$\Delta v \cap$	M.,	۷⊢ ^८

======= Disposal Considerations ===========

Waste Disposal Methods:DISPOSE IN ACCORDANCE W/LOCAL,STATE, AND FEDERAL REGULATIONS. RCRA CLASSIFICATION D005 261.24 (BARIUM), RCRA CLASSIFICATION 261.21 (LOW FLASH)

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied,

warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.