

DOW CORNING CORP -- MOLYKOTE 44 GREASE,MIL-L-15719 A -- 9150-00-257-5358

=====
Product Identification
=====

Product ID:MOLYKOTE 44 GREASE,MIL-L-15719 A

MSDS Date:11/19/1993

FSC:9150

NIIN:00-257-5358

MSDS Number: BDPJL

=== Responsible Party ===

Company Name:DOW CORNING CORP

Address:3901 SOUTH SAGINAW ROAD

City:MIDLAND

State:MI

ZIP:48686

Country:US

Info Phone Num:517-496-6000

Emergency Phone Num:51

7-496-5900

CAGE:5D028

=== Contractor Identification ===

Company Name:ACCUMETRIC INC

Address:350 RING RD

Box:843

City:ELIZABETHTOWN

State:KY

ZIP:42701

Country:US

Phone:502-769-3385

CAGE:58149

Company Name:DOW CORNING CORP

Address:3901 S SAGINAW RD

Box:997

City:MIDLAND

State:MI

ZIP:48686-0997

Country:US

Phone:517-496-6000/517-496-6315

CAGE:5D028

Company Name:DOW CORNING CORP

Address:2200 W SALZBURG RD

Box:City:AUBURN

State:MI

ZIP:48611

Country:US

Phone:517-496-4388

CAGE:71984

Company Name:INLAND P

ACKAGING INC
Address:209 PETERSON DR
Box:644
City:ELIZABETHTOWN
State:KY
ZIP:42701-9804
Country:US
Phone:502-737-6757
CAGE:66172

=====
===== Composition/Information on Ingredients =====

Ingred Name:LITHIUM STEARATE
CAS:4485-12-5
RTECS #:WI4370000
Fraction by Wt: 19.0%
Other REC Limits:NONE SPECIFIED

Ingred Name:2,6-CIS-DIPHENYLHEXAMETHYLCYCLOTETRASILOXANE
CAS:33204-76-1
RTECS #:GZ4390000
Fraction by Wt: 121C
Extinguishing Media:WATER FOG, CARBON DIOXIDE, SAND, FOAM/DRY CHEMICAL.

WATER SPRAY MAY BE USED TO KEEP FIRE EXPOSED CONTAINERS COOL.
Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND
NIOSH-APPROVED SELF CONTAINED BREATHING APPARATUS. TOXIC FUMES MAY
BE FORMED.
Unusual Fire/Explosion Hazard:NONE

=====
===== Accidental Release Measures =====

Spill Release Procedures:SCOOP UP EXCESS GREASE. PICK-UP RESIDUE WITH
NON-FLAMMABLE ABSORBENT MATERIAL SUCH AS DIATOMACEOUS EARTH, SAND
OR VERMICULITE. SWEEP UP AND TR
ANSFER TO A CONTAINER FOR PROPER
DISPOSAL. CLEAN AREA WITH SOAPY WATER.
Neutralizing Agent:NOT RELEVANT

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE AWAY FROM OXIDIZERS. KEEP
CONTAINERS TIGHTLY CLOSED WHEN NOT IN USE. KEEP OUT OF REACH OF
CHILDREN.
Other Precautions:MINIMIZE SKIN CONTACT. WHEN HEATED TO TEMPERATURES
ABOVE 356F (180C) IN AIR, PRODUCT CAN FORM FORMALDEHYDE VAPORS.
FORMALDEHYDE IS A POTENTIAL CANCER

R HAZARD, A KNOWN SKIN AND
RESPIRATORY SENSITIZER, AND AN IRRITANT TO EYES, NOSE, THROAT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQUIRED. IF MATERIAL IS HEATED,
WEAR NIOSH-APPROVED RESPIRATORY PROTECTION.

Ventilation:ADEQUATE

Protective Gloves:WASH AT MEALTIME AND END OF SHIFT

Eye Protection:CHEMICAL GOGGLES/SAFETY GLASSES

Other Protective Equipment:EYE WASH STATION AND SAFETY SHOWER.

INDUSTRIAL-TYPE WORK CLOTHING
AND APRON AS REQUIRED.

Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND
RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHING OR
FOOTWEAR.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V6

NRC/State Lic Num:NOT RELEVANT

Vapor Pres: