

AMERICAN WRITING INK. -- VV-L-820C;LUBRICATING OIL -- 9150-00-261-8146

=====  
Product Identification  
=====

Product ID:VV-L-820C;LUBRICATING OIL

MSDS Date:05/03/1987

FSC:9150

NIIN:00-261-8146

MSDS Number: BDPPS

=== Responsible Party ===

Company Name:AMERICAN WRITING INK.

Address:33 FARNSWORTH STREET

City:BOSTON

State:MA

ZIP:02210-1210

Country:US

Info Phone Num:617-482-9167

Emergency Phone Num:617-4

82-9167

Preparer's Name:NOT REQUIRED

CAGE:82956

=== Contractor Identification ===

Company Name:AMERICAN INK AND OIL CORP

Address:33 ENDICOTT STREET

Box:City:NORWOOD

State:MA

ZIP:02062-3006

Country:US

Phone:781-762-0026 / FAX: 781-762-1617

CAGE:82956

=====  
Composition/Information on Ingredients  
=====

Ingred Name:PETROLEUM DISTILLATE

Other REC Limits:5MG/CUM AS OILMIST

Ingred Name:OTHER COMPONENTS (NOT SPECIFIED)

=====  
Hazards Identification  
=====

=====

Health Hazards Acute and Chronic:ACUTE:IRRITATION OF EYES,SKIN,RESPIRATORY TRACT;REDNESS OR DRYING OF SKIN. CHRONIC:DERMATITIS.

Effects of Overexposure:PROLONGED OR REPEATED SKIN CONTACT MAY CAUSE MILD SKIN IRRITATION

Medical Cond Aggravated by Exposure:NO DATA AVAILABLE.

===== First Aid Measures =====

First Aid:CONTACT:IMMED FLUSH EYES W/PLENTY OF WATER. CALL A PHYSICIAN. WASH SKIN W/ SOAP AND WATER.

===== Fire Fighting Measures =====

Flash Point:320F/160C

Lower Limits:1

Upper Limits:6

Extinguishing Media:USE CARBON DIOXIDE, FOAM, DRY CHEMICAL, OR WATER FOG.

Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.

Unusual Fire/Explosion Hazard:CARBON MONOXIDE,SULFUR OXIDES.

===== Accidental Release Measures =====

Spill Release Procedures:TAKE UP WITH NONCOMBUSTIBLE ABSORBANT

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED, HANDLE & STORE IN WELL VENTILATED AREA AWAY FM HEAT, FLAME & STRONG OXIDANTS.

Other Precautions:AVOID BRTHG OIL MIST. REMOVE OIL SOAKED CLOTHING & LAUNDER PRIOR TO RE-USE.WASH SKIN THOROUGHLY W/SOAP & WATER AFTER HANDLING.

===== Exposure Controls/Personal Protection =====

Respiratory

Protection:USE NIOSH/MSHA APPROVED RESPIRATOR FOR OIL  
MIST/VAPOR IF ABOVE TLV/PEL OR SCBA IN AN ENCLOSED AREA.  
Ventilation:LOCAL EXHAUST TO ELIMINATE MISTS/FUMES/GASES.  
Protective Gloves:RUBBER  
Eye Protection:SAFETY/CHEM GOGGLES  
Other Protective Equipment:CHEMICAL RESISTANT CLOTHING,EYE-WASH  
FOUNTAIN.  
Work Hygienic Practices:AVOID CONTACT WITH SKIN AND EYES.WASH  
THOROUGHLY AFTER USE.DO NOT USE CONTAMINATED CLOTHES.  
Supplemental Safety and Health

===== Physical/Chemica  
l Properties =====

HCC:V6  
Boiling Pt:B.P. Text:540F/282C  
Vapor Pres:11  
Spec Gravity:0.9  
Evaporation Rate & Reference: