

ROCKWELL INTERNATIONAL -- ROCKWELL 950 SEALANT (STICK GRADE) -- 9150-00-261-8290

=====
Product Identification
=====

Product ID:ROCKWELL 950 SEALANT (STICK GRADE)

MSDS Date:01/01/1985

FSC:9150

NIIN:00-261-8290

MSDS Number: BDPQD

=== Responsible Party ===

Company Name:ROCKWELL INTERNATIONAL

Emergency Phone Num:(412)247-3000

CAGE:76278

=== Contractor Identification ===

Company Name:ROCKWELL INTERNAT

IONAL

CAGE:76278

=====
Composition/Information on Ingredients
=====

Ingred Name:POLYESTER RESIN

Fraction by Wt: 47.0%

ACGIH TLV:NOT SPECIFIED

Ingred Name:CLAY (TREATED)

Fraction by Wt: 20.0%

ACGIH TLV:NOT SPECIFIED

Ingred Name:LITHIUMHYDROXY STEARATE

Fraction by Wt: 13.0%

ACGIH TLV:NOT SPECIFIED

Ingred Name:CALCIUM STEARATE

CAS:1592-23-0

RTECS #:WI3000000

Fraction by Wt: 1.0%

ACGIH TLV:NOT SPECIFIED

Ingred Name:WAX (SYNTHETIC) SEE SUPP DATA.

CAS:8002-74-2

RTECS #:RV0350

000
Fraction by Wt: 8.0%
ACGIH TLV:NONE SPECIFIED

===== Hazards Identification =====

Effects of Overexposure:NONE KNOWN TO MFR.MAY IRRITATE EYES AND SKIN,MAY RESULT IN DERMATITIS.

===== First Aid Measures =====

First Aid:EYE CONTACT:FLUSH WITH LARGE AMOUNTS OF WATER FOR 15 MIN.CALL A PHYSICIAN IF NEEDED.FOR SKIN CONTACT, WASH WITH SOAP AND WATER.

===== Fire Fighting Measures =====

=

Flash Point:320F/160C (COC)
Extinguishing Media:CO*2,DRY CHEMICAL
Fire Fighting Procedures:USE SCBA IN CONFINED AREA
Unusual Fire/Explosion Hazard:NONE SPECIFIED BY THE MFR

===== Accidental Release Measures =====

Spill Release Procedures:RECOVER THE SPILL MATERIAL INTO A CONTAINER.USE ABSORBENT IF NEEDED.

===== Handling and Storage =====

Handling and Storage Precautions:USE NORMAL PROCEDURES FOR HANDLING OIL & GREASES
Other Precautions:AVOID SKIN AND CONTACT.USE PROPER CLOTHING

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NO SPECIAL REQMENTS UNDER ORDINARY CONDITIONS/ADEQUATE VENT.
Ventilation:MECH(GEN)OR LOCAL EXHAUST THAT PROVIDES ADEQUATE VENTILATION
Protective Gloves:RUBBER
Eye Protection:GOGGLES
Other Protective Equipment:AS REQUIRED TO PREVENT PROLONGED CONTACT.
Supplemental Safety and Health
MSDS IS UNDATED.THE REST OF THE INGREDIENTS ARE PROPYLENE

CARBONATE=10%
AND OTHER LIKE INHIBITOR CORROSION=