

ALLOY RODS CORPORATION -- ATOM ARC 8018-B2 0.125 -- 3439-00-262-2746

=====  
Product Identification  
=====

Product ID:ATOM ARC 8018-B2 0.125  
MSDS Date:06/06/1986  
FSC:3439  
NIIN:00-262-2746  
MSDS Number: BDPXT  
=== Responsible Party ===  
Company Name:ALLOY RODS CORPORATION  
Address:WILSON AVENUE  
Box:517  
City:HANOVER  
State:PA  
ZIP:17331  
Info Phone Num:717-637-8911  
Emergency Phone Num:717-637-8911  
CAGE:84021

=== Contractor Identification ===  
Company Name:ESAB GROUP INC  
Address:801 WILSON AVENUE  
Box:517  
City:HANOVER  
State:PA  
ZIP:17331  
Country:US  
Phone:717-637-8911 OR 800-933-7070  
CAGE:84021

=====  
Composition/Information on Ingredients  
=====

Ingred Name:IRON  
CAS:7439-89-6  
RTECS #:NO4565500  
Other REC Limits:5MG/M\*3  
OSHA PEL:10MG/M\*3  
ACGIH TLV:5MG/M\*3

Ingred Name:SILICON  
CAS:7440-21-3  
RTECS #:VW0400000  
Other REC Limits:10MG/M\*3  
OSHA PEL:15 MG/M3 TDUST  
ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:SODIUM SILICATE  
CAS:6834-92-0  
RTECS #:VV9275000  
OSHA PEL:5MG/M\*3 (RESP. DUST)  
ACGIH TLV:0.1MG/M\*3(RESP.DUST)

Ingred Name:CALCIUM CARBONATE (MARBLE) (LIMESTONE)  
CAS:1317-65-3  
RTECS #:EV9580000  
Other REC Limits:10MG/M\*3  
OSHA PEL:15 MG/M3 TDUST  
ACGIH TLV:10 MG/M3 TDUST; 9192

Ingred Name:TITANIUM DIOXIDE  
CAS:13463-67-7  
RTECS #:XR2275000  
Other REC Limits:10MG/M\*3  
OSHA PEL:15 MG/M3 TDUST  
ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:MANGANESE (SARA III)  
CAS:7439-96-5  
RTECS #:OO9275000  
O  
ther REC Limits:5MG/M\*3 (C)  
OSHA PEL:(C) 5 MG/M3 DUST  
ACGIH TLV:5 MG/M3 DUST 9293

Ingred Name:POTASSIUM SILICATE  
CAS:1312-76-1  
OSHA PEL:5MG/M\*3 (RESP.DUST)  
ACGIH TLV:0.1MG/M\*3(RESP.DUST)

Ingred Name:CALCIUM FLUORIDE  
CAS:7789-75-5  
RTECS #:EW1760000  
Other REC Limits:2.5MG/M\*3  
OSHA PEL:2.5 MG/M3 (F)  
ACGIH TLV:2.5 MG/M3 (F); 8990

Ingred Name:POTASSIUM FELDSPAR  
CAS:7789-75-5  
Other REC Limits:10MG/M\*3(NUISANCE)  
OSHA PEL:NOT LISTED  
ACGIH TLV:NOT LISTED

Ingred Name:ZIRCON (ZIRCONIUM IV,SILICATE)  
CAS

:14940-68-2  
RTECS #:ZH9000000  
Other REC Limits:5MG/M\*3  
OSHA PEL:5 MG/M3/10 STEL (ZR)  
ACGIH TLV:5 MG/M3/10 STEL (ZR)

Ingred Name:CHROMIUM (SARA III)  
CAS:7440-47-3  
RTECS #:GB4200000  
Other REC Limits:0.5MG/M\*3  
OSHA PEL:1 MG/M3  
ACGIH TLV:0.5 MG/M3; 9192  
EPA Rpt Qty:1 LB  
DOT Rpt Qty:1 LB

Ingred Name:MOLYBDENUM  
CAS:7439-98-7  
RTECS #:QA4680000  
Other REC Limits:5MG/M\*3  
OSHA PEL:15 MG/M3 TDUST  
ACGIH TLV:10 MG/M3; 9293

=====  
===== Hazards Identification =====

Routes of Ent

ry: Inhalation:YES Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES

Health Hazards Acute and Chronic:ACUTE:METALLIC TASTE,NAUSEA,TIGHTNESS  
OF CHEST,FEVER,DIZZINESS,DRYNESS,IRRITATION OF EYES,NOSE,THROAT.  
CHRONIC:EXCESSIVE LEVELS MAY CAUSE BRONCHIAL ASTHMA,LUNG  
FIBROSIS,SIDEROSIS. ARC RAYS CAN INJURY EYES & BURN SKIN. ELECTRIC  
SHOCK CAN KILL.

Explanation of Carcinogenicity:CHROMIUM VI IS A HUMAN CARCINOGEN.  
CHROMIUM III IS A SUSPECTED HUMAN CAR  
CINOGEN.

Effects of Overexposure:SEE HEALTH HAZARDS.

Medical Cond Aggravated by Exposure:AGGRAVATION OF EXISTING RESPIRATORY  
OR ALLERGIC CONDITIONS. HIGHER LEVEL OF LUNG RELATED PROBLEMS AMONG  
SMOKERS.

=====  
===== First Aid Measures =====

First Aid:REMOVE FROM EXPOSURE & OBTAIN PROMPT MEDICAL ATTENTION. IF  
NOT BREATHING,GIVE CPR. IF UNCONSCIOUS,GIVE OXYGEN. EMPLOY FIRE AID  
TECHNIQUES RECOMMENDED BY AMERICAN RED CROSS.

=====  
===== Fire

Fighting Measures =====

Flash Point:NONE

Extinguishing Media:APPROPRIATE FOR SURROUNDING FIRE.

Unusual Fire/Explosion Hazard:WELDING ARCS & SPARKS CAN IGNITE  
COMBUSTIBLE PRODUCTS.

===== Accidental Release Measures =====

Spill Release Procedures:CLEAN UP ANY GRINDING DUST OR WASTE RESIDUE &  
PLACE IN APPROPRIATE DISPOSAL CONTAINER.

===== Handling and Storage =====

Other Precautions:TRAIN WELDER TO KEEP HIS  
HEAD OUT OF THE FUMES.

MONITOR AIR TO ENSURE ACCEPTABLE EXPOSURES. AVOID ELECTRICAL SHOCK  
BY MAINTAINING DRY WORK AREA.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:FUME RESPIRATOR OR AIR SUPPLIED RESPIRATOR IN  
CONFINED SPACES OR WHERE VENTILATION DOES NOT KEEP EXPOSURE BELOW  
TLV.

Ventilation:LOCAL EXHAUST

Protective Gloves:WELDER'S GLOVES

Eye Protection:HELMET OR FACE SHIELD WITH FILTER LENS

Other Protective Equipment:SUBSTANTIAL

DARK CLOTH,ARM

PROTECTOR,APRON,HAT,SHOULDER PROTECTION.

Work Hygienic Practices:WASH AFTER HANDLING.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:N1

Appearance and Odor:WELDING RODS 0.125 INCHES DIAMETER BY 14 INCHES  
LONG.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Hazardous Decomposition Products:FUMES OF METALS & METAL  
OXIDES,CO,CO\*2,NO\*2,O\*3,FLUORIDES

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IAW FEDERAL,STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document

should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.