View NSN Online: https://aerobasegroup.com/nsn/6685-00-263-1792

Product ID:THERMOMETER, MIL-T-2863 MSDS Date:01/01/1987 FSC:6685 NIIN:00-263-1792 **MSDS Number: BDQGM** === Responsible Party === Company Name: WEKSLER INSTRUMENTS CORP. Address:80 MILL RD City:FREEPORT,LONG ISLAND State:NY ZIP:11520-4616 Country:US Info Phone Num:516-623-0100 **Emergency Phone N** um:516-623-0100 CAGE:64467 === Contractor Identification === Company Name: WEKSLERIGLASS THERMOMETER CORP Address:80 MILL ROAD Box:City:FREEPORT State:NY ZIP:11520 Country:US Phone:516-623-0100 CAGE:64467 Ingred Name:MERCURY (SARA III)

CAS:7439-97-6 RTECS #:OV4550000 Fraction by Wt: 100% OSHA PEL:S, C, 0.1 MG/M3 ACGIH TLV:S, 0.05 MG/M3; 9192 EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

================= Hazards Identification ===

LD50 LC50 Mixture:TCLO-MAN 4430 UG/CUM 8HR Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: ACUTE MERCURY POISONING IS RARE. MOSE OFTEN IT IS THE RESULT OF CRONIC INHALATION. MERCURY MAY ALSO BE ABSORBED THROUGH THE SKIN. Effects of Overexposure: SIGNS OF MERCURY POISONING ARE METALLIC TASTE, EXCESSIVE SALIVATION, IRRITABILITY, AND TREMORS. SKIN CONTACT MAY CAUSE DERMATI TIS AND/OR ALLERGIC SENSITIZATION. Medical Cond Aggravated by Exposure: TUBERCULOSIS, KIDNEY DISEASE, ALCOHOLISM First Aid:REMOVE FROM EXPOSURE. CONSULT A PHYSICIAN. Flash Point:NONE Extinguishing Media: USE MEDIA TO EXTINGUISH SURROUNDING FIRE. Fire Fighting Procedures: USE SELF CONTAINED BREATHING APPARATUS. Unusual Fire/Explosion Hazard: IS NON-FLAMMABLE BUT EVAPORATES RAPIDLY WHEN HEATED CREATING TOXIC FUMES. Spill Release Procedures: VACUUM SPILLS WITH VACUUM HAVING A FILTERED EXHAUST. DO NOT SWEEP. WASH AREA WITH SOAP AND WATER. Neutralizing Agent:NONE Handling and Storage Precautions: HANDLE AND STORE THERMOMETERS

CAREFULLY. AVOID BREAKAGE AND RELEASE OF MERCURY.

======== Exposure Contro

Is/Personal Protection ========

Respiratory Protection:NIOSH APPROVED RESPIRATOR. TYPE DEPENDS ON LEVEL OF EXPOSURE. Ventilation:SUFFICIENT TO MAINTAIN EXPOSURE BELOW TLV. Protective Gloves:RUBBER/PLASTIC Eye Protection:SAFETY GLASSES Other Protective Equipment:CLOTHING NECESSARY TO PREVENT SKIN CONTACT. Work Hygienic Practices:KEEP FOOD STUFF STORED AWAY FROM MERCURY. Supplemental Safety and Health THERMOMETER CONTAINS APPROXIMATELY 1 ML OF MERCURY. THERE IS NO HAZARD AS LONG AS THE UNIT IS INTACT.

HCC:Z2 Boiling Pt:=357.8C, 676.F Melt/Freeze Pt:=-38.7C, -38.F Vapor Pres:0.0019 Vapor Density:1.015 Spec Gravity:13.59 Evaporation Rate & amp; Reference: