

HENRY W W CO -- 232 ASPHALT CUT BACK ADHESIVE MMM-A-110B -- 8040-00-264-3891

=====
Product Identification
=====

Product ID:232 ASPHALT CUT BACK ADHESIVE MMM-A-110B

MSDS Date:02/01/1988

FSC:8040

NIIN:00-264-3891

MSDS Number: BDQJD

=== Responsible Party ===

Company Name:HENRY W W CO

Address:WHITEHEAD AVE

Box:111

City:SOUTH RIVER

State:NJ

ZIP:08882

Country:US

Info Phone Num:908-254-2424

Emergency Ph

one Num:908-254-2424

CAGE:87866

=== Contractor Identification ===

Company Name:HENRY W W CO

Address:WHITEHEAD AVE

Box:111

City:SOUTH RIVER

State:NJ

ZIP:08882

Country:US

Phone:908-254-2424

CAGE:87866

=====
Composition/Information on Ingredients
=====

Ingred Name:PETROLEUM DISTILLATES (NAPHTHA OR RUBBER SOLVENT)

CAS:8002-05-9

RTECS #:SE7449000

Fraction by Wt: 28.0%

OSHA PEL:400 PPM

ACGIH TLV:400 PPM; 8990

Ingred Name:ASBESTOS (AMIANTHUS, OBSOLETE AMOSITE), (FOR OSHA PEL, SEE

29CFR 1910.1101)
CAS:1332-21-4
RTECS #:CI6475000
Fraction by Wt: 7.0%
OSHA PEL:0.2 FIBERS/CC
ACGIH TLV:0.5 FIBERS/CC; A1;89
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

=====
Hazards Identification
=====

Effects of Overexposure:INHALATION:POSSIBLE ASPHYXIATION. EYE IRRITANT

=====
First Aid Measures
=====

First Aid:INHALATION:REMOVE TO FRESH AIR. IF NORMAL RESPIRATION HAS STOPPED, APPLY ARTIFICIAL RESP EYES:FLUS W/WATER AT LEAST 15 MIN.
IF IRRITATION PERSISTS GET MEDICAL ATTENTION.

=====
Fire Fighting Measures
=====

Flash Point:56.0F,13.3C
Lower Limits:1%
Extinguishing Media:FOAM, CO2, DRY CHEMICAL, WATER FOG.
Fire Fighting Procedures:NONE KNOWN. USE NIOSH/MSHA APPROVED SCBA & FULL PROTECTIVE EQUIPMENT .
Unusual Fire/Explosion Hazard:VAPS ARE FLAM IF ALLOWED TO COLLECT & CONCENTRATE. ADHESIVE WILL FLOAT TO SURF OF WATER & MAINTAIN FLAME. WATER CAN SPREAD FLAME. CLOSED CONTAINERS MAY (SUPDAT)

=====
Accidental Release Measures
=====

Spill Release Procedures:EXTINGUISH ALL SOURCES OF COMBUSTION IN THE AREA. CLEAN UP SPILL AS SOON AS POSSIBLE

=====
Handling and Storage
=====

Handling and Storage Precautions:KEEP AWAY FROM HEAT, SPARKS OR OPEN FLAME
Other Precautions:DOT: FLAMMABLE

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:MFG STATES PR

OPER VENTILATION IS SUFFICIENT

Ventilation: TO KEEP VAPOR CONCENTRATION BELOW MFG RECM TLV OF 350 PPM

Supplemental Safety and Health

THE BOILING PT & VAP-PRESS ARE FOR THE SOLVENT PORTION ONLY. THIS
PRODUCT CONTAINS ASBESTOS, DETERMINED TO BE A HUMAN CARCINOGEN.

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt: B.P. Text: >257F, >125C

Vapor Pres: SEE ING

Vapor Density: HVR/AIR

Spec Gravity: 0.946

Evaporation Rate & Reference: SLOWER THAN ETHER

Solubility in

Water: NOT KNOWN

Appearance and Odor: NONE SPECIFIED BY MANUFACTURER.

Percent Volatiles by Volume: 40

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

NONE KNOWN.

Stability Condition to Avoid: HEAT, SPARKS, OPEN FLAME AND ALL OTHER
IGNITION SOURCES.

Hazardous Decomposition Products: INCMPLT COMBSTN: CO; NORM COMBSTN: BLK
SMOKE, CO₂, WATER.

===== Disposal Considerations =====

Waste Disposal Methods: S

COOP ALL MATERIAL INTO METAL CONTAINERS &

REMOVE TO SAFE PLCE. MFG RECM ALLOWNG TO DRY BY EVAPORATION OR
DISPOSAL BY BURNING, IF PERMITTED. FOLLOW FED, STLTE & LOCAL CODES.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. An

y person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.