

OCTAGON PROCESS, INC. -- CALIBRATION FLUID,MIL-C-7024B,TYPE II -- 6850-00-264-5771
===== Product Identification =====

Product ID:CALIBRATION FLUID,MIL-C-7024B,TYPE II

MSDS Date:01/01/1985

FSC:6850

NIIN:00-264-5771

MSDS Number: BDQKJ

=== Responsible Party ===

Company Name:OCTAGON PROCESS, INC.

Address:596 RIVER ROAD

City:EDGEWATER

State:NJ

ZIP:07020-1105

Country:US

Info Phone Num:201-945-9400

Emer

gency Phone Num:201-945-9400

CAGE:DO973

=== Contractor Identification ===

Company Name:OCTAGON PROCESS INC.

Address:596 RIVER ROAD

Box:City:EDGEWATER

State:NJ

ZIP:07020

Country:US

Phone:201-945-9400

CAGE:82925

Company Name:OCTAGON PROCESS,INC.

Address:596 RIVER ROAD

City:EDGEWATER

State:NJ

ZIP:07020-1105

Country:US

Phone:201-945-9400

CAGE:DO973

===== Composition/Information on Ingredients =====

Ingred Name:PETROLEUM HYDROCARBONS

Fraction by Wt: UNK

Ingred Name:NAPHTHA (PETRO

LEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

Fraction by Wt: UNK

OSHA PEL:100 PPM

Ingred Name:SOLVENT

Fraction by Wt: UNK

ACGIH TLV:150 PPM(PER MFR

=====
===== Hazards Identification =====

Effects of Overexposure:SEVERE EYE IRRITATION,DRYING OF SKIN.EXCESSIVE
INHALATION CAUSES HEADACHE DIZZINESS & NAUSEA.

=====
===== First Aid Measures =====

First Aid:INHALE:REMOVE TO FRESH AIR, GIVE CPR/O*2 IF
NEED;EYES/SKIN:FLU
SH W LG AMTS H*20 FOR 15 MIN;INGEST:RINSE MOUTH;
GET MEDICAL ATTENTION FOR EYES, BREATHING DIFFICULTY, OR OTHER
SYMPTOMS OF OVEREXPOSURE.A PPLY SKIN CREAM IF NEEDED FOR DRYNESS OF
SKIN.

=====
===== Fire Fighting Measures =====

Flash Point:>100F (TCC)
Lower Limits:0.7
Upper Limits:6.0
Extinguishing Media:WATER SPRAY,CO*2,FOAM,DRY CHEMICAL
Fire Fighting Procedures:NONE
Unusual Fire/Explosion Hazard:NONE

=====
===== Accidental Release Measures ====
=====

Spill Release Procedures:ELIMINATE IGNITION SOURCES. STOP LEAK.
EVACUATE AREA.DO NOT TOUCH SPILLAGE. SM SPILL:ABSORB W. INERT
ABSORBENT. PLACE IN CLOSED CONTAINER. FLUSH AREA W. WATER. LG
SPILL: DIKE AHEAD FOR LATER DISPOSAL. NOTIFY AUTHORITIES.

=====
===== Handling and Storage =====

Handling and Storage Precautions:KEEP AWAY FROM HEAT,SPARKS & OPEN
FLAM.USE W/ADEQUATE VENTILATION.AVOID PROLONGED OR REPEATED CONTACT
WITH SKIN.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:WEAR SELF-CNTND BRTHG APP
Ventilation:LOCAL EXHAUST PREFERRED,MECHANICAL EXHAUST ACCEPTABLE.
Protective Gloves:IMPERVIOUS
Eye Protection:SAFETY/CHEM GOGGLES
Other Protective Equipment:FACE WASH,SAFETY SHOWER
Supplemental Safety and Health
MSDS FM MFR UNDATED;MATERIAL TYPE II OF MIL-C-7024B.PER MFR,PRODUCT
ALSO AVAILABLE IAW MIL-C-7024C.

===== Physical/Chemical Properties =====

=====

HCC:F4
Boiling Pt:B.P. Text:300-410F
Vapor Pres:2.0
Vapor Density:4.9
Spec Gravity:0.77
Evaporation Rate & Reference:0.06
Solubility in Water:NEGLIGIBLE
Appearance and Odor:WATER-WHITE LIQUID
Percent Volatiles by Volume:100

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS.
Stability Condition to Avoid:HEAT, IGNITION SOURCES
Hazardous Decomposition Products:THERMAD DECOMPOSITION MAY YEILD CARBON
MONOXIDE

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE IN APPROVED INCINERATOR OR DISPOSE OF
IN APPROVED CHEMICAL DUMP IN ACCORDANCE WITH LOCAL,STATE & FEDERAL
REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information t

o be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.