

E. I. DUPONT DE NEMOURS AND COMPANY -- FREON 12 FLUOROCARBON -- 6830-00-264-5913  
===== Product Identification =====

Product ID:FREON 12 FLUOROCARBON

MSDS Date:09/23/1991

FSC:6830

NIIN:00-264-5913

MSDS Number: BDQLJ

=== Responsible Party ===

Company Name:E. I. DUPONT DE NEMOURS AND COMPANY

Address:FREON PRODUCTS DIVISION

City:WILMINGTON

State:DE

ZIP:19898

Info Phone Num:800-441-3637

Emergency Phon

e Num:800-441-3637/800-424-9300(CHEMTREC)

CAGE:73925

=== Contractor Identification ===

Company Name:DDRV STOCK MAINTENANCE DIV/DDRV-H

Address:8000 JEFFERSON-DAVIS HIGHWAY

Box:City:RICHMOND

State:VA

ZIP:23297

Country:US

Phone:804-279-3125

CAGE:02LX8

Company Name:DU PONT E I DE NEMOURS AND CO INC PETROCHEMICALS DEPT

Address:1251 BRANDYWINE BLDG

Box:City:WILMINGTON

State:DE

ZIP:19898

Phone:302-773-5676

CAGE:73925

===== Composition/Information on Ingredients =====

Ingred Name:

DICHLORODIFLUOROMETHANE (SARA III)

CAS:75-71-8

RTECS #:PA8200000

Fraction by Wt: 100%

OSHA PEL:1000 PPM

ACGIH TLV:1000 PPM; 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ozone Depleting Chemical:1

=====  
===== Hazards Identification =====

LD50 LC50 Mixture:TLV IS 1000 PPM, 4950 MG/M3.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE-INHALE:MAY CAUSE TINGLING  
SENSA

TION,HUMMING IN THE AIR,SLURRED SPEECH,AMNESIA,IRREGULAR HEART  
BEAT,UNCONSCIOUSNESS OR DEATH.MISUSE CAN BE  
FATAL.EYE:TEARING,IRRITATION.SKIN:LIQUID MAY CAUSE FROST  
BITE.ORAL:LIQUID MAY CAUSE NECROSIS OF LIPS & TONGS,BLANCHING OF  
SKIN,PAIN & TENDERNESS.CHRONIC-MAY CAUSE CNS EFFECTS.

Effects of Overexposure:INHALATION MAY CAUSE TINGLING SENSATION,  
HUMMING IN THE AIR, SLURRED SPEECH, AMNESIA, IRREGULAR HEART BEAT,  
UNCONSCIOUSNESS OR DEATH. MISUSE CAN BE FATAL. EYE IRRITATION

&

BLURRED VISION. SKIN EXPOSUR E TO LIQUID MAY CAUSE FROSTBITE.  
ORALLYLIQUID MAY CAUSE NECROSIS OF LIPS & TONGS, BLANCHING OF SKIN,  
PAIN & TENDERNESS.

Medical Cond Aggravated by Exposure:INDIVIDUALS WITH PRE-EXISTING  
DISEASES OF THE CENTRAL NERVOUS OR CARDIOVASCULAR SYSTEM MAY HAVE  
INCREASED SUSCEPTIBILITY TO THE TOXICITY OF EXCESSIVE EXPOSURES.

=====  
===== First Aid Measures =====

First Aid:GET MEDICAL ATTENTION IN ALL CASES. EYE:FLUSH WITH  
WATER FOR

15 MINUTES. HOLD EYELIDS OPEN. SKIN:FLUSH WITH WATER. TREAT FOR  
FROSTBITE IF NECESSARY. INHALED:REMOVE TO FRESH AIR & PROVIDE  
OXYGEN/CPR IF NEEDED. ORAL:INGESTION IS NOT CONSIDERED A POTENTIAL  
ROUTE OF EXPOSURE.

=====  
===== Fire Fighting Measures =====

Flash Point:WILL NOT BURN

Extinguishing Media:WATER, CO2, FOAM OR DRY CHEMICAL. WATER SPRAY MAY  
BE USED TO KEEP FIRE EXPOSED CONTAINERS COOL & FLUSH SPILLS AWAY.

Fire Fighting Procedure

s:WEAR FULL PROTECTIVE CLOTHING AND

NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS WITH FULL FACEPIECE OPERATED IN THE POSITIVE PRESSURE MODE.

Unusual Fire/Explosion Hazard:MAY FORM HYDROGEN FLUORIDE, HYDROGEN CHLORIDE AND TRACES OF CARBONYL HALIDES. CYLINDERS MAY BE RUPTURED UNDER FIRE CONDITIONS.

===== Accidental Release Measures =====

Spill Release Procedures:KEEP UPWIND. VENTILATE ENCLOSED SPACES UNTIL GAS IS DISPERSED. DO NOT SMOKE OR OPERATE INTERNAL COMBUSTION ENGINES IN IMMEDIATE VICINITY.

===== Handling and Storage =====

Handling and Storage Precautions:STORAGE-STORE IN COOL, DRY PLACE. CYLINDERS ARE UNDER PRESSURE. KEEP AWAY HEAT & INCOMPATIBLE MATERIALS.

Other Precautions:AVOID BREATHING VAPORS. AVOID EYE OR SKIN CONTACT. WASH WITH SOAP AND WATER BEFORE EATING OR DRINKING. USE WITH ADEQUATE VENTILATION. NEVER USE IN CONFINED OR CLOSED SPACE

===== Exposure

Controls/Personal Protection =====

Respiratory Protection:WEAR NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS OPERATED IN POSITIVE PRESSURE MODE OR SUPPLIED-AIR RESPIRATOR WITH FULL FACEPIECE AND OPERATED IN PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE .

Ventilation:LOCAL EXHAUST/MECHANICAL

Protective Gloves:CLOTH-LINED RUBBER GLOVES

Eye Protection:SAFETY GOGGLES/FACE SHIELD

Other Protective Equipment:EYEBATH, SAFETY SHOWER, PROTECTIVE CLOTHING

Work Hygienic Practices

:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING.

Supplemental Safety and Health

VP=4893MM HG(80PSIG).NOTE:EXPSRE TO HIGH VAP.LEVELS MAY CAUSE CARDIAC ARRYTH-VAP.MAY COLLECT IN LOW PLACES-NON-FLAMM,FREON 12-DECOMP.SLOWLY W.WTR-TYPE 12 OF FED SPEC BB-F-1421/MSDS DATED OCT85

===== Physical/Chemical Properties =====

HCC:G3

Boiling Pt:B.P. Text:-22F,-30C

Vapor Pres:4888 @ 25C

Vapor

Density:4.26

Spec Gravity:1.315

Solubility in Water:NEGLIGIBLE

Appearance and Odor:CLEAR, COLORLESS LIQUEFIED GAS - SLIGHT ETHEREAL  
ODOR

Percent Volatiles by Volume:100

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

ALKALI OR ALKALINE EARTH METALS, POWDERED ALUMINUM, ZINC, BERYLLIUM,  
ETC.

Stability Condition to Avoid:FIRE, TEMPERATURES ABOVE 125F

Hazardous Decomposition Products:MAY FORM HYDROGEN FLUORIDE, HYDROGEN  
CHL

ORIDE AND TRACES OF CARBONYL HALIDES.

===== Disposal Considerations =====

Waste Disposal Methods:FOR DISCHARGE OR DISPOSING OF WASTE MATERIAL,  
CONSULT LOCAL, STATE AND FEDERAL AUTHORITIES.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurat

e and

disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.