View NSN Online: https://aerobasegroup.com/nsn/2640-00-264-6642

MANSFIELD TIRE & RUBBER CO-TALC MFG BY CASCO PROD -- 443 -- 2640-00-264-6642

Product ID:443 MSDS Date:01/01/1987 FSC:2640 NIIN:00-264-6642 MSDS Number: BDQTY === Responsible Party === Company Name:MANSFIELD TIRE & RUBBER CO-TALC MFG BY CASCO PROD CAGE:79899 === Contractor Identification === Company Name:MANSFIELD TIRE & RUBBER CO-TALC MFG BY CASCO PROD CAGE:7989 9

Ingred Name:TALC (CONTAINING NO ASBESTOS) CAS:14807-96-6 RTECS #:WW2710000 Fraction by Wt: 87% OSHA PEL:2 MG/M3 RDUST ACGIH TLV:2 MG/M3 RDUST; 9192

Ingred Name:ASBESTOS, CHRYSOTILE CAS:12001-29-5 RTECS #:CI6478500 Fraction by Wt: 13% OSHA PEL:0.2 FIBERS/CC ACGIH TLV:2 FIBERS/CC; A1;9192

Effects of Overexposure: EXPOSURE MAY CAUSE CANCER.

First Aid:CONSULT MD FOR DERMATITIS.FLUSH EYE WITH FOLLOWED BY TREATMENT BY OPHTHALMOLOGIST.RECOMMEND EXAMINATIONS BY MD,ESPECIALLY CHEST X-RAY.

Spill Release Procedures: VACUUM UP SPILLED MAT	FERIAL.WEAR SELF CONTAINED
BREATHING GEAR.	

|--|--|

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENT

ILATED

AREA. PROTECT FROM PHYSICAL DAMAGE.AVOID ANY PHYSICAL CONTACT. KEEP CONTAINERS TIGHTLY CLOSED

====== Exposure Controls/Personal Protection ==========

Respiratory Protection:SCBA, SUPPLIED AIR RESPIRATOR Ventilation:PROVIDE MECHAN(GEN/LOCAL EXHAUST)VENT TO MAINTN