View NSN Online: https://aerobasegroup.com/nsn/6810-00-264-6722

Product ID:PHOSPHORIC ACID MSDS Date:12/12/1988 FSC:6810 NIIN:00-264-6722 MSDS Number: BDQWC === Responsible Party === Company Name: MONSANTO CO Address:800 N LINDBERGH BLVD **City:ST LOUIS** State:MO ZIP:63167 Country:US Info Phone Num:314-694-2333 Emergency Phone Num:314-694-1000 COLLECT CAGE:76541 === Contractor I dentification === Company Name: MONSANTO COMPANY Address:800 N LINDBERGH BLVD Box:City:SAINT LOUIS State:MO ZIP:63167 Country:US Phone:314-694-6661 OR 800-332-3111 CAGE:76541

Ingred Name:PHOSPHORIC ACID (SARA III) CAS:7664-38-2 RTECS #:TB6300000 Fraction by Wt: 75 - 85% Other REC Limits:NONE RECOMMENDED OSHA PEL:1 MG/M3/3 STEL ACGIH TLV:1 MG/M3/3 STEL; 9293 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

======= Haz

LD50 LC50 Mixture:LD50 (ORAL, RAT) 3,500-4,400 MG/KG Routes of Entry: Inhalation:NO Skin:NO Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:CORROSIVE. ACUTE- EYE:MAY CAUSE SEVERE IRRITATION, BURNS, PERMANENT TISSUE DAMAGE. SKIN:MAY CAUSE SEVERE IRRITATION. NO IMMEDIATE BURNING SENSATIONS MAY BE EXPECTED. INHALED: MIST/VAPORS MAY CAUSE SEVE RE RESPIRATORY IRRITATION. **ORAL:MAY CAUSE SEVE RE DIGESTIVE SYSTEM IRRITATION & BURNS, TISSUE** DAMAGE.CHRONIC- UNKNOWN. Effects of Overexposure: CORROSIVE. SEVERE EYES, SKIN, RESPIRATORY AND DIGESTIVE TRACTS IRRITATION AND BURNS Medical Cond Aggravated by Exposure:NOT KNOWN First Aid:GET MEDICAL ATTENTION IMMEDIATELY. EYE/SKIN:IMMEDIATELY FLUSH WITH WATER FOR AT LEAST 15 MINUTES. HOLD EYELIDS OPEN. INHALED: REMOVE TO FRESH AIR & PROVIDE OXYGEN/CPR IF NEEDED. ORAL:DO NOT INDUCE VOMI TING. IF CONSCIOUS, DRINK LARGE AMOUNT OF WATER/MILK. CALL A PHYSICIAN IMMEDIATELY. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. 

Flash Point:NONE

Extinguishing Media:WATER SPRAY, CARBON DIOXIDE, FOAM OR DRY CHEMICAL FOR SURROUNDING FIRE. USE WATER SPRAY TO COOL FIRE EXPOSED CONTAINERS.

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SE

LF CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:CAN REACT WITH METALS TO LIBERATE HYDROGEN, A FLAMMABLE GAS.

Spill Release Procedures:WEAR FACE PROTECTION, RUBBER BOOTS, APRON AND GLOVES. DIKE SPILL WITH SAND OR CLAY TO KEEP IT OUT OF SEWER SYSTEM. NEUTRALIZE WITH SODA ASH. REQUIRES GOOD VENTILATION AS CO2 IS PRODUCED. PLACE NEUTRAL IZED SPILL IN DOT APPROVED DISPOSAL CONTAINER Neutralizing

## Agent:SODA ASH

- Handling and Storage Precautions:STORE IN PLASTIC, RUBBER-LINED OR 316 STAINLESS STEEL TANKS DESINED FOR H3PO4. STORE DRUMS AWAY FROM HEAT AND OUT OF DIRECT SUNLIGHT.
- Other Precautions: KEEP OUT OF REACH OF CHILDREN. DO NOT GET IN EYES, ON SKIN OR ON CLOTHING. AVOID BREATHING MISTS OR VAPORS. WASH THOROUGHLY AFTER HANDLING.

======= Exposure Controls/Personal Protection ==========

Resp

iratory Protection:IF LEVELS EXCEED THE RECOMMENDED HEALTH STANDARDS, WEAR A NIOSH/MSHA APPROVED ORGANIC VAPOR RESPIRATOR FOR ACID. FOR EMERGENCY USE, WEAR A NIOSH APPROVED POSITIVE-PRESSURE MODE, SELF-CONTAINED BREATHI NG APPARATUS (SCBA).
Ventilation:PROVIDE SUFFICIENT LOCAL EXHAUST VENTILATION TO CONTROL INHALATION EXPOSURES BELOW OSHA'S PEL.
Protective Gloves:NEOPRENE OR RUBBER
Eye Protection:SAFETY GOGGLES & FACE SHIELD
Other Protective Equipment:EYE WASH STATION AND SAFETY
SHOWER.
INDUSTRIAL-TYPE WORK CLOTHING AND APRON AS REQUIRED.
Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHING OR FOOTWEAR.
Supplemental Safety and Health

HCC:C1

Boiling Pt:B.P. Text:275F-309F Melt/Freeze Pt:M.P/F.P Text:0.5F - 70F Vapor Pres:0.03 @ 68F Spec Gravity:1.575 - 1.692 pH:< 2 Evaporation Rate & amp; Reference:NOT RELEVANT Solubil

## ity in Water:COMPLETE Appearance and Odor:CLEAR, COLORLESS, SYRUPY LIQUID - NO ODOR

Stability Indicator/Materials to Avoid:YES STRONG ALKALIES, METALS, SULFIDES AND SULFITES Stability Condition to Avoid:EXCESSIVE HEAT Hazardous Decomposition Products:NONE

Waste Disposal Methods:DISPOSAL SHOULD BE MADE IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL LAWS AND REGULATIONS. REPORTABLE QUANTITY (RQ) IS 5000 LBS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibili ty for the suitability of this information to their particular situation.