View NSN Online: https://aerobasegroup.com/nsn/6810-00-264-8983

CHEMICAL COMMODITIES AGENCY, INC. -- METHYL ETHYL KETONE -- 6810-00-264-8983

Product ID:METHYL ETHYL KETONE

MSDS Date:01/01/1987

FSC:6810

NIIN:00-264-8983

MSDS Number: BDQYF === Responsible Party ===

Company Name: CHEMICAL COMMODITIES AGENCY, INC.

Address:27447 PACIFIC STREET

City:HIGHLAND

State:CA

ZIP:92346-2640 Country:US

Info Phone Num:909-864-2310/FAX 6220 D.

ANGELO

Emergency Phone Num:909-864-2310

CAGE:60777

=== Contractor Identification ===

Company Name: CHEMICAL COMMODITIES AGENCY, INC.

Address:27447 PACIFIC STREET

Box:City:HIGHLAND

State:CA

ZIP:92346-2640

Country:US Phone:909-864-2310

CAGE:60777

======= Composition/Information on Ingredients ========

Ingred Name: METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS:78-93-3

RTECS #:EL6475000 Fraction by Wt: 100%

OSHA PEL:200 PPM/300 STEL

ACGIH TLV:200 PPM/300STEL 9192

EPA Rpt Qty:5

000 LBS DOT Rpt Qty:5000 LBS
========= Hazards Identification ===========
LD50 LC50 Mixture:NOT GIVEN Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:ACUTE:IRRITATION OF EYES,SKIN,RESPIRATORY OR G.I.TRACTS;CNS EFFECTS LIKE HEADACHE,DIZZINESS,NAUSEA,VOMITING AND POSSIBLE UNCONSCIOUSNESS;REDNESS OR BURNS OF EYES/SKIN POSSIBLE.CHRONIC:DRYING OF SKIN,D EFATTING OR DERMATITIS CNS DEPRESSION. Explanation of Carcinogenicity:DATA PER MSDS
Effects of Overexposure:IRRIT OF NOSE,THROAT, EYES.
HEADACHE,NAUSEA,VOMITING Medical Cond Aggravated by Exposure:PERSONS WITH A HISTORY OF AILMENTS OR WITH A PRE-EXISTING DISEASE INVOLVING THE EYES, SKIN, OR RESPIRATORY TRACT MAY BE AT INCREASED RISK FROM EXPOSURE.
======================================
First Aid:INHALATION:REMOVE TO FRESH AIR. RESUSCITATE IF NOT BREATHING.
GET MEDICAL ATTENTION. EYES:IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR 15 MINUTES HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION. SKIN:REMOVE CONTAMINATED CLOTHING. WASH WITH SOAP AND WATER. IF IRRITATION PERSISTS, GET MEDICAL ADVICE. INGESTION:DO NOT INDUCE VOMITING. GIVE NOTHING BY MOUTH IF UNCONSCIOUS. GET IMMEDIATE MEDICAL ATTENTION.
======================================
Flash Point Method:TCC Flash Point:21.0F,-6.1C Lower Limits:1.8 Upper Limits:10 Extinguishing Media:USE WATER FOR CARRON DIOXIDE FOAM OR DRY
Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY

CHEMICAL.

Fire Fighting Procedures: FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.

Unusual Fire/Explosion Hazard:NONE

======== Accidental Release Measures ===============

Spill Release Procedures: USE PROPER PERSONAL PROTECTION; CONTAIN FREE MATERIAL IF POSSIBLE; USE SUITABLE INERT

ABSORBENT MATERIAL AND RECOVER FOR PROPER DISPOSAL IN AN APPROVED CONTAINER. Neutralizing Agent:NOT APPLICABLE.
======================================
Handling and Storage Precautions:STORE IN A COOL, DRY, WELL VENTILATED AREA. KEEP CONTAINERS TIGHTLY CLOSED WHEN NOT IN USE. PROTECT CONTAINERS FROM PHYSICAL DAMAGE. Other Precautions:DO NOT TAKE INTERNALLY. DO NOT BREATHE MIST. AVOID PROLONGED OR REPEATED BREATHING OF VAPOR. AVOID CONTACT WITH EYES.
USE WITH ADEQUATE VENTILATION. WASH THOROUGHLY AFTER HANDLING.
======= Exposure Controls/Personal Protection ========
Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR AS REQUIRED IF ABOVE PEL/TLV OR SCBA IN AN ENCLOSED AREA. Ventilation:LOCAL/GENERAL TO MAINTAIN PEL/TLV. Protective Gloves:NEOPRENE, NITRILE, OR NATURAL RUBBER Eye Protection:SAFETY GOGGLES WITH OPTIONAL FACE SHIELD Other Protective Equipment:EYE WASH STATION AND SAFETY SHOWER,WORK CLOTHING AND APRON AS REQUIRED. Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHING OR FOOTWEAR.
Supplemental Safety and Health AVOID PROLONGED OR REPEATED EXPOSURE. DO NOT GET ON SKIN OR IN EYES. DO NOT BREATHE VAPORS OR MISTS.
======================================
HCC:F2 Boiling Pt:=79.4C, 175.F Vapor Pres:70 Vapor Density:2.5 Spec Gravity:0.8061 Evaporation Rate & Description Reference: 5.7 (BUTL ACT=1) Solubility in Water: 24% BY WT Appearance and Odor: CLEAR LIQUID, NON-RESIDUAL ODOR Percent Volatiles by Volume: 100
========== Stability and Reactivity Data ==========
Stability Indicator/Materials to Avoid:YES ALKALINE MATERIALS, MINERAL ACIDS, HALOGENS Stability Condition to Avoid:NONE Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE AND OTHER UNIDENTIFIED COMPONENTS.
========= Disposal Considerations =============
Waste Disposal

Methods:CONSULT LOCAL AUTHORITIES.DISPOSAL MUST BE MADE IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL LAWS AND REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document

should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.