View NSN Online: https://aerobasegroup.com/nsn/6850-00-264-9038

Product ID:LOW FLASH STODDARD SOLVENT MSDS Date:01/01/1987 FSC:6850 NIIN:00-264-9038 MSDS Number: BDRBN === Responsible Party === Company Name:TRIANGLE REFINERIES INC Address:3020 KNIGHT ST SUITE 130 City:SHREVEPORT State:LA ZIP:71105 Country:US CAGE:6G367 === Contractor Identification ===

Company Name:TRIANGLE REFINERIES INC Address:3020 KNIGHT ST SUITE 130 Box:3367 City:SHREVEPORT State:LA ZIP:71105 Country:US CAGE:6G367

Ingred Name:ALIPHATIC HYDROCARBON SOLVENT (SATURATES) Fraction by Wt: 86.6% ACGIH TLV:NOT SPECIFIED

Ingred Name:AROMATICS Fraction by Wt: 13.4%

Effects of Overexposure: EXCESSIVE INHALATION MAY CAUSE LOCAL IRRITATION,

DROWSINESS, COLLAPSE, MUSCLE TWITCHING, COMA-PNEUMONIA.

First Aid:FOLLOW NORMAL FIRST AID PROCEDURES.CALL A DOCTOR IF NEEDED. DO NOT INDUCE VOMITING.

Flash Point:106F(ASTM D 56) Lower Limits:UNKN Upper Limits:UNKN Extinguishing Media:CO*2,DRY CHEMICAL,FOAM. Fire Fighting Procedures:USE SCBA FOR FIREFIGHTING. Unusual Fire/Explosion Hazard:THE MATERIAL WILL IGNITE ON CONTACT WITH AN OPEN FLAMES.

Spill Release Procedures: CLEAN IT UP, USE WIPING CLOTH OR ABSORBENT PAPER IN A SUITABLE MANNER (USE SAFETY TYPE TRASH RECEPTICLE)

Handling and Storage Precautions: KEEP AWAY FROM HEAT AND OPEN FLAMES. FOLLOW NORMAL PROCEDURES FOR HANDLING OIL/PETROLEUM PRODUCT. Other Precautions: AVOID SKIN AND EYE CONTACT.

=

Respiratory Protection:NO SPECIAL REQMNTS UNDER ORDINARY CONDITIONS/ADEQUATE VENT. Ventilation:PROVIDE MECHAN(GEN/LOCAL EXHAUST)VENT TO MAINTN