

THE W.W. HENRY CO. -- #232 ASPHALT CUTBACK ADHESIVE -- 8040-00-266-7425

=====
Product Identification
=====

Product ID:#232 ASPHALT CUTBACK ADHESIVE

MSDS Date:01/01/1987

FSC:8040

NIIN:00-266-7425

MSDS Number: BDRHG

=== Responsible Party ===

Company Name:THE W.W. HENRY CO.

Address:5608 SOTO ST

City:HUNTINGTON PARK

State:CA

ZIP:90255-2629

Country:US

CAGE:EO968

=== Contractor Identification ===

Compa

ny Name:HENRY W W CO

Box:3001

City:LANCASTER

State:PA

ZIP:17604

Country:US

Phone:717-396-2328;717-396-2935

CAGE:11761

Company Name:THE W.W. HENRY CO/HUNTINGTON PARK, CA 90255

CAGE:EO968

=====
Composition/Information on Ingredients
=====

Ingred Name:PETROLEUM DISTILLATES (NAPHTHA OR RUBBER SOLVENT)

CAS:8002-05-9

RTECS #:SE7449000

Fraction by Wt: 28%

OSHA PEL:400 PPM

ACGIH TLV:400 PPM; 8990

Ingred Name:ASBESTOS

RTECS #:CI6430000

Fraction by Wt: 7%

=====
Hazar

ds Identification =====

Effects of Overexposure:INHALATION OF HIGHLY CONCENTRATED VAPORS MAY LEAD TO ASPHYXIATION.PROMPT REMOVAL TO FRESH AIR USUALL

===== First Aid Measures =====

First Aid:MOVE VICTIM TO FRESH AIR AND APPLY ART. RESPIR. IF NEEDED.FOR EYE CONTACT,FLUSH EYES W/WATER FOR 15 MIN. IF IRRIT. PERSISTS, GET DR.

===== Fire Fighting Measures =====

Flash Point:90 F TOC 32 C

Lower Limi

ts:1%

Upper Limits:6%

Extinguishing Media:CO*2 DRY CHEM.

===== Accidental Release Measures =====

Spill Release Procedures:EXTINGUISH ALL SOURCES OF COMBUSTION IN THE AREA. CLEAN UP SPILLS AS SOON AS POSSIBLE.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP AWAY FROM HEAT,SPRAKS OR OPEN FLAME.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:PROPER VENTILAT
ION SUFFICIENT

Ventilation:YES-LOCAL EXHAUST TO KEEP VAPOR CONCENTRATION BELOW 350 PPM

Supplemental Safety and Health

BOILING POINT:OF SOLVENT PORTION:257-310 F 124-154 C

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:257-310 F

Vapor Density:4.2

Spec Gravity:0.93

Solubility in Water:INSOLUBLE

Appearance and Odor:BLACK LIQUID,ASPHALTIC ODOR

Percent Volatiles by Volume:36

===== Stability and Reactivity Data =====

Stability In

icator/Materials to Avoid: YES
MAY REACT W/STRONG OXIDIZING MATERIALS
Hazardous Decomposition Products: NORMAL COMBUSTION FORMS
BLK.SMOKE,CARBON DIOXIDE & WATER.VAPOR

===== Disposal Considerations =====

Waste Disposal Methods: SCOOP MATERIAL INTO METAL CONTAINERS & REMOVE TO SAFE PLACE. ALLOW TO DRY BY EVAPORATION OR DISPOSE OF BY BURNING IF PERMITTED.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.