

INDUSTRIAL RUBBR CEMENT CO. -- I.C.985 CUT-BACK ADHESIVE -- 8040-00-266-7425  
===== Product Identification =====

Product ID:I.C.985 CUT-BACK ADHESIVE  
MSDS Date:01/01/1985  
FSC:8040  
NIIN:00-266-7425  
MSDS Number: BDRHH  
=== Responsible Party ===  
Company Name:INDUSTRIAL RUBBR CEMENT CO.  
Address:15257 E PROCTOR AVE  
City:CITY OF INDUSTRY  
State:CA  
ZIP:91745-1019  
Country:US  
CAGE:LO027  
=== Contractor Identification ===  
Company Name:INDUSTRIAL RUBBER CEMENT CO  
Address:15257 E PROCTOR AVE  
Box:City:CITY OF INDUSTRY  
State:CA  
ZIP:91745-1019  
Country:US  
CAGE:55913  
Company Name:INDUSTRIAL RUBBR CEMENT CO.  
Address:15257 E PROCTOR AVE  
Box:City:CITY OF INDUSTRY  
State:CA  
ZIP:91745-1019  
Country:US  
CAGE:LO027

===== Composition/Information on Ingredients =====

Ingred Name:SHELL, M-75  
Fraction by Wt: 37%  
ACGIH TLV:200 PPM

===== Hazards Identification =====

E

Effects of Overexposure:SKIN/EYES-SLIGHTLY TO MODERATELY  
TOXIC.INHAL-MODERATE IRRIT OF NASAL & UPPER RESPIRATORY TRACT FR VA

=====  
First Aid Measures  
=====

First Aid:ORAL-DO NOT INDUCE VOMITING.DO NOT LAVAGE. ADMINISTER 2 TO  
4OZ OLIVE OIL & 1 TO 2 OZ OF ACTIVATED CHARCOAL. SKIN & EYES:WASH  
W/COPIOUS QUANTITIES OF WATER.

=====  
Fire Fighting Measures  
=====

Flash Point:40F TCC 4C  
Upper Limits:7.5  
Extinguishing Me  
dia:WATER FOG,FOAM,CO\*2,DRY CHEMICAL.  
Fire Fighting Procedures:DO NOT USE WATER EXCEPT AS A FOG.

=====  
Accidental Release Measures  
=====

Spill Release Procedures:SOAK UP PRODUCT INTO AN ABSORBANT MATERIAL  
SUCH AS SAWDUST,RAGS OR FINELY DIVIDED MINERAL WATER. KEEP AWAY  
FORM OPRN FLAMES & PROVIDE VENTILATION.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:STORE BELOW 120F.KEEP AWAY FROM HEAT &  
OPEN FL  
AMES. PROVIDE VENTILATION.  
Other Precautions:NONE

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:ORGANIC CANISTER OR FACE MASK AS REQD.  
Ventilation:LOC EXHAUST-PROVIDE GOOD VENT.MECH-USE FANS IN ENCLOS AREAS  
Protective Gloves:RUBBER/PLAST  
Eye Protection:SAFETY GLAS-NO SIDE SHIEL  
Other Protective Equipment:CLEAN, BODY PROTECTIVE CLOTHING ONLY.  
Supplemental Safety and Health

=====  
Physical/Chemical Properties  
=====

HCC:F2

Boiling Pt:B.P. Text:216F 102C

Vapor Pres:7.2

Vapor Density:3.5

Spec Gravity:.973

Evaporation Rate & Reference:2.1

Solubility in Water:NONE

Appearance and Odor:BLACK, FIBROUS LIQUID-TOLUENE ODOR

Percent Volatiles by Volume:38

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Hazardous Decomposition Products:CO,CO\*2 UPON COMBUSTION

===== Disposal Considerations =====

Waste Disposal Methods:BURN OR

BURY SOLID WASTES.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their

particular situation.