

SHORE CHEMICAL (STEVEN INDUSTRIES) -- N-1005 -- 8040-00-266-7427

===== Product Identification =====

Product ID:N-1005

MSDS Date:01/01/1987

FSC:8040

NIIN:00-266-7427

MSDS Number: BDRHL

=== Responsible Party ===

Company Name:SHORE CHEMICAL (STEVEN INDUSTRIES)

Emergency Phone Num:201-299-5400

CAGE:LO028

=== Contractor Identification ===

Company Name:SHORE CHEMICAL (STEVEN INDUSTRIES)

CAGE:LO028

Comp

any Name:STEVEN INDUSTRIES

Address:39 AVENUE C

Box:8

City:BAYONNE

State:NJ

ZIP:07002-3417

Country:US

Phone:201-437-6501

CAGE:33150

===== Composition/Information on Ingredients =====

Ingred Name:PIGMENTS-METALLIC OXIDES

Fraction by Wt: .4%

ACGIH TLV:NA

Ingred Name:VEHICLE- RUBBER

Fraction by Wt: 6.1%

ACGIH TLV:NA

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 30%

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qt

y:1000 LBS

Ingred Name:HEXANE (N-HEXANE)

CAS:110-54-3

RTECS #:MN9275000

Fraction by Wt: 30%

OSHA PEL:500 PPM

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Name:HEPTANE

Fraction by Wt: 30%

ACGIH TLV:445

===== Hazards Identification =====

Effects of Overexposure:EYE,THROAT,SKIN,LUNG IRRITANT

===== First Aid Measures =====

First Aid:WASH SKIN THOROUGHLY FLUSH EYES WITH WATER,REMOVE TO FRESH AIR,REMOVE CONTAMINATED CLOTHING GIVE ARTIFICIAL RESPIRATION IF NEEDED,CALL DOCTOR

===== Fire Fighting Measures =====

Flash Point:20F,6.7C

Lower Limits:1.2

Upper Limits:8.0

Extinguishing Media:FOAM,DRY CHEMICAL,FOG,CARBON DIOXIDE, TRICHLORET

Fire Fighting Procedures:WEAR SELF CONTAINED BREATHING APPARATUS

Unusual Fire/Explosion Hazard:AVOID FIRE,HEAT,SPARKS,IGNITION SOURCES,STORAGE IN DRECT SUNLIGHT

===== Accidental Release Measures =====

=====

Spill Release Procedures:VENTILATE AREA MECHANICALLY,KEEP FROM FLAME,FIRE,SPARKS,IGNITION SOURCES;DO NOT BREATHE VAPORS; CLEAN UP WITH ABSORBENT MATERIAL

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED,UPRIGHT,AWAY FROM FIRE,FLAME,SPARKS,IGNITION SOURCES,DIRECT SUNLIGHT

Other Precautions:NA

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NA

Ventilation:LOC

AL EXHAUST

Eye Protection:GOGGLES/GLASSES

Other Protective Equipment:NA

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:152F,66.7C

Vapor Pres:5.4

Vapor Density:.69

Spec Gravity:.63

Evaporation Rate & Reference:>BUTYL ACETATE

Solubility in Water:NEGLIGIBLE

Appearance and Odor:WHITE, NAPHTHA ODOR

Percent Volatiles by Volume:93.5

===== Stability and Reactivity Data =====

Stability Indic

ator/Materials to Avoid:YES

NA

Stability Condition to Avoid:NA

Hazardous Decomposition Products:OXIDES OF ZINC, SULFUR, CARBON,
METHANE GAS

===== Disposal Considerations =====

Waste Disposal Methods:SOLVENT DISPOSAL PROCEDURES

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, w
arrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.