

EASTMAN KODAK COMPANY -- 146 4932 DK-50 DEVELOPER,PART A -- 6750-00-266-7627
===== Product Identification =====

Product ID:146 4932 DK-50 DEVELOPER,PART A

MSDS Date:05/31/1995

FSC:6750

NIIN:00-266-7627

Kit Part:Y

MSDS Number: BDRHN

=== Responsible Party ===

Company Name:EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Country:US

Info Phone Num:716-722-5151

Emergenc

y Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

Company Name:EASTMAN KODAK CO US CUSTOMER SERVICE/GOVERNMENT SALES

Address:800 LEE RD

Box:City:ROCHESTER

State:NY

ZIP:14650-3129

Country:US

Phone:800-828-6203

CAGE:5K871

===== Composition/Information on Ingredients =====

Ingred Nam

e:HYDROQUINONE (SARA 302/313) (CERCLA)

CAS:123-31-9

RTECS #:MX3500000

Fraction by Wt: 50%

Other REC Limits:NONE SPECIFIED

OSHA PEL:2 MG/M3

ACGIH TLV:2 MG/M3; 9495

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Name:P-METHYLAMINOPHENOL SULFATE (METOL)

CAS:55-55-1

RTECS #:SL8650000

Fraction by Wt: 45 - 50%

Other REC Limits:NONE SPECIFIED

=====
===== Hazards Identification =====

LD50 LC50 Mixture:TLV FOR HYDROQUINONE IS 2 MG/M3.

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

estion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:TARGET ORGANS:EYES, SKIN, RESPIRATORY AND GASTROINTESTINAL TRACTS. ACUTE- CAUTION. CONTAINS HYDROQUINONE. INHALE:MAY CAUSE IRRITATION. HARMFUL IF INHALED. EYES/SKIN:CAUSES IRRITATION. MAY CAUSE ALLERGIC SKIN REACTION. ORAL:HARMFUL IF SWALLOWED. MAY CAUSE IRRITATION OF GI TRACT. CHRONIC- MAY CAUSE EYE INJURY.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:IRRITATION, ALLERGIC SKIN REACTION, EYE INJURY, PAIN

Medical Cond Aggravated by Exposure:PERSONS WITH PRE-EXISTING SKIN DISORDERS, EYE PROBLEMS OR IMPAIRED RESPIRATORY FUNCTION MAY BE MORE SUSCEPTIBLE TO THE EFFECTS OF THIS PRODUCT.

=====
===== First Aid Measures =====

First Aid:GET MEDICAL ATTENTION IF SYMPTOMS PERSIST. SKIN:REMOVE CONTAMINATED CLOTHING. WASH SKIN WITH SOAP & WATER. EYE:FLUSH WITH WATER FOR 15 MINUTES. HOLD EYELIDS OPEN. INHALED:REMOVE T

O FRESH

AIR. PROVIDE OXYGEN/CPR IF NEEDED. ORAL:IF CONSCIOUS, INDUCE VOMITING IMMEDIATELY AS DIRECTED BY MEDICAL PERSONNEL. CALL A PHYSICIAN/POISON CONTROL CENTER IMMEDIATELY. NEVER GIVE ANYTHING TO AN UNCONSCIOUS PERSON.

=====
===== Fire Fighting Measures =====

Flash Point:NONE

Extinguishing Media:WATER SPRAY, CARBON DIOXIDE, DRY CHEMICAL. USE WATER SPRAY TO COOL FIRE EXPOSED CONTAINERS.

Fire Fighting Procedures:WEAR PROTECTIVE CLOTHING AND NIOSH-APPROVED

SELF-CONTAINED BREATHING APPARATUS. FIRE MAY PRODUCE HAZARDOUS DECOMPOSITION PRODUCT.

Unusual Fire/Explosion Hazard:POWDERED MATERIAL MAY FORM EXPLOSIVE DUST- AIR MIXTURES.

=====
===== Accidental Release Measures =====

Spill Release Procedures:WEAR PERSONAL PROTECTIVE EQUIPMENT. VACUUM SPILLAGE WITH A VACUUM CLEANER OR CAREFULLY SWEEP UP. AVOID RAISING DUST. WASH SPILL SITE AFTER PICK-UP IS COMPLETE.

Neutralizing Agent:NOT RELEVANT

=====

=====
===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINER CLOSED. STORE AWAY FROM INCOMPATIBLE MATERIALS.

Other Precautions:AVOID CONTACT WITH EYES, SKIN AND CLOTHING. USE WITH ADEQUATE VENTILATION. WASH THOROUGHLY AFTER HANDLING. THE ROUTINE USE OF A NONALKALINE (ACID) TYPE OF HAND CLEANER AND REGULAR CLEANING OF WORKING SURFACES WILL MINIMIZE SKIN REACTION.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF ENGINEERING CONTROLS DO NOT MAINTAIN AIRBORNE CONCENTRATIONS TO AN ACCEPTABLE LEVEL, A NIOSH-APPROVED RESPIRATOR FOR DUST MUST BE WORN. IF RESPIRATORS ARE USED, A PROGRAM SHOULD BE INSTITUTED TO ASSURE COMPLIANCE WITH OSHA 29CFR 1910.134.

Ventilation:GOOD GENERAL VENTILATION SHOULD BE SUFFICIENT. TYPICALLY, 10 ROOM VOLUMES PER HR IS CONSIDERED GOOD GENERAL VENTILATION.

Protective Gloves:RUBBER/LATEX

Eye Protection:SAFETY GLASSES WITH SIDE SHIELD/GOGGLES

Other Protective Equipment:EYE WASH STATION, QUICK DRENCH SHOWER AND IMPERVIOUS CLOTHING

Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHING OR FOOTWEAR.

Supplemental Safety and Health

KEY1:T4. SEE PNI B FOR PART B. THIS PRODUCT HAS: A HIGH BIOCHEMICAL OXYGEN DEMAND, A HIGH POTENTIAL TO AFFECT AQUATIC ORGANISMS. AFTER DILUTION WITH A LARGE AMOUNT OF WATER, FOLLOWED BY WASTE TREATMENT, IT IS NOT EXPECTED TO CAUSE ADVERSE ENVIRONMENT EFFECTS.

===== Physical/Chemical Properties =====

HCC:T4

NRC/State Lic Num:NOT RELEVANT

Vapor Pres:NEGLIGIBLE

Spec Gravity:1.00

Viscosity:NOT RELEVANT

Evaporation Rate & Reference:NOT RELEVANT

Solubility in Water:COMPLETE

Appearance and Odor:LIGHT TAN SOLID - ODORLESS

Percent Volatiles by Volume:NEGLIG

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:EXCESSIVE HEAT

Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE, OXIDES OF SULFUR, OXIDES OF NITROGEN MAY BE FORMED.

===== Disposal Considerations =====

Waste Disposal Methods:DISCHARGE, TREATMENT OR DISPOSAL MAY BE SUBJECT TO FEDERAL, STATE OR LOCAL LAWS. CONTRACT WITH A LICENSED CHEMICAL DISPOSAL AGENCY.

Disclaimer (provided with this information by the compiling agencies):
This information

is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.