

SOUTHWEST PETRO-CHEM -- SF 871 1010 -- 9150-00-271-8427

=====
Product Identification
=====

Product ID:SF 871 1010

MSDS Date:01/01/1987

FSC:9150

NIIN:00-271-8427

MSDS Number: BDRWY

=== Responsible Party ===

Company Name:SOUTHWEST PETRO-CHEM

Emergency Phone Num:(913) 782-5800

CAGE:70878

=== Contractor Identification ===

Company Name:EXXON CO USA-SOUTHWEST GREASE BUSINESS UNIT

Address:1400 S HARRISO

N

Box:1974

City:OLATHE

State:KS

ZIP:66061

Country:US

Phone:913-656-3701/800-424-9300(CHEMTREC)

CAGE:70878

=====
Composition/Information on Ingredients
=====

Ingred Name:MINERAL OIL; CAS #64742-52-5

CAS:64742-52-5

RTECS #:PY8035000

ACGIH TLV:5MG/CUM(MIST)

Ingred Name:BARIUM SULFONATE; CAS #61790-48-5

Ingred Name:THICKENING AGENT

=====
Hazards Identification
=====

Effects of Overexposure:EYES:IRRITATION;SKIN:IRRITATION ON
PROLONGED/REPE

ATED CONTACT;INGEST:NAUSEA,HEAD,GI IRRITATION,DIARR

=====
===== First Aid Measures =====

First Aid:SKIN:WASH W.SOAP & H*2O EYES:FLUSH W. H*2O. INGESTED:GIVE 2 GLASSES H*2O; INDUCE VOMITING.CALL A PHYSICIAN. INHALE:REMOVE TO FRESH AIR. GIVE CPR/OXYGEN IF NEED. KEEP WARM & QUIET. REMOVE CONTAMINATED CLOTHING. IF UNCONS DO NOT TAKE ANYTHING BY MOUTH.

=====
===== Fire Fighting Measures =====

Flash Point:334F/168C (COC)
Extinguishing Media:CO*2, FOAM, DRY CHEM & H*2O FOG.
Fire Fighting Procedures:WEAR SELF-CNTD BRTHG,APP H*2O SPRAY TO COOL CONTR.
Unusual Fire/Explosion Hazard:BURNS WITH DENSE SMOKE.

=====
===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE IGNITION SOURCES. STOP LEAK. EVACUATE AREA.DO NOT TOUCH SPILLAGE. SM SPILL:ABSORB W. INERT ABSORBENT. PLACE IN CLOSED CONTAINER. FLUSH AREA W. WATER. LG SPILL: DIKE AHEAD FOR LATER DISPOSAL. NOTIFY AUTHORITIES.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED AREA. PROTECT FROM PHYSICAL DAMAGE.AVOID ANY PHYSICAL CONTACT. KEEP CONTAINERS TIGHTLY CLOSED
Other Precautions:AVOID CONTACT WITH SKIN,EYES & CLOTHING.WASH THOROUGHLY AFTER HANDLING.KEEP AWAY FROM FEED & FOOD PRODUCTS.LAUNDER CLOTHES BEFORE REUSE.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE SHOULD BE NEEDED
Ventilation:NO SPECIAL REQUIREMENTS W ADEQUATE VENT.
Protective Gloves:RUBBER/PLASTIC
Eye Protection:GOGGLES/FACE SHIELD
Other Protective Equipment:NORMAL WORK CLOTHING COVERING ARMS & LEGS.
Supplemental Safety and Health
MSDS FM MFR DATE:9/5/85; SPEC REFERENCE: MIL-L-3150C.

=====
===== Physical/Chemical Properties =====

HCC:V6
Spec Gravity:0.926
Solubility in Water:NEGLIGIBLE
Appearance and Odor:AMBER COLOR OIL.MINERAL OIL ODOR.

=====

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

STRONG OXIDIZING AGENTS.

Stability Condition to Avoid: EXCESSIVE HEAT & IGNITION SOURCES

Hazardous Decomposition Products: INCOMPLETELY BURNED CARBON PRODUCTS,
CO₂, CO.

===== Disposal Considerations =====

Waste Disposal Methods: KEEP IN COVERED DRUMS, PENDING DISPOSAL. HANDLE &
DISPOSE IN FULL COMPLIANCE WITH ALL APPLICABLE
INTERNATIONAL, FEDERAL, STATE, &
LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their

particular situation.